

ACCEPTED

OCT 11 1985

Under the Federal Insecticide, Fungicide, and Rodenticide Act, this product is registered with EPA Reg. # 200-105



ENDURANCE

OIL STAIN

THREE YEAR LIMITED WARRANTY

When applied according to label instructions, over a properly prepared surface, Glidden warrants that its ENDURANCE Oil Exterior Stain will not crack, peel or blister for 3 years from date of application. Unsatisfactory performance resulting from breakdown of previous coatings and/or substrates are not covered by this warranty. If this stain fails to perform as warranted, Glidden will supply an equal amount of stain, or refund the purchase price.

This Warranty specifically excludes labor or cost of labor. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

SEMI-TRANSPARENT EXTERIOR

DANGER! KEEP OUT OF REACH OF CHILDREN. COMBUSTIBLE.
See back panel for additional precautionary statements.

WATER REPELLEN
WITH PRESERVATIVE
WARRANTY PENETRATES GENUINELY
WOOD GRAIN SIDING SHAKES
SHINGLES TRIM BRACKETS ETC.

0726 SIERRA GREEN
ONE GALLON

PRECAUTIONARY STATEMENTS—HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear goggles and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water for 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, seal can tightly in water and use up or store in a closed metal container away from buildings and other combustible materials. **COMBUSTIBLE.** Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty containers. Do not dump into water or trash collection. Keep away from food and feed.

A durable wood preservative and water repellent semi-transparent exterior stain for above-ground use only. This penetrates into the wood to protect and enhance the wood grain beauty of all types of wood shingles, shakes, rough siding, porches, decks and railings. May also be used on wood lawn furniture. May be top coated with a clear exterior varnish if desired. Excellent when used on pilings, shakes and large areas of siding. Lumber pre-treated with commercial preservatives should weather one season to maintain absorption and/or lifting of the stain. **DO NOT USE ON PAINTED SURFACES.**

NOTE: DRAMATONE® Colorant must be added to Tint Bases before application. See Glidden Colorant Manual.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

MATERIAL PREPARATION

- Mix thoroughly, stirring with a smooth, rigid motion to assure color uniformity.
- Apply unthinned for one coat application.
- If necessary (when applying two coats), first coat may be thinned with up to one part by parts water. Do not thin with water, oil, other stains or paints.
- May be tinted with DRAMATONE Multi-Purpose Colorants only, as specified in Glidden Color Manual.

SURFACE PREPARATION

- **General and for New Wood**—All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax, or any other substances which might affect adhesion or performance. Putty all cracks, close large openings with caulk.
- **Remove mildew**—scrub with solution of one tablespoon dry powdered laundry detergent to one quart of water. For heavy mildew, use bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Scrub surfaces under eaves, porch ceilings or recesses to remove accumulated dirt/mildew. Make sure all surfaces are externally dry.
- **Previously Stained**—Use this product over old semi-transparent stain only. (If previous stain is "solid color" type, use DRAMATONE Exterior Solid Color Oil Stain.) **NOTE:** The original color will be deepened by a new application of this stain even when it is closely matched to the new color.

APPLICATION

- One gallon covers approximately 200-300 square feet on smooth surfaces and about 100-200 square feet on rough surfaces.
- Use on exterior surfaces only. Stir frequently during application.
- Always pretest on an inconspicuous area to assure desired results. Apply carefully to avoid dark hot marks.
- Stain is best applied by brushing, working well into surface. Roller and pad application should be supplemented by brushing on devices. Spray at only 15-20 lbs. pressure to avoid frothing. Use spray masks or hoods.
- **Horizontal Work**—Do only 4 to 6 boards at a time, extending each work area to structural breaks such as doors, windows or corners.
- **Vertical Work**—Do only 4 to 6 boards or one complete panel at a time, finishing fully from top to bottom.
- Do not apply when surface or atmospheric temperatures are less than 50°F.
- Dries to touch in 6-8 hours under normal conditions (70°F., 50% R.H.). Recoat after 12 hours minimum.
- Clean tools and equipment with No. 60 SPRED Brush & Roller Cleaner or paint thinner (mineral spirits).

NON-PHOTOCHEMICALLY REACTIVE

Handwritten signatures and notes:
J. J. [unclear]
[unclear]
[unclear]

ACCEPTED

OCT 11 1985

Federal District Court
Southern District of New York
New York, New York
Case No. 85-100-102

GB

SCM. GLIDDEN COATINGS & RESINS • Cleveland, Ohio 44116
DIVISION OF SCM CORPORATION

L. G. 569101