

U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (WH-567) WASHINGTON, D.C. 20460	EPA REGISTRATION NO. 200-120	DATE OF ISSUANCE SEP 29 1982
	TERM OF ISSUANCE	
	NAME OF PESTICIDE PRODUCT Emulsion of Oxok Maltin and Preservative 9.4% Translucent Oil 9.5% Clear Tint Base	

NOTICE OF PESTICIDE: REGISTRATION
 REREGISTRATION
*(Under the Federal Insecticide, Fungicide,
 and Rodenticide Act, as amended)*

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

THE WILCOX COMPANY
 2700 10th Avenue
 Cleveland, OH 44115

219609 / 161
 18

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(a)(7) by providing the following:

1. Submit an application and data required for registration/reregistration of your product under FIFRA sec. 3(b)(5) when the Agency requires all registrants of similar products to submit such data.
2. Add the phrase "EPA Registration No. 200-120" to your label in form and release the product for shipment.
3. Under the environmental hazard heading, add the following statement: "Do not use with water when licensing of equipment washwater".
4. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a full description of the required labeling.

If these conditions are not complied with, the registration of this product is canceled in accordance with FIFRA sec. 6(c). Your labeling is evidence of the manufacturer's acceptance of these conditions.

A copy of each of the label is enclosed for your records.

(Signature)
 TERRY A. ROSS
 Director, Registration Division
 U.S. Environmental Protection Agency
 Registration Division (WH-567)

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

PRECAUTIONARY STATEMENTS—HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

CAUTION! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash off with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water for 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. **COMBUSTIBLE.** Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.

A durable water repellent semi-transparent exterior stain to control fungal decay of wood. For above-ground use only. Penetrates into the wood to protect and enhance the wood grain beauty of all types of wood, decks and fencing. May also be used on wood lawn furniture. Lumber pre-treated with commercial preservatives should weather one season to minimize discoloration and for lifting of the stain. **DO NOT USE ON PAINTED SURFACES.**

NOTE: DRAMATONE® Colorant must be added to Tint Base before application. See Glidden color literature.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

MATERIAL PREPARATION

- Mix thoroughly, stirring with a smooth, lifting motion to assure color uniformity.
- Apply unthinned for one coat application.
- If necessary (when applying two coats), first coat may be thinned with up to one pint of paint thinner (mineral spirits) per gallon of stain. Do not thin with water, oils, other stains or paints.
- May be tinted with DRAMATONE Multi-Purpose Colorants only, as specified in Glidden color literature.

SURFACE PREPARATION


- **General and for New Wood**—All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax or any other contaminants that might affect adhesion or performance.
- **Remove mildew**—scrub with solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite type household bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Make sure all surfaces are internally dry.
- **Previously Stained**—Use this product over old semi-transparent stain only. **NOTE:** The original color will be deepened by a new application of this stain even when it is closely matched to the new color.

APPLICATION

- One gallon covers approximately 200-300 square feet on smooth surfaces, about 150-200 square feet on rough surfaces.
- Use on exterior surfaces only. Stir frequently during application.
- Always pretest on an inconspicuous area to assure desired results. Apply carefully to avoid dark lap marks.
- Stain is best applied by brushing, working well into surface. Roller and pad application should be supplemented by brushing to fill crevices. Spray at only 15-20 lbs. pressure to avoid frothing. **When spraying wear respiratory protection (NIOSH/MSHA TC23C) chemical cartridge or equivalent.**
- Do not apply when surface or atmospheric temperatures are less than 50°F.
- Dries to touch in 6-8 hours under normal conditions (70°F, 50% R.H.). Recoat after 12 hours minimum. May be walked upon after drying 16 hours minimum.
- Clean tools and equipment with No. 60 GLIDDEN® Brush & Roller Cleaner or paint thinner (mineral spirits). L.C.



THE GLIDDEN COMPANY
CLEVELAND, OHIO 44115



PANTONE®
424C



PANTONE®
682C



PANTONE®
491C



ENDURANCE

DECK STAIN & PRESERVATIVE

OUR MOST WATER REPELLENT STAIN

SEMI-TRANSPARENT OIL



Warranted/Protects & Preserves
Against Mildew & Rot

**CAUTION! KEEP OUT OF REACH
OF CHILDREN. COMBUSTIBLE.**
See back panel for additional precautionary statements.

9890 CLEAR TINT BASE
118 FL. OZ. (3 QT. 1 PT. 6 OZ.) 3.489 L

Active Ingredient
Benzoin Resin 10.0%
Benzoin Glycerite 10.0%
Propyl Glycol 10.0%
EPA Reg. No. 700-00 EPA Est. No. 000 PA 00,
No. GA 00, 000 CA 00, 000 IL 00, 000 TX 00

**ASSURED SATISFACTION
LIMITED WARRANTY**
Glidden warrants satisfaction when applied according to label instructions. If not satisfied as warranted, return the unused portion along with sales receipt to place of purchase. They will refund the price paid for the product or replace with product of equal value.
THIS WARRANTY SPECIFICALLY EXCLUDES LABOR OR COST OF LABOR FOR THE APPLICATION OF ANY STAIN. Some states do not allow the exclusion of incidental or consequential damages, so the limitation or exclusion contained in the above warranty may not apply to you.
This warranty gives you specific rights. There may also be other rights which vary from state to state.

Made in U.S.A. - Manufactured in America

