



ENDURANCE

DECK STAIN & PRESERVATIVE

OUR MOST WATER REPELLENT STAIN

SEMI-TRANSPARENT OIL



BEST AVAILABLE COPY

NON PHOTOCHEMICALLY REACTIVE

ASSURED SATISFACTION LIMITED WARRANTY

Glidden warrants satisfaction when applied according to label instructions. If not satisfied as warranted, return the unused portion along with sales receipt to place of purchase. They will refund the price paid for the product or replace with product of equal value.

THIS WARRANTY SPECIFICALLY EXCLUDES LABOR OR COST OF LABOR FOR THE APPLICATION OF ANY STAIN. Some states do not allow the exclusion of incidental or consequential damages, so the limitation or exclusion contained in the above warranty may not apply to you.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Warranted/Protects & Preserves Against Mildew & Rot

CAUTION! KEEP OUT OF REACH OF CHILDREN. COMBUSTIBLE.

See back panel for additional precautionary statements.

ACCEPTED

Active Ingredient: 2 parts 2-Acetyl-1-Pyrone
Inert Ingredients: 98 parts

EPA Reg. NO. 000-00 EPA Est. NO. 000-PA-00
000-GA-00 000-CA-00 000-IL-00 000-TX-00

9894 CEDARTONE
ONE GALLON 3.785 L

ANALYSIS
Pigment: TiO₂
Vehicle: Acrylic Resin and Oil
Solvent: Methyl Ethyl Solvent
Microcrystalline Wax
Additives
*Defined as hazardous 9894 78

Made in U.S.A. © 1987 The Glidden Co.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. **COMBUSTIBLE.** Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.

A durable water repellent semi-transparent, exterior stain to control fungal decay of wood. For above-ground use only. Penetrates into the wood to protect and enhance the wood grain beauty of all types of wood, decks and fencing. Lumber pre-treated with commercial preservatives should weather one season to minimize discoloration and/or lifting of the stain. **DO NOT USE ON PAINTED SURFACES.**

Do not use on wood that will be used in contact with food, feed or potable water or where prolonged skin contact will occur. Due to the presence of petroleum distillates in this product, do not use on lumber where dairy cattle or livestock can come in contact with the treated wood.

NOTE: DRAMATONE Colorant must be added to Tint Base before application. See Glidden color literature.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

9/1/88

MATERIAL PREPARATION

- * Mix thoroughly stirring with a smooth, lifting motion to assure color uniformity.
- * Apply unthinned for one coat application.
- * if necessary (when applying two coats), first coat may be thinned with up to one pint of paint thinner (mineral spirits) per gallon of stain. Do not thin with water, oils, other stains or paints.
- * May be tinted with DRAMATONE Multi-Purpose Colorants only, as specified in Glidden color literature.

SURFACE PREPARATION

- * General and for New Wood - All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax or any other contaminants that might affect adhesion or performance.
- * Remove mildew - scrub with solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite-type household bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Make sure all surfaces are internally dry.
- * Previously Stained - Use this product over old semi-transparent stain only. NOTE: The original color will be deepened by a new application of this stain even when it is closely matched to the new color. ✓

For best results and uniformity of appearance, retreat once every three years.

APPLICATION

- * One gallon covers approximately 200-300 square feet on smooth surfaces, about 150-200 square feet on rough surfaces.
- * Use on exterior surfaces only. Stir frequently during application.
- * Always pretest on an inconspicuous area to assure desired results. Apply carefully to avoid dark lap marks.
- * Stain is best applied by brushing, working well into surface. Roller and pad application should be supplemented by brushing to fill crevices. Spray at only 15-20 lbs. pressure to avoid frothing. When spraying wear respiratory protection (NIOSH/MSHA TC23C) chemical cartridge or equivalent.
- * Do not apply when surface or atmospheric temperatures are less than 60°F.

9/1/88

*Dries to touch in 6-8 hours under normal conditions (70° F., 50% R.H.). Recoat after 12 hours minimum. May be walked upon after drying 16 hours minimum.

*Cut wood prior to treatment if possible. If not, liberally apply two coatings of preservative to all joints, cracks, cut-ends, holes or other openings.

*Applying wood finishes often results in splashing or dripping. Cover desirable plants and shrubs to protect against possible injury.

*Clean tools and equipment with No. 60 GLIDDEN Brush & Roller Cleaner or paint thinner (mineral spirits).

GLIDDEN

THE GLIDDEN COMPANY
CLEVELAND, OHIO 44115

AN ICI COMPANY

9/1/88