

**NET CONTENTS: 5 GALLONS**

**FOR USE BY PEST CONTROL OPERATORS ONLY  
NOT FOR SALE TO THE GENERAL PUBLIC**

SOLID GARNET RED



**Aldrite<sup>®</sup> 4**

SOLID GARNET RED  
WITH A BLACK DROP SHADOW



**EMULSIBLE CONCENTRATE INSECTICIDE**

ACTIVE INGREDIENTS	BY WEIGHT
Aldrin .....	43.4%*
Petroleum Hydrocarbons .....	50.6%
<b>INERT INGREDIENTS</b> .....	6.0%
	<b>TOTAL 100.0%</b>

\*Equivalent to 41.2%w Hexachlorohexahydro-endo, exo-dimethanonaphthalene and 2.2%w Related Compounds.

**ACCEPTED**

AUG 1 1975

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 201-245 AA

**DO NOT STORE  
BELOW 32° F**

**WARNING!**

**KEEP OUT OF REACH OF CHILDREN.**

SOLID GARNET RED

See other precautions on back panel.

EPA REG. NO. 201-245 AA

**CONTAINS 4 LBS. ALDRIN PER GALLON**

**CODE 110 JG**

**Read the Directions and Precautions  
Carefully and Follow Them at all Times**

**PRECAUTIONS IN USING**

**WARNING! HAZARDOUS IF SWALLOWED, INHALED, OR ABSORBED THROUGH SKIN!** Do not breathe spray mist. Do not get in eyes, on skin or on clothing. Do not use or store near heat or open flame.

Wash thoroughly with soap and water after handling and before eating or smoking. Wear clean clothing. During commercial or prolonged exposure in spray-mixing and loading operations, wear clean synthetic rubber gloves and a mask or respirator of a type passed by the U.S. Bureau of Mines for aldrin protection.

In case of spillage on person or clothing, remove clothing immediately and flush skin or eyes with plenty of water; for eyes get medical attention. If swallowed, induce vomiting immediately and get medical attention.

Do not apply or allow to drift to areas occupied by unprotected humans or beneficial animals. Do not contaminate feed and foodstuffs.

This product is poisonous to fish and wildlife. Keep out of lakes, ponds, and streams. Do not apply in any manner not specified on the label.

**DESTROY USED CONTAINERS.** Empty containers as thoroughly as possible, then crush and bury.

**USE AND APPLICATION DIRECTIONS**

ALDRITE 4 Emulsible Concentrate can be used in conventional hydraulic sprayers and low-volume ground applicators. Mix this product thoroughly by agitation with sufficient water to provide uniform coverage of the soil surface. If allowed to stand, re-agitate before use. Use this product only for recommended purposes and at recommended dosages.

**TERMITE CONTROL:** To control termites dilute the required amount of this product with sufficient water to provide a mixture containing 0.5% w aldrin (approximately 1 pt. per 12 gals. of water) and apply at the following rates.

**(A) Buildings with Crawl Spaces**

- (1) Apply 2 gallons per 5 linear feet to critical areas only under the house, such as along the inside of foundation walls, around piers, sewer pipes, conduits, etc. Trench according to directions in part (2) below.

- (2) Along the outside of foundation walls, dig a narrow trench with a band no wider than six inches, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside those foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 ft. apart.

- (3) Apply 1 gallon per 10 square feet of soil surface under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the grade level. Where crawl spaces exist, treat as described in part (1) above.

- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

**(B) Buildings with Concrete Slab on the Ground**

- (1) Apply 1 gallon per 10 sq. ft. as an overall treatment under the slab as well as under attached porches, entrance platforms, utility entrances and similar situations where slab or fill is at grade level. In case of washed gravel, cinders, or similar coarse material, increase dosage by at least one-half. If soil is treated and the concrete slab is not poured shortly thereafter on the same day, a polyethylene sheeting or other waterproof material shall be placed over the treated soil.

- (2) Apply 2 gallons per 5 linear feet to critical areas only under the slab, such as along the inside of foundation walls, around sewer pipes, conduits, etc. Trench as in part (3) below.

- (3) Along the outside of foundation walls, dig a narrow trench with a band no wider than six

inches no deeper than the top of the footings, but no deeper than 15 inches, unless the footing is much deeper in some places on account of the slope of the land, then treat as under (A)(2).

- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

**(C) Buildings with Basements**

- (1) Apply 1 gallon per 10 sq. ft. as an over all treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.

- (2) Apply 2 gallons per 5 linear ft. to critical areas only under the basement floorings, as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers, etc. Trench according to directions in part (3) below.

- (3) Along the outside of foundation walls, dig a narrow trench with a band no wider than six inches and no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of the footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.

- (4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

**DO NOT STORE  
BELOW 32° F**

SOLID GARNET RED

# SHELL CHEMICAL COMPANY

A Division of Shell Oil Company,  
AGRICULTURAL CHEMICALS  
SAN RAMON, CALIF. 94583

**NOTICE OF WARRANTY** ———— **SOLID GARNET RED**

SHELL CHEMICAL COMPANY MAKES NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PURPOSE, OR OTHERWISE, EXPRESS OR IMPLIED, concerning this product or its uses which extend beyond the use of the product under normal conditions in accord with the statements made on this label.