

Vinyl-Cote™ No-Cop™

ANTI-FOULING COATING

7082 Red (178-R-401)

ACTIVE INGREDIENT	
bis (Tributyltin) Oxide	9.7%
INERT INGREDIENTS	90.3%
Total	100.0%

CONTAINS METHANOL AND PETROLEUM DISTILLATES

EPA Establishment No. 200-TX-1
EPA Registration No. 200-57


FOR COMMERCIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN.

DANGER!

See side panel for additional precautionary statements.

ONE GALLON 3.785L



PHYSICAL OR CHEMICAL HAZARDS
Do not use or store near heat or open flame.

DANGER! FLAMMABLE.
MAY IGNITE EXPLOSIVELY.

Keep away from heat, sparks and open flame. Do not smoke. Vapors may ignite explosively. Extinguish all flames, burners, stove, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Use portable explosion-proof lighting and ventilating equipment connected to exterior self contained power source. Nonexplosion proof equipment must be placed well away from areas where vapors may collect. Use non ferrous tools and wear conductive and nonsparking shoes in areas where explosion hazards exist. Vapors may spread long distances.

USE ONLY WITH ADEQUATE VENTILATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT THE CURRENT PROTECTIVE MAINTENANCE COATINGS DATA SHEET AND MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT. EMERGENCY PHONE: (216) 826 5566.

LIMITATION OF LIABILITY

We guarantee our product to conform to Glidden's specifications. **WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE.** Liability, if any, is limited to replacement of the product or refund of the purchase price. **LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**



**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS
(AND DOMESTIC ANIMALS)
DANGER!**

Corrosive. Causes skin burns. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants, and hat. Causes eye irritation. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. This product may be a dermal sensitizer.

Avoid contact with skin, eyes, or clothing. Avoid breathing vapor, spray mist, dust or chips from sanding. Wash thoroughly with any soap and water after handling and before eating or smoking. Use with adequate ventilation.

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. **Get medical attention.**

Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage.

If on skin: Wash with plenty of soap and water. **Get medical attention.**

If in eyes: Flush with plenty of water. **Get medical attention if irritation persists.**

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. **Get medical attention.**

While spraying and or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

ENVIRONMENTAL HAZARD

This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

Made in U.S.A.
1984 SCM Corp

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

A copper-free fast drying polyvinyl chloride type anti-fouling coating for marine use in both fresh and salt water.

GENERAL - Do not apply at film thicknesses in excess of those specified. Do not apply directly to bare metal, oil, fog, mist, or rain. Do not use for potable water or food contact service. Do not add unspecified solvents or thinners to equipment immediately after use with Vinyl Cote Standard Reducer No. 7090, Hot Weather Reducer No. 7091. Refer to this product's Protective Maintenance Coatings Data Sheet for detailed recommendations, and primer on new surfaces.

MATERIAL PREPARATION Mix thoroughly using a heavy duty power mixer with a surface scraping action for free flowing.

NEW CONSTRUCTION Consult Glidden specifications for surface preparation, protective coatings, and maintenance of steel marine equipment before application of VINYL-COTE™ No Cop Anti-Fouling Coating. VINYL-COTE™ Intermediate coats at any time after application providing the surface is clean and free from contaminants.

REFRESHER COAT As soon as vessel is dry docked and before hull dries, remove contamination. When surface is clean or No. 7091 solvent, spot prime, apply build coats as necessary and apply complete refresher coat of Anti-Fouling.

APPLICATION Apply by spray. Use other methods only when absolutely necessary. Recommended application of VINYL-COTE Anti-Fouling at a minimum dry film thickness of 2 mils. If more than one coat is applied, allow one hour between coats. Vessel may be launched one hour after application is completed.

THINNING Use No. 7090 or No. 7091 reducers for spray. Do not reduce for brush or roll application.

NOTE: If application is desired over coatings other than the recommended VINYL-COTE System, consult your distributor.

IMPORTANT: Do not store or apply at temperature below 50°F.

STORAGE AND DISPOSAL

Keep closures tight and upright to prevent leakage. Keep container closed when not in use. Store below 100°F in closed containers as they may explode when exposed to extreme heat or fire. In case of spillage, absorb with inert material at an approved waste disposal facility. Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE DISPOSAL

Pesticide waste is toxic. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal law. Do not be dispersed by use according to label instructions, contact your State Pesticide or Environment Department, or Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a safe manner according to approved State and local procedures.