

NET CONTENTS
ONE GALLON

Tobacco States
BRAND

4-Lb. Aldrin Emulsion

for Termite Control

ACTIVE INGREDIENTS:	By Weight
Aldrin	41.22%*
Aromatic Petroleum Solvent	54.78%
INERT INGREDIENTS	4.00%
Total	100.00%

*Equivalent to 39.16% hexachlorohexahydro-endo, exo-dimethanonaphthalene and 2.06% related compounds.

WARNING: Keep out of reach of children.

See other warnings on back panel.

Read the directions and useage warnings carefully and follow them at all times

(Use and Application directions continued)

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

(B) BUILDINGS WITH CONCRETE SLAB ON THE GROUND

(1) Apply 1 gallon per 10 sq. ft. as an over-all treatment under the slab as well as under attached porches, entrance platforms, utility entrances and similar situation where slab or fill is at grade level. In case of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. If soil is treated and the concrete slab is not poured shortly thereafter on the same day, a polyethylene sheeting or other waterproof material shall be placed over the treated soil.

(2) Apply 2 gallons per 5 linear feet to critical areas only under the slab, such as along the inside of foundation walls, around sewer pipes, conduits, etc. Trench as in part (3) below.

(3) Along the outside of foundation walls, dig a narrow trench no deeper than the top of the footings, but no deeper than 15 inches, unless the footing is much deeper in some places on account of the slope of the land, then treat as under (A) (2).

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footings.

(C) BUILDINGS WITH BASEMENTS

(1) Apply 1 gallon per 10 sq. ft. as an over-all treatment under the basement flooring as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab fill is at the grade level. In case of washed gravel, cinders or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.

(2) Apply 2 gallons per 5 linear feet to critical areas only under the basement floorings, as well as porches and entrances having crawl spaces, such as along the inside of foundation walls, around sewer pipes, conduits, piers etc. Trench according to directions in part (3) below.

(3) Along the outside of foundation walls dig a narrow trench, with a band no wider than six inches, such trench to be dug no deeper than the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench 30 inches deep is a maximum depth required alongside foundations where the top of footings is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12" to 15" deep and rod to footing, spacing the holes about 1 foot apart.

(4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. It is best to apply the chemical near the footing.

NOTICE OF WARRANTY

Tobacco States Chemical Company, Inc., makes no warranty of merchantability, fitness, for any purpose or otherwise express or implied concerning this product or its uses which extend beyond the use of the product under normal conditions in accord with the statements made on this label.

EPA Reg. No. 226-239

EPA Est. 226-KY-1

TOBACCO STATES CHEMICAL CO., INC.
LEXINGTON, KENTUCKY 40501