2568-99 11/15/2012 1/4

U S ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue NW
Washington, D C 20460

NOTICE OF PESTICIDE
x Registration
__ Reregistration
(under FIFRA as amended)

EPA Reg Number	Date of Issuance
2568-99	NOV 15 2012

Term of Issuance
Expires 12/13/14

Name of Pesticide Product
Coating
60A5000 Seavictor 50 Antifouling Red

Name and Address of Registrant (include ZIP Code)

Jotun Paints, Inc
9203 Highway 33
Belle Chase, LA 70037

Note Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce In any correspondence on this product always refer to the above EPA registration number

On the basis of information furnished by the registrant the above named pesticide is hereby registered/reregistered under the Federal Insecticide Fungicide and Rodenticide Act

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency In order to protect health and the environment the Administrator on his motion may at any time suspend or cancel the registration of a pesticide in accordance with the Act The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others

This product is conditionally registered in accordance with FIFRA sec 3(c)(7)(A) provided that you

1 Submit and/or cite all data required for registration of your product under FIFRA sec 3(c)(5) when the Agency requires all registrants of similar products to submit such data, and submit acceptable responses required for re-registration of your product under FIFRA section 4

2 Make the labeling changes listed below before you release the product for shipment

a Add the phrase "EPA Registration Number '2568-99 "

Signature of Approving Official

M Swindell

Marshall Swindell
Product Manager-33
Regulatory Management Branch I
Antimicrobials Division (7510P)

Date
NOV 15 2012

EPA Form 8570-6

b Place the appropriate EPA Establishment No on the product labeling

3 Submit the protocol and study by June 1, 2005, of this date stamped of this Notice of Conditional Registration

Inhalation Monitoring Study*

*(Intent Measure airborne concentrations of Sea-Nine 211 during Ship painting operations with a representative marine antifoulant (MAF) paint Prior to initiating the monitoring study, submit the Study Design for Agency review to ensure compliance with Agency Methodologies for conducting such studies Also, note that this study is intended to support only the presence of 3% active ingredient in end-use paint formulations)

The data being required as a condition of the registration must be submitted, reviewed, and found to be acceptable by June 1st, 2010 As you are aware the manufacturer of this active ingredient is responsible for gathering the above data to support all end-use products

This conditional registration will expire on December 31, 2014 If you fail to satisfy the conditions imposed on the registration, EPA may issue a Notice of Registration to cancel under Section 6 (e) of FIFRA

4 Submit two copies of the revised final printed labeling before you release the product for shipment

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec 6(e) Your release for shipment of the product constitutes acceptance of these conditions

A stamped copy of the label is enclosed for your records Submit one (1) copy of your final printed labeling prior to release of this product for shipment If you have any questions concerning this letter, please contact Karen Leavy at (703)-308-6237

Sincerely,

Marshall Swindell
Product Manager 33
Regulatory Branch I
Antimicrobials Division (7510P)

Enclosure (Stamped Labeling)

NOV 15 2012
Under the Federal Insecticide Fungicide and Rodenticide Act as amended for the pesticide registered under EPA Reg No. 2568-99

BATCH 51118419 DOM 08/01/2008

Health	3
Fire hazard	3
Reactivity	1
Protective Equipment	x

D O T SHIPPING NAME PAINT

D O T HAZARD CLASS FLAMMABLE LIQUID

D O T HAZARD IDENTIFICATION NUMBER UN1263

3GFDRD

E P A REG NO 2568 99
E P A EST NO 002568 LA 001

Jotun Paints Inc
9203 Highway 23
Belle Chasse LA 70037

STORAGE AND DISPOSAL

DO NOT CONTAMINATE WATER FOOD OR FEED BY STORAGE OR DISPOSAL KEEP CONTAINER CLOSED WHEN NOT IN USE IN CASE OF SPILLAGE ABSORB WITH INERT MATERIAL AND DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC IMPROPER DISPOSAL OF EXCESS PESTICIDE SPRAY MIXTURE OR RINSATE IS A VIOLATION OF FEDERAL LAW IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE

CONTAINER DISPOSAL

NONREFILLABLE CONTAINER

DO NOT REUSE OR REFILL THIS CONTAINER OFFER FOR RECYCLING IF AVAILABLE TRIPLE RINSE CONTAINER PROMPTLY AFTER EMPTYING TRIPLE RINSE AS FOLLOWS EMPTY THE REMAINING CONTENTS INTO APPLICATION EQUIPMENT OR A MIX TANK AND DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP FILL THE CONTAINER 1/10TH FULL WITH THINNER AND RECAP SHAKE FOR 10 SECONDS POUR RINSATE INTO APPLICATION EQUIPMENT OR A MIX TANK OR STORE RINSATE FOR LATER USE OR RECYCLING DRAIN FOR 10 SECONDS AFTER THE FLOW BEGINS TO DRIP REPEAT THIS PROCEDURE TWO MORE TIMES THEN OFFER FOR RECYCLING OR RECONDITIONING OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL OR BY OTHER APPROVED STATE AND LOCAL PROCEDURES

ANTIFOULING
SEAFORCE 300 AV
DARK RED

ACTIVE INGREDIENT CUPROUS OXIDE	39 59%
ACTIVE INGREDIENT 4 5 DICHLORO 2 N OCTYL 4 ISOTHIAZOLIN 3 ONE	2 19%
INERT INGREDIENTS	58 22% *
	100 00%

METALLIC COPPER EQUIVALENT 35 16%

CONTAINS PETROLEUM DISTILLATES XYLENE OR XYLENE RANGE AROMATIC SOLVENTS

KEEP OUT OF THE REACH OF CHILDREN

DANGER

FOR USE IN COMMERCIAL OR GOVERNMENT SHIPYARDS ONLY NOT FOR USE BY PRIVATE APPLICATORS OR MARINAS NOT FOR USE ON STATIONARY STRUCTURES

NOT SOLD FOR USE IN AIR POLLUTION REGULATION AREAS PHOTOCHEMICALLY REACTIVE PER RULE 102

SEE FIRST AID AND OTHER PRECAUTIONS ON SIDE PANEL

Net 20 LITERS (5 28 GALLONS)

3/4

NOV 15 2012
Registered under EPA reg No. 2568-99

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS
DANGER

CORROSIVE CAUSES IRREVERSIBLE EYE DAMAGE HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN AVOID CONTACT WITH EYES SKIN OR CLOTHING WEAR A FULL FACE SHIELD AVOID BREATHING VAPOR MIST DUST OR CHIPS FROM PAINTING OR SANDING WHILE SPRAYING PAINT OR SANDING BOAT SURFACE WEAR A SUPPLIED AIR OR POWERED AIR PURIFYING RESPIRATOR (PAPR) APPROVED BY NIOSH FOR USE WITH PAINTS AND COATINGS

WEAR A TYVEK HOODED COVERALL OR THE EXACT EQUIVALENT COVERALLS BENEATH THE TYVEK HOODED COVERALLS IMPERVIOUS GLOVES AND IMPERVIOUS FOOTWEAR THAT PROTECTS THE LOWER LEG REMOVE CONTAMINATED CLOTHING AND DISCARD AFTER EACH USE DO NOT REUSE WASH THOROUGHLY WITH SOAP AND WATER AFTER HANDLING AND BEFORE EATING OR SMOKING

ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH AND AQUATIC INVERTEBRATES DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT INTO LAKES STREAMS PONDS ESTUARIES OCEANS OR OTHER WATER UNLESS IN ACCORDANCE WITH THE REQUIREMENTS OF A NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT AND THE PERMITTING AUTHORITY HAS BEEN NOTIFIED IN WRITING PRIOR TO DISCHARGE DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT TO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE LOCAL SEWAGE TREATMENT PLANT AUTHORITY FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICES OF THE EPA DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER DISPOSE OF PAINT DEBRIS IN AN APPROVED LANDFILL WEAR PROTECTIVE CLOTHING AND SUPPLIED AIR RESPIRATOR IN ACCORDANCE WITH THE PRECAUTIONARY STATEMENTS ABOVE WHEN HANDLING PAINTING OR REMOVING THIS PAINT

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME

FIRST AID	
IF IN EYES	HOLD EYES OPEN AND RINSE SLOWLY AND GENTLY FOR 15 20 MINUTES REMOVE CONTACT LENSES IF PRESENT AFTER THE FIRST 5 MINUTES AND THEN CONTINUE RINSING CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE
IF SWALLOWED	IMMEDIATELY CALL A POISON CONTROL CENTER OR DOCTOR DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTER OR DOCTOR DO NOT GIVE ANY LIQUID TO THE PERSON DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSIOUS PERSON
IF ON SKIN OR CLOTHING	TAKE OFF CONTAMINATED CLOTHING RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15 20 MINUTES CALL A POISON CONTROL CENTER OR DOCTOR FOR TREATMENT ADVICE
IF INHALED	MOVE A PERSON TO FRESH AIR IF PERSON IS NOT BREATHING CALL 911 OR AN AMBULANCE THEN GIVE ARTIFICIAL RESPIRATION PREFERABLY MOUTH TO MOUTH IF POSSIBLE CALL A POISON CONTROL CENTER OR DOCTOR FOR FURTHER TREATMENT ADVICE
OTHER	HAVE THE PRODUCT CONTAINER OR LABEL WITH YOU WHEN CALLING A POISON CONTROL CENTER OR DOCTOR OR GOING FOR TREATMENT
MEDICAL EMERGENCY NUMBER 1 800 424 9300	
NOTE TO PHYSICIAN Contains petroleum distillate – vomiting may cause aspiration pneumonia	

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

ANTIFOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING I E BARNACLES GRASS ALGAE TUBE WORMS MUSSELS AND SNAILS ON HULLS OF BOATS AND VESSELS IN SALT BRACKISH AND FRESH WATER WHICH WOULD SUSTAIN SUCH GROWTH WHEN USED ON ALUMINUM HULLS A BARRIER COAT OF TWO COATS OF EPOXY COATING ATTAINING AT LEAST 12 MILS DFT MUST BE APPLIED FIRST CONSULT WITH YOUR REPRESENTATIVE FOR SPECIFIC BARRIER RECOMMENDATIONS A MINIMUM OF TWO COATS OF THIS PRODUCT IS RECOMMENDED FOR BEST PERFORMANCE THIS PRODUCT IS NOT FOR USE ON PLEASURE CRAFTS OR USE IN MARINAS

SURFACE PREPARATION

BEFORE APPLICATION OF ANTIFOULING ALL SURFACES MUST BE DRY AND CLEANED OF DIRT DUST OIL RUST LOOSE PAINT SALT RESIDUES AND OTHER CONTAMINANTS STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI CORROSIVE BARRIER COATS

MIXING

BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY

APPLICATION

APPLY BY BRUSH ROLL OR SPRAY CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 95°F) AIRLESS SPRAY OR REGULAR COLD SPRAY APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN DO NOT PAINT IN COLD OR DAMP WEATHER

THINNING

NORMALLY NO THINNING REQUIRED WHERE THINNING IS NECESSARY USE JOTUN THINNER 7

DRYING TIME

AT 70 F AND 50% R H ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS AND A MINIMUM OF 8 HOURS BEFORE IMMERSION

REFER TO PRODUCT MATERIAL SAFETY DATA BULLETIN AVAILABLE UPON REQUEST FOR FURTHER SAFETY AND HANDLING INFORMATION

THE VOC OF THIS PAINT IS
396 GRAMS/LITER (3 3 LBS/GAL)