

Manufactured by KLENZADE PRODUCTS, Division of Economics Laboratory, Inc., Osborn Bldg., St. Paul, Minnesota 55102



48454

KANCEL

formula HC-34

EPA Reg. No. 292-74AA

FOR CONTROL OF BACTERIAL SLIME IN BREWERY PASTEURIZERS & WARMERS

Active ingredients:

n-alkyl (50% C₁₄, 40% C₁₇, 10% C₁₆) dimethyl benzyl ammonium chloride 9.00%
Tetrasodium ethylene diamine tetraacetate 0.80%

Inert ingredients:

90.20%

DANGER: KEEP OUT OF REACH OF CHILDREN.

CORROSIVE. CAUSES EYE DAMAGE AND SKIN IRRITATION. DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WEAR GOGGLES OR FACE SHIELD AND RUBBER GLOVES WHEN HANDLING. HARMFUL IF SWALLOWED. AVOID CONTAMINATION OF FOOD.

FIRST AID: IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES OR SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. FOR EYES, CALL A PHYSICIAN. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

IF SWALLOWED, DRINK PROMPTLY A LARGE QUANTITY OF MILK, EGG WHITES, GELATIN SOLUTION OR IF THESE ARE NOT AVAILABLE, DRINK LARGE QUANTITIES OF WATER. AVOID ALCOHOL. CALL A PHYSICIAN IMMEDIATELY.

NOTE TO PHYSICIAN: PROBABLE MUCOSAL DAMAGE MAY CONTRAINDICATE THE USE OF GASTRIC LAVAGE. MEASURES AGAINST CIRCULATORY SHOCK, RESPIRATORY DEPRESSION AND CONVULSION MAY BE NEEDED.

GENERAL DIRECTIONS

Manual Addition

1. In uses with either tunnel pasteurizers or container warmers that have been thoroughly cleaned first, add 15 oz. Kancel to 200 gal. of water. This will provide an initial concentration of 600 ppm of product
2. Kancel should be added on daily basis in proportion to the amount of make-up water required.
3. Kancel should be added to each compartment of the pasteurizer or warmer at the pump well to provide equal dispersion throughout.
4. It is recommended that Klensch be used in conjunction with Kancel to provide corrosion protection.

Automatic Addition

Kancel, when added proportionately to water, usage should be preset at a concentration of 400 ppm of product — 10 oz. to 200 gal. of water.

Dilution Table

10 oz. of Kancel to 200 gal. of water equals 400 ppm of product. 15 oz. of Kancel to 200 gal. of water equals 600 ppm of product.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

DO NOT RE-USE EMPTY DRUM. RETURN TO DRUM RECONDITIONER OR DESTROY BY PERFORATING OR CRUSHING AND BURYING IN A SAFE PLACE.

NET CONTENTS: 50 GALS.

APRIL 13, 1973