

CONTENTS 1 GALLON

# MARTIN'S TERMI-TREAT<sup>®</sup> WOOD PRESERVER

**RECOMMENDED FOR**  
EXPOSED WOOD WORK      SHINGLE ROOFS  
FOUNDATIONS              WOODEN GATES  
BARNs                              FENCING

Controls Rot Fungi, Termites, and Certain  
Other Wood Inhabiting Insects

**CAUTION: KEEP OUT OF REACH OF CHILDREN.  
SEE BACK PANEL FOR OTHER CAUTIONS.**



Manufactured By  
**C. J. MARTIN COMPANY**  
Nacogdoches, Texas 75741

## Directions for Use of Martin's Termi Treat

As a WOOD PRESERVER -- two thorough applications of Termi Treat should be made with a spray or brush especially to all wood coming in contact with the ground

For TERMITE CONTROL -- treatment should be made prior to use of wood in construction, two applications to all foundation timbers. For further protection, the soil immediately adjacent to the foundation and approximately 6 inches below the surface should be thoroughly treated. Use 2 gallons per 5 cubic feet of infested soil.

For DIP TREATMENT timbers should be soaked 12 to 24 hours. Posts may be treated by putting on end in 50 gallon drum or barrel and filling with Termi Treat. Reverse to treat opposite end.

**CAUTION:** Harmful if swallowed. Avoid breathing vapor, fumes or spray mist. Avoid contact with skin. May cause skin irritation. Do not use or store near heat or open flame. Do not reuse empty container. Return to drum reconditioner or destroy by perforating or crushing and burying in safe place.

U.S.D.A. Reg. No. 299-129

07911

1971  
INSECTICIDE  
U.S. DEPT. OF AGRICULTURE  
U.S. GOVERNMENT PRINTING OFFICE