

Huntolene is a highly refined floor maintainer with bacteriostatic properties. It is excellent for use on sealed wood floors. Huntolene mixes readily with water, which permits quick and easy removal of soil from the mop head.

DIRECTIONS

Sweep floors daily with Huntolene treated mops. Use Huntolene as directed below.

INITIAL TREATMENT: Spray or sprinkle one ounce Huntolene to each 6 inches of mop length on new or freshly cleaned mops. Allow Huntolene to penetrate 24 hours before using.

SUBSEQUENT TREATMENT: Spray one ounce Huntolene to each 12 inches of mop length. Allow to stand over-night before using.

Weighing mop heads is a much more accurate guide.


Initial Treatment: 1 ounce Huntolene to each 4 ounces cotton. Subsequent Treatment: 1 ounce Huntolene to each 8 ounces cotton.

When mop is dirty, rinse in water, then soak in Floor-San solution. Rinse thoroughly and dry. Huntolene is emulsifiable, so mop head will be clean, fluffy and absorbent. Re-treat clean mop head. "Classified by Underwriters' Laboratories, Inc., as to Fire Hazard Only. See UL Index of Products Classified as to Specific Hazards Only. Huntolene is rated in a class between Kerosene and Paraffin Oil."

ACTIVE INGREDIENTS: Dilauryl Dimethyl Ammonium Bro-

CAUTION: KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. If swallowed, do not induce vomiting. Call physician. Avoid contact with skin and eyes. In case of contact with eyes, flush with plenty of water for 15 minutes. For eyes, get immediate medical attention. In case of skin contact, wash thoroughly with soap and water. Contains: Petroleum Distillate. Keep container closed when not in use. Avoid contamination of food.



E.P.A. Reg. No. 303-56 SL 6M DC11 Where research leads to better products

HUNTINGTON LABORATORIES, INC. • P. O. Box 710, Huntington, Indiana 46750

Dallas, Texas 75215 . Lansdale, Pennsylvania 19446 . Bramalea, Ontario Litho In U. S. A.

Huntington Laboratories, Inc. P.O. Box 710 Huntington, Indiana 46750 January 11, 1972

