

TOWER ALGAECIDE 15

Net Weight 10.00 lb.
Gross Weight 11.29 lb.
Weight per gallon 8.58 lb.
Weight of active ingredient per gallon 1.29 lb.

APPLICATION

Tower Algaecide 15 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial dosage of 4.0 to 10.0 fluid ounces of Tower Algaecide 15 per 1000 gallons of water to provide a concentration of 5 to 10 parts per million of active ingredient based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent dosages of 4.0 to 10.0 fluid ounces of Tower Algaecide 15 per 1000 gallons of water to provide 5 to 10 parts per million of active ingredient should be employed every 2 to 4 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slime additions should be made on the sump of water cooling towers.

CAUTION:

KEEP OUT OF REACH OF CHILDREN

Do not inhale dust. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food. This product is toxic to fish. Do not discharge directly where it will drain into lakes, streams, or ponds. Do not contaminate water, clothing, equipment or food with wastes. See only a directed label. For more safety data, contact your distributor or contact the manufacturer at the address on the label.

334-408

NET GAL

