

DIRECTIONS

WATERENE used in air wash and humidifying systems provides additional control of lint and dust, keeps eliminator plates clean and nozzles open.

Descale system if necessary with LESTER SCALEX. Flush system with fresh water. Recharge.

1. Initial Charge:

Add 1 lb. WATERENE per 100 gallons of water directly to the sump. Stir to dissolve if necessary. Start circulation of water in system.

2. Maintenance Charge:

Maintenance charge depends on the amount of daily make up water lost to bleed-off. For each 100 gallons of water lost daily to bleed-off, add 0.4 lb. WATERENE for algae control. Feed WATERENE by proportion pump or by daily addition to tower sump in an overflow bucket to level out dissolution of powder into system.

USDA REGISTRATION NO. 337-37

337-37
Cameraman's Note
Poor Copy

WATERENE

Combined water conditioner, corrosion preventive and algae control for water recirculating systems such as air wash, humidifying or water cooling towers for air conditioning.

Active Ingredients:

Sodium Pentachlorophenate 8.5%
Related Compounds 1.5%

Inert Ingredients:* 90%

*But active for corrosion and water hardness control

CAUTION: Keep out of reach of children.

See right panel for additional caution statements.

CONTENTS _____ LBS.

MANUFACTURED BY

LESTER LABORATORIES, INC.
2370 Lawrence Street
Atlanta, Georgia 30344

Eas
hyc
of
of

Cle
per
cor
rins

Die
No
tori

WAR
swa
Do
Was
con

Thi
lak

1200

237-37

Cameraman's Note
Poor Copy

Other Lester Products of Interest

SCALEX

Easy-to-use, new liquid scale remover containing no hydrochloric or other fuming acids, for rapid reduction of head pressure and complete descaling and desliming of air conditioning systems.

METALENE

Cleaner for air-flow cooling coils, condenser coils, and permanent type filters. Non-flammable, non-toxic. Highly concentrated; dilute with water before use. Cold water rinseable.

TETLES

Dielectric solvent for electric motors, switches, etc. No rinse is needed. Approved by Underwriters' Laboratories. Contains no toxic carbon tetrachloride.

WARNING: Causes skin irritation. Harmful if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Do not re-use container. Destroy when empty.

This product is toxic to fish. Keep out of lakes, streams and ponds.

WATERENE

Combined water conditioner, corrosion preventive and algae control for water recirculating systems such as air wash, humidifying or water cooling towers for air conditioning.

Active Ingredients:	
Sodium Pentachlorophenate	8.5%
Related Compounds	1.5%
Inert Ingredients:*	90%

*But active for corrosion and water hardness control

CAUTION: Keep out of reach of children.
See right panel for additional caution statements.

CONTENTS _____ LBS.
MANUFACTURED BY

LESTER LABORATORIES, INC.
2370 Lawrence Street
Atlanta, Georgia 30344