



ACC  
Oct. 21, 1974  
337-59

# ALGAECIDE C

FOR CONTROLLING ALGAE, FUNGI AND BACTERIA IN  
RECIRCULATING COOLING WATER SYSTEMS. FOAM  
AND DUSTING CONTROLLED.

ACTIVE INGREDIENTS:	
Sodium Pentachlorophenate	79%
Sodium salts of other chlorophenols	11%
INERT INGREDIENTS:	10%

### DIRECTIONS

#### INTERMITTENT METHOD

**INITIAL DOSE:** When the system is noticeably fouled, apply 1 3 lb. to 2 3 lbs. of ALGAECIDE C per 1000 gallons of water in the system. Repeat until control is achieved. Apply at a point in the system where the product will be uniformly mixed.

**SUBSEQUENT DOSE:** When microbial control is evident, add 1 6 lb. to 1 3 lb. of ALGAECIDE C per 1000 gallons of water in the system as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun. Apply at a point in the system where the product will be uniformly mixed.

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

### DANGER: KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on this label.

**FIRST AID:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

DO NOT REUSE CONTAINER DESTROY WHEN EMPTY.

E.P.A. REGISTRATION NO. 337-59

NET WEIGHT      LBS.

SOLD BY

**LESTER LABORATORIES**

ATLANTA, GEORGIA, U.S.A. 30344

BEST DOCUMENT AVAILABLE

# TOWER ALG

Active ingredients .....

Disodium cyanodithioiridocarbonate .....

Potassium N-methyldithiocarbamate .....

Inert ingredients .....

Weight per gallon .....

Weight of active ingredients per gallon .....

## APPLIC

Tower Algacide N 17.5 is used to inhibit the recirculating commercial and industrial cooling towers. Tower Algacide N 17.5, systems must be cleaned of slime and other deposits. Then the system should receive a dose of 3.3 to 6.6 fluid ounces of Tower Algacide N 17.5 in the system. Repeat the initial dosage until the water is clear. Additions of 1.1 to 6.6 fluid ounces of Tower Algacide N 17.5 to the water should be made every 1 to 5 days or as recommended. The frequency depends on the relative amount of bleedoff and the water temperature. Slud additions of Tower Algacide N 17.5 to the cooling towers.

## WA

## KEEP OUT OF REA

Causes eye damage and skin irritation. Do not breathe dust. Wear goggles or face shield and rubber gloves. Do not swallow. Avoid contamination of food.

FIRST AID: In case of contact, immediately flush with water for at least 15 minutes. For eyes, call a physician before reuse.

If swallowed, give patient doses of powdered milk, or raw egg white, milk, gruel, or flour and water. Do not give mustard in warm water. Call a physician if necessary.

Do not reuse empty drum. Return to drum recycler for crushing and burying in a safe place. This product is toxic to fish. Treated effluents should not be drained into lakes, streams, ponds, or public waterways. See instructions on this label.

Do not contaminate water by cleaning of equipment.

# NET

EPA Est. 334-IL-1

EPA Reg. No. 334-415AA





AC  
Set 2/19/74  
377 59

# ALGAECIDE C

**FOR CONTROLLING ALGAE, FUNGI AND BACTERIA IN  
RECIRCULATING COOLING WATER SYSTEMS. FOAM  
AND DUSTING CONTROLLED.**

ACTIVE INGREDIENTS:		
Sodium Pentachlorophenate	.....	79%
Sodium salts of other chlorophenols	.....	11%
INERT INGREDIENTS:	.....	10%

### DIRECTIONS

#### INTERMITTENT METHOD

**INITIAL DOSE:** When the system is noticeably fouled, apply 1 3 lb. to 2 3 lbs. of ALGAECIDE C per 1000 gallons of water in the system. Repeat until control is achieved. Apply at a point in the system where the product will be uniformly mixed.

**SUBSEQUENT DOSE:** When microbial control is evident, add 1 6 lb. to 1 3 lb. of ALGAECIDE C per 1000 gallons of water in the system as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun. Apply at a point in the system where the product will be uniformly mixed.

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

### DANGER: KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on this label.

**FIRST AID:** In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

DO NOT REUSE CONTAINER. DESTROY WHEN EMPTY.

E.P.A. REGISTRATION NO. 337-59

NET WEIGHT      LBS.

SOLD BY

