

Zehring

PENTASEAL

3 TO 1 CONCENTRATE

**WATER REPELLENT
WOOD PRESERVATIVE**

Stops Rot and Decay

*Protects Against Warping, Swelling, Shrinking
and Checking*

Kills Termites, Powder Post Beetles

Paintable

Mix 1 gal. Pentaseal Concentrate with 3 gals. Paint Thinner which gives a ready-to-use solution containing 5% Pentachlorophenol.

DIRECTIONS

Best results will be had by soaking the wood for at least 3 minutes, but if not possible apply liberally with at least two flowing coats by brush or spray. Cover all possible surfaces. Allow at least 24 hours drying time before top coats of paint are applied.

USES

Pentaseal treated wood will prevent decay, rot, blue mold and mildew; kill boring insects and provide a clean, odorless, sealed surface to receive oil stain, paint or varnish. The water-resistant surface protects wood from warping, checking, staining, swelling and shrinking caused by moisture changes.

Use Pentaseal treatment on shingles, doors, windows and frames, joists, sills, plates, stairs, porches, steps, subflooring, interior trim, furniture, wall paneling, fences, flooring, cabinets, screens, storm sash and most other wood around the home.

Kill powder-post beetles and termites in furniture, flooring and structural lumber.

Stops Rot and Decay
Protects Against Warping, Swelling, Shrinking
and Checking

Kills Termites, Powder Post Beetles
Paintable

Mix 1 gal. Pentaseal Concentrate with 3 gals. Paint Thinner which gives a ready-to-use solution containing 5% Pentachlorophenol.

DIRECTIONS

Best results will be had by soaking the wood for at least 3 minutes, but if not possible apply liberally with at least two flowing coats by brush or spray. Cover all possible surfaces. Allow at least 24 hours drying time before top coats of paint are applied.

USES

Pentaseal treated wood will prevent decay, rot, blue mold and mildew; kill boring insects and provide a clean, odorless, sealed surface to receive oil stain, paint or varnish. The water-resistant surface protects wood from warping, checking, staining, swelling and shrinking caused by moisture changes.

Use Pentaseal treatment on shingles, doors, windows and frames, joists, sills, plates, stairs, porches, steps, subflooring, interior trim, furniture, wall paneling, fences, flooring, cabinets, screens, storm sash and most other wood around the home.

Kill powder-post beetles and termites in furniture, flooring and structural lumber with applications of Pentaseal. Such insects will not attack wood so treated.

WARNING

May cause skin irritation. Harmful if swallowed. Do not breathe vapor fumes or spray mist. Avoid contact with eyes, skin or clothing. In case of contact wash copiously with warm water. Flammable. Do not use near open flame.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS GALLONS

Active Ingredients:		--To be revised
Pentachlorophenol*	18%	per application
Petroleum Hydrocarbons	57%	
Inert Ingredients:		
Water Repellents, Special Solvents	25%	
Total	100%	

*as defined by federal specification TT W-570.

ZEHRUNG CHEMICAL CO.

PORTLAND, OREGON

197
6-39