

DU PONT Protective Coatings

FOR MAINTENANCE AND MARINE

CHLORINATED RUBBER ANTI-FOULING RED

360-Y-782

ACTIVE INGREDIENTS:

Cuprous Oxide25.0%
(Total copper as metallic 22.2%)
Bis (Tri-n-Butyltin) Oxide1.7%

INERT INGREDIENTS73.3%

EPA Reg. No. 352-393
EPA Est. No. 352-PA-1

Contains Petroleum Distillate And Less
Than 3% Carbon Tetrachloride.

**KEEP OUT OF REACH OF CHILDREN
DANGER**

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS**

Before using read Du Pont Material Safety Data Sheet for this product.

CORROSIVE. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling. Harmful or fatal if swallowed. Do not breathe vapor or spray mist. Use only with adequate ventilation. If engineering and administrative control of air contamination is not feasible, use approved respirator.

FIRST AID: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician. Flush skin with water.



ENVIRONMENTAL HAZARDS

Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. Keep away from heat, sparks and flame. Keep container closed when not in use. In case of fire, use water spray, foam, dry chemical or CO₂.

DIRECTIONS FOR USE


It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

This product is an anti-fouling paint for steel ship bottoms that provides below-the-water protection from barnacles and other fouling marine animals in tropical, Gulf Coast and northern waters.

DISPOSAL

Do not reuse empty container. Wrap container and put in trash container.

In case of spill, absorb and dispose of in accordance with local regulations. 688



PAINT LIQUID

FOR USE IN COMMERCIAL SHIPYARDS ONLY

5 GALLONS/18.925 Liters

E. I. du Pont de Nemours & Co. (Inc.) • Fabrics & Finishes Department
Maintenance Finishes • Wilmington, DE 19898

MADE IN U.S.A.

DOCUMENT AVAILABLE

2M-300-057-1279