PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS

DANGER

FOR USE IN COMMERCIAL SHIPYARDS ONLY

Before using read Du Pont Material Safety Data Sheet for this product

Corrosive. Causes skin burns. Wear protective clothing such as gloves, longsleeved cotton shirt, long pants, and hat Causes eye irritation. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. This product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing vapor or spray mist. While spraying paint or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation:

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE.

Keep away from heat or open flume. Keep container closed when not in use. In case of fire, use water spray, foam, fry chemical or CO₂.



Protective Coatings

FOR

MAINTENANCE AND MARINE

EXTENDED LIFE ANTI-FOULING RED

360-785

ACTIVE INGREDIENTS:

Cuprous Oxide (Total copper as metallic 33.2%)
Bis (Tri-n-Butyltin) Oxide (Total tin as metallic .6%)
INERT INGREDIENTS

Contains Petroleum Distillate And Less Than 3% Carbon Tetrachlorid

KEEP OUT OF REACH OF CHIERREN OF

DANGER

If swallowed: Drink promptly a large quantity of milk egg whites gelatin solution or, if these are not available, drink large grantites of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

If on skin: Wash with plenty of soap and water. Get medical attention.

If in eyes: Flush with plenty of water. Get medical attention if irritation persists.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Est. No. 352—PA-1 EPA Est. No. 352—GA-1 EPA Est. No. 352—CA-1 EPA Est. No. 352—NJ-3 EPA Est. No. 352—0H-03 EPA Reg. No. 352—426

5 GALLONS/18.92 Liters

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling


This product is an anti-fouling paint for steel ship bottoms that provides below-the-water protection from barnacles and other fouling marine animals in tropical. Gulf Coast and northern waters.

STORAGE AND DISPOSAL

Pesticide, spray mixture, or rinsate water that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

Metal containers should be triple rinsed (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

SEE TECHNICAL BULLETIN FOR THIS PRODUCT



1M 3068 057 0884