

DESCRIPTION

Coopersote Creosote Oil is a time-tested liquid wood preserver. Recommended for preservation of all types of exposed unpainted lumber such as fence posts, shingles, underground sills, sub frames, piers, bridges, boardwalks, etc. Protects against decay, rot and wood borers. For protection against termites, wood should be treated prior to use in construction.

APPLICATION

Lumber to be treated should be dry and seasoned before applying. When applying by brush, two flowing coats of Coopersote Creosote Oil applied at temperature about 60°F is recommended. Where wood will be in direct contact with the ground, such as fence posts and heavy timbers, the wood should be peeled of bark and immersed in Coopersote for a period of 12 to 48 hours.

When applying by brush, apply with stiff brush and cover knots, checked places and end of timber thoroughly.

COVERAGE

Approximately 100 square feet per gallon.

COOPERSOTE CREOSOTE OIL

Durable Preservative for Wood

Efficient Protection Against

Rot or Decay

and

Wood Borers

Successful Usage of Over 30 Years

ENVIRONMENTAL PRECAUTIONS

This product is toxic to fish and wildlife. Keep out of any body of water. Do not apply where runoff is likely to occur. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

SINCE 1915

THE **C-4** BRAND

Coopersote Creosote Oil

**PRESERVES AND LENGTHENS LIFE OF WOOD
BRUSH OR SPRAY APPLICATION
STAINS A RICH CHESTNUT BROWN COLOR**

ACTIVE INGREDIENTS

Coal Tar Distillate 86%

Coal Tar Acids 6%

INERT INGREDIENTS 8%

DANGER: KEEP OUT OF REACH OF CHILDREN AND ANIMALS

Do not get in eyes, on skin or clothing. Wash thoroughly. Keep away from food. May be fatal if swallowed or absorbed through skin. May produce severe burns. Avoid breathing spray mist. Flammable — Keep away from heat and open flame.

READ PRECAUTIONS ON SIDE PANEL

EPA Registration Number 363-15

STORE IN WARM PLACE

EPA Est. 363-PA-1

— GALLONS U. S. MEASURE

IMPORTANT

Coopersote remains in liquid about 40°F temperature. Keep from freezing while in storage, otherwise setting occurs. If exposed to temperatures below 40°F, place in warm area for 24 hours or more and shake well. Do not use on wood which is to be painted afterwards as creosote bleeds through most paints. Use Decays-Not Clear Wood Preservative for areas which are to be painted.

DANGER

Use with adequate ventilation. Avoid prolonged breathing of vapors and direct contact with the skin. Use protective cream or vaseline and wear goggles when spraying. To eliminate discomfort, wash with soap and water and apply vaseline.

If swallowed, do not induce vomiting, but call a physician at once. If product gets into eyes, flush with plenty of cold water and call a physician at once.

Do not reuse empty container. Wash equipment and containers thoroughly with water and detergent and dispose of wastes by burying in non-crop lands away from water supplies. Containers should be disposed of by punching holes in them and burying with wastes.

This product will burn. Do not use, pour, spill, or store near heat or open flame. For outside use only. This product has a strong odor. Do not use where odor may penetrate to cause an odor problem. Do not use inside barns, silos, or other such structures where it may contact food and feed or livestock. Close container after each use.

NOTICE:

This product is offered in good faith, however, the seller is not responsible for damages of any kind caused by careless or improper handling or use.

AND
USE IT YOURSELF

COOPERS CREEK CHEMICAL CORP
WEST CONSHOHOCK, PENNSYLVANIA, U.S.A.

USE THE **C-4** BRAND
AND
USE IT YOURSELF

ACCEPTED