

Precautionary Statements
Hazardous to Humans and Domestic Animals

WARNING

Harmful or Fatal if Swallowed
or Absorbed through Skin
Causes Eye and Skin Irritation
Vapor Harmful — Combustible
May Produce Severe Burns
Avoid Breathing Vapor

This product must be used in a well-ventilated area. Do not use or store near heat or open flame. Avoid breathing of vapors and direct contact with skin. Do not breathe vapor or spray mist. Keep contents and freshly treated articles away from flame, food, and plants. Do not use in poultry houses or wood that will be in contact with humans, food, or growing plants. Do not get in eyes, on skin or clothing. Use protective cream, goggles and protective clothing before using and when working with this product and handling freshly treated lumber.

FIRST AID: If swallowed, DO NOT induce vomiting. Call a Physician at once. If inhaled, remove to fresh air. If not breathing, give artificial respiration, if breathing is difficult, give oxygen. Call a physician at once. For eye contact, flush eyes at once with plenty of cool water for 15 minutes and get medical attention. In case of skin contact, remove from skin at once by wiping with waterless hand cleaner followed by soap and water. Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water or wet lands. Do not apply where runoff is likely to occur. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS

This product is a combustible liquid and will burn. Do not use, pour, spill, or store near heat or open flame. Do not use in poultry houses, inside barns, silos, or other structures where it may contact food feed, livestock or growing plants. Product has a strong odor. Do not use where odor may penetrate to cause an odor problem. For outside or exterior use only.

COOPERSOTE CREOSOTE OIL
Durable Preservative for Wood
Efficient Protection Against
Rot or Decay
and
Wood Bore
Successful Usage of Over 30 Years

NOTICE

This product is offered in good faith, however, the seller is not responsible for damages of any kind caused by careless or improper handling or use.

FOR EXTERIOR USE ONLY

SINCE 1915

THE C-4 BRAND Coopersote Creosote Oil

PRESERVES AND LENGTHENS LIFE OF WOOD
BRUSH OR DIP APPLICATION
STAINS A RICH CHESTNUT BROWN COLOR

ACTIVE INGREDIENTS

Coal Tar Distillate 86%

Coal Tar Acids 6%

INERT INGREDIENTS 8%

KEEP OUT OF REACH OF CHILDREN

WARNING

Do not get in eyes, on skin or clothing. Wash thoroughly. Keep away from food. May be fatal if swallowed or absorbed through skin. May produce severe burns. Avoid breathing vapor mist. Combustible—Keep away from heat and open flame.

ACCEPTED

APR 6 1984

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 363-15

See Side Panel
for Additional Precautionary Statements
EPA Registration Number 363-15

STORE IN WARM PLACE

EPA Est. 363-PA-1
5 GALLONS U.S. MEASURE

REST AVAILABLE COPY

DIRECTIONS FOR USE

Apply this product only as specified on this label. It is a violation of Federal Law to use this product in a manner inconsistent with labeling.

GENERAL USE CLASSIFICATION

Coopersote Creosote Oil is a time-tested liquid wood preservative. Recommended for preservation of all types of exposed unpainted lumber such as fence posts, shingles, underground sills, pier bridges. Protects against decay, rot, and wood borers. For protection against termites, wood should be treated prior to use in construction.

APPLICATION

1. Treating may be done by brush or dip. Be sure to use a protective cream on your skin before using and read the precautionary statement.
2. Lumber to be treated should be dry and seasoned before applying. When applying by brush, two flowing coats of Coopersote Creosote Oil applied at temperatures about 60°F is recommended. Use a stiff brush and cover knots, checked places, and end of timber thoroughly.
3. Where wood will be in direct contact with ground, such as fence posts and heavy timbers, the wood should be peeled of bark and immersed in Coopersote for a period of 12 to 48 hours.

COVERAGE

Approximately 100 square feet per gallon

IMPORTANT

Coopersote remains in liquid about 40°F temperatures. Keep from freezing while in storage, otherwise settling occurs. If exposed to temperatures below 40°F, place in warm area for 24 hours or more and shake well. Do not use on wood which is to be painted afterwards as creosote bleeds through most paints. Use Decays—N Clear Wood Preservative for areas which are to be painted.

STORAGE

Combustible Liquid. Store in closed containers in a cool, well ventilated area. Wear protective neoprene rubber gloves, chemical safety goggles and protective clothing before opening and applying. Avoid contact with skin. If product is leaking or has been spilled, use an absorbent or sand and scrape up. Dispose in an approved chemical disposal facility. Do not use or store near heat or open flame. Close container after each use. Not for use or storage in or around the home.

DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Do not reuse empty container. Triple rinse (or equivalent). Puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Wiping with waterless hand cleaner followed by soap and water.
Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water or wet lands. Do not apply where runoff is likely to occur. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS

This product is a combustible liquid and will burn. Do not use, pour, spill, or store near heat or open flame. Do not use in poultry houses, inside barns, silos, or other structures where it may contact food, feed, livestock or growing plants. Product has a strong odor. Do not use where odor may penetrate to cause an odor problem. For outside or exterior use only.

COOPERSOTE CREOSOTE OIL
Durable Preservative for Wood
Efficient Protection Against
Rot or Decay
and
Wood Borers
Successful Usage of Over 30 Years

NOTICE

This product is offered in good faith, however, the seller is not responsible for damages of any kind caused by careless or improper handling or use.

FOR EXTERIOR USE ONLY

STAINS A RICH CHESTNUT BROWN COLOR

ACTIVE INGREDIENTS

Coal Tar Distillate 86%
Coal Tar Acids 6%

INERT INGREDIENTS 8%

KEEP OUT OF REACH OF CHILDREN

WARNING

Do not get in eyes, on skin or clothing. Wash thoroughly. Keep away from food. May be fatal if swallowed or absorbed through skin. May produce severe burns. Avoid breathing vapor mist. Combustible—Keep away from heat and open flame.

ACCEPTED

APR 6 1984

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 363-15

See Side Panel

for Additional Precautionary Statements
EPA Registration Number 363-15

STORE IN WARM PLACE

EPA Est. 363-PA-1

5 GALLONS U.S. MEASURE

USE THE C-4 BRAND
AND
C-4 YOURSELF

MANUFACTURED BY

COOPERS CREEK CHEMICAL CORP.

WEST CONSHOHOCKEN, PENNSYLVANIA, U.S.A. 19380

DIRECTIONS FOR USE

Apply this product only as specified on this label. It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

GENERAL USE CLASSIFICATION

Coopersote Creosote Oil is a time-tested liquid wood preserver. Recommended for preservation of all types of exposed unpainted lumber such as fence posts, shingles, underground sills, piers, bridges. Protects against decay, rot, and wood borers. For protection against termites, wood should be treated prior to use in construction.

APPLICATION

1. Treating may be done by brush or dip. Be sure to use a protective cream on your skin before using and read the precautionary statement.
2. Lumber to be treated should be dry and seasoned before applying. When applying by brush, two flowing coats of Coopersote Creosote Oil applied at temperatures about 60 F is recommended. Use a stiff brush and cover knots, checked places and end of timber thoroughly.
3. Where wood will be in direct contact with ground, such as fence posts and heavy timbers, the wood should be peeled of bark and immersed in Coopersote for a period of 12 to 48 hours.

COVERAGE

Approximately 100 square feet per gallon.

IMPORTANT

Coopersote remains in liquid about 40°F temperatures. Keep from freezing while in storage, otherwise settling occurs. If exposed to temperatures below 40°F, place in warm area for 24 hours or more and shake well. Do not use on wood which is to be painted afterwards as creosote bleeds through most paints. Use Decays—Not Clear Wood Preservative for areas which are to be painted.

STORAGE

Combustible Liquid. Store in closed containers in a cool, well-ventilated area. Wear protective neoprene rubber gloves, chemical safety goggles and protective clothing before opening and applying. Avoid contact with skin. If product is leaking or has been spilled, use an absorbent or sand and scrape up. Dispose in an approved chemical disposal facility. Do not use or store near heat or open flame. Close container after each use. Not for use or storage in or around the home.

DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

Do not reuse empty container. Triple rinse (or equivalent). Puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

USE THE C-4 BRAND
AND
C-4 YOURSELF

5 3 6
0 0 0 0

363-15 1-1081

Precautionary Statements
Hazardous to Humans and Domestic Animals

WARNING

**Harmful or Fatal if Swallowed
or Absorbed through Skin
Causes Eye and Skin Irritation
Vapor Harmful — Combustible
May Produce Severe Burns
Avoid Breathing Vapor**

This product must be used in a well-ventilated area. Do not use or store near heat or open flame. Avoid breathing of vapors and direct contact with skin. Do not breathe vapor or spray mist. Keep contents and freshly treated articles away from flame, food, and plants. Do not use in poultry houses or wood that will be in contact with humans, food, or growing plants. Do not get in eyes, on skin or clothing. Use protective cream, goggles and protective clothing before using and when working with this product and handling freshly treated lumber.

FIRST AID: If swallowed, DO NOT induce vomiting. Call a Physician at once. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician at once. For eye contact, flush eyes at once with plenty of cool water for 15 minutes and get medical attention. In case of skin contact, remove from skin at once by wiping with waterless hand cleaner followed by soap and water. Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water or wet lands. Do not apply where runoff is likely to occur. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS

This product is a combustible liquid and will burn. Do not use, pour, spill, or store near heat or open flame. Do not use in poultry houses, inside barns, silos, or other structures where it may contact food feed, livestock or growing plants. Product has a strong odor. Do not use where odor may penetrate to cause an odor problem. For outside or exterior use only.

COOPERSOTE CREOSOTE OIL
Durable Preservative for Wood
Efficient Protection Against
Rot or Decay
and
Wood Borens
Successful Usage of Over 40 Years

NOTICE

This product is offered in good faith, however, the seller is not responsible for damages of any kind caused by careless or improper handling or use.

FOR EXTERIOR USE ONLY

SINCE 1915

THE C-4 BRAND Coopersote Creosote Oil

**PRESERVES AND LENGTHENS LIFE OF WOOD
BRUSH OR DIP APPLICATION
STAINS A RICH CHESTNUT BROWN COLOR**

ACTIVE INGREDIENTS

Coal Tar Distillate	86%
Coal Tar Acids	6%
INERT INGREDIENTS	8%

KEEP OUT OF REACH OF CHILDREN

WARNING

Do not get in eyes, on skin or clothing. Wash thoroughly. Keep away from food. May be fatal if swallowed or absorbed through skin. May produce severe burns. Avoid breathing vapor mist. Combustible—Keep away from heat and open flame.

ACCEPTED

APR 6 1984

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 363-15

See Side Panel
for Additional Precautionary Statements
EPA Registration Number 363-15

STORE IN WARM PLACE

EPA Est. 363-PA-1
5 GALLONS U.S. MEASURE

BEST AVAILABLE COPY

**USE THE C-4 BRAND
AND
C-4 YOURSELF**

MANUFACTURED BY
COOPERS CREEK CHEMICAL CORP.
WEST CONSHOHOCKEN, PENNSYLVANIA, U.S.A. 19386

DIRECTIONS FOR USE

Apply this product only as specified on this label. It is a violation of Federal Law to use this product in a manner inconsistent with labeling.

GENERAL USE CLASSIFICATION

Coopersote Creosote Oil is a time-tested liquid wood preservative. Recommended for preservation of all types of exposed wood, including lumber such as fence posts, shingles, underground sill plates, bridges. Protects against decay, rot, and wood borers. For protection against termites, wood should be treated prior to use in construction.

APPLICATION

1. Treating may be done by brush or dip. Be sure to use a skin cream on your skin before using and read the precautionary statement.
2. Lumber to be treated should be dry and seasoned before using. When applying by brush, two flowing coats of Coopersote Creosote Oil applied at temperatures about 60°F is recommended. Use a stiff brush and cover knots, checked places, and end of timber thoroughly.
3. Where wood will be in direct contact with ground, such as posts and heavy timbers, the wood should be peeled or sanded and immersed in Coopersote for a period of 12 to 48 hours.

COVERAGE

Approximately 100 square feet per gallon.

IMPORTANT

Coopersote remains in liquid about 40°F temperatures. It may freeze while in storage, otherwise settling occurs. If temperatures below 40°F, place in warm area for 24 hours and shake well. Do not use on wood which is to be painted, as creosote bleeds through most paints. Use Deco Clear Wood Preservative for areas which are to be painted.

STORAGE

Combustible Liquid. Store in closed containers in a cool, well-ventilated area. Wear protective neoprene rubber gloves, safety goggles and protective clothing before opening and avoid contact with skin. If product is leaking or has been spilled, use an absorbent or sand and scrape up. Dispose in an approved disposal facility. Do not use or store near heat or open flame. Close container after each use. Not for use or storage in the home.

DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess spray mixture, or residue is a violation of Federal Law. If the product cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Region for guidance.

Do not reuse empty container. Triple rinse (or equivalent) and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**USE THE C-4 BRAND
AND
C-4 YOURSELF**