



CREOSOTE

WOOD

PRESERVATIVE

CAUTION
COMBUSTIBLE

KEEP OUT OF REACH OF CHILDREN

SEE ADDITIONAL PRECAUTIONS ON SIDE PANEL

MANUFACTURED FOR
ELROY TURPENTINE CO.

SUN. OF E. E. ZIMMERMAN CO.
SWAINSBORO, GA. 30401

EPA EST. NO. 374G401

EPA REG. NO. 371-7

ACTIVE INGREDIENTS: CREOSOTE COAL TAR-100%

NET 5 U.S. GALLONS

CAUTION
COMBUSTIBLE

KEEP OUT OF REACH OF CHILDREN

DO NOT USE, POUR, SPILL OR SCORE NEAR HEAT OR OPEN FLAME.
USE WITH ADEQUATE VENTILATION. DO NOT SMOKE WHILE USING.

Harmful if swallowed or absorbed through the skin. May cause severe burns. Do not breathe vapor. Do not get in eyes, on skin or clothing. Wash thoroughly with warm water and soap after handling. Wear protective clothing and rubber gloves when handling freshly treated lumber.

ENVIRONMENTAL CAUTION: This product is harmful to fish and wildlife. Keep out of lakes streams, and ponds. Do not contaminate water supplies by cleaning of equipment or disposal of wastes.

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard it in a safe place.

FIRST AID: If swallowed, drink promptly a large quantity of milk, raw egg white, gruel, or corn starch paste. Follow with an emetic such as a tablespoon of mustard in a glass of water. Call a physician.

DIRECTIONS

Apply this product only as specified on this label. Treat wood after all cuts are made and before use in structures. Treat wood against termites, powder post beetles, carpenter ants and wood rotting fungi by applying two flow coats of Creosote Oil to all lumber. Fence posts, poles and heavy wood members must be free of bark, dry and well seasoned. Immerse in Creosote Oil 12 to 48 hours for protection against wood rotting fungi. Do not use treated wood inside dairy barns, silos or other structures where it may contact food, feed or live stock.