

ACCEPTED

3-68

FEDERAL INSECTICIDE AND RODENTICIDE ACT
ECONOMIC PERSON REGISTER

390-4

PETTIT

marine  paint

ANTI-FOULING

1645

VINYLCIDE

RED

ONE U.S. QUART LIQ.

WARNING! FLAMMABLE.
See cautions elsewhere on label.

PETTIT PAINT CO., INC.

PETTIT OLD SALEM VINYLCIDE ANTI-FOULING PAINT

This is a hard plastic type of very strong anti-fouling paint which incorporates the most recent developments in the marine field. VINYLCIDE paint is manufactured for use on the bottom of steel, wood or fiberglass boats for protection against barnacles, teredo worms and other forms of marine growths. VINYLCIDE produces an exceptionally hard smooth surface that may be buffed to a high polish with fine #1 steel wool for extra speed. **DO NOT USE ON ALUMINUM BOATS.**

DIRECTIONS

The bottom to be painted should be dry and old paint thoroughly cleaned. For best results the old paint should be removed especially if it is the soft anti-fouling type. Stir the paint thoroughly at first and then occasionally during application. Allow at least four hours drying time between coats and at least three hours after the final coat before launching.

WOODEN HULLS: Prime all bare wood with PETTIT VINYL RED UNDERCOATER reduced to brushing consistency with #140 SPECIAL THINNER. Air dry 4 hours; sand lightly. Apply two coats of VINYLCIDE RED.

STEEL: Apply one coat of PETTIT METAL PRIMER. Follow with two coats of PETTIT VINYL RED UNDERCOATER. Finish with two coats of VINYLCIDE.

FIBERGLASS: Sand and apply one coat of PETTIT VINYL RED UNDERCOATER as directed, followed by two coats of VINYLCIDE.

Use #140 SPECIAL THINNER for thinning and cleaning.

USDA Reg. No. 390-4

DANGER  **POISON**

HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE!

CONTAINS COPPER AND PETROLEUM DISTILLATE. DO NOT INDUCE VOMITING. Do not apply on window sills, toys, furniture, or interior surfaces which may be chewed by children. Avoid prolonged contact with skin and breathing of vapor or spray mist. Wash thoroughly after handling and before eating or smoking. **FLAMMABLE.** Keep away from heat, sparks and open flame. Close container after each use.

Use with adequate ventilation.

KEEP OUT OF THE REACH OF CHILDREN.

ONE QUART U.S. STANDARD

IMPERIAL MEASURE 33 FL. OZ.

SAN LEANDRO, CALIF. BELLEVILLE, N. J.

APCF
4-1

PETTIT

marine  paint

PETTIT OLD SALEM VINYLICIDE ANTI-FOULING PAINT

ANTI-FOULING

CAUTION
KEEP OUT OF THE
REACH OF CHILDREN.
OTHER WARNINGS
ON BACK PANEL

1645

ACTIVE INGREDIENTS
Cuprous Oxide..... 55.20%
INERT INGREDIENTS..... 44.80%
100.00%
COPPER AS METALLIC... 49.80%

VINYLCIDE RED

ONE US GALLON

WARNING! FLAMMABLE!
See instructions on container.

DANGER

PETTIT PAINT CO., INC.

SAN LEANDRO, CALIF. BELLEVILLE, N. J.