



ANTI-FOULING

1342

GREEN

TROPICOP

CAUTION

- 15 METALLIC. 14.00%

PETTIT TROOK OF ANTI FOR ENGLISHING

.

DANGER **

.

PETTIT PAINT CO., INC.

SAN LEANDRO, CALIF. BELLEVILLE, N. J.

PETTIT marine () paint

ANTI-FOULÏNG

1342

GREEN

COPPER

TROPICOP

NET 32 FL.OZ.(1 QT.)

CAUTION KEEP OUT OF THE REACH OF CHILDREN.
OTHER WARNINGS ON BACK PANEL

PETTIT PAINT CO., INC.

PETTIT TROPICOP ANTI-FOULING PAINT

This is a plastic type of strong anti-fouling paint which incorporates the latest research developments in the marine field.

TROPICOP GREEN should be used on wooden boats only. Both provide positive, protection against barnacles, teredo worms and other marine growths. TROPICOP GREEN develops its bright green color after two weeks immersion.

DO NOT USE ON ALUMINUM BOATS.

DIRECTIONS

The bottom to be painted should be dry and the old paint thoroughly cleaned. Old paint in poor condition should be removed.

Stir the paint thoroughly at first and ther occasionally during application.

Allow at least six hours drying time between coats and after the final coat before launching.

WOODEN HULLS — Prime all bare wood with PETIT'S RED LEAD PRIMER and dry overnight, sand lightly. Apply two coats of TROPICOP GREEN. On repaint work apply two coats of TROPICOP.

Use PETTIT'S = 120 BRUSHING THINNER for thinning, if necessary, and for cleaning brushes.

USDA Reg. No. 390-11

DANGER 🕏



HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

CONTAINS COPPER, ARSENIC AND PETROLEUM DISTILLATE. DO NOT INDUCE VOMITING. Do not apply on window sills, toys, furniture, or interior surfaces which may be used by children. Avoid prolonged contact with skin and breathing vapor or spray mist. Wash thoroughly after handling and before eating or smoking. Keep away from heat and open flame. Close container after each use.

Use with adequate ventilation. KEEP OUT OF THE REACH OF CHIEDREN

ONE QUART U.S. STANDARD

IMPERIAL MEASURE 33 FL. OZ.

SAN LEANDRO, CALIF. BELLEVILLE, N. J.