

ACCEPTED
June 17, 1971
ALL INSECTICIDE
PARENTICIDE ACT
POISON REGISTER.
Comments

390-17

PETTIT
marine  *paint*

ANTI-FOULING

1643
PACIFIC
SPECIAL
ANTI-FOULING
RED

100%

NET 32 FL. OZ. (1 QT.)

CAUTION KEEP OUT OF THE REACH OF CHILDREN.
OTHER WARNINGS ON BACK PANEL

PETTIT PAINT CO., INC.

SAN LEANDRO, CALIF. BELLEVILLE, N. J.

PACIFIC SPECIAL ANTI-FOULING RED

This new copper anti-fouling paint has been formulated for specific use in West Coast waters. Extensive testing on work boats and pleasure craft has shown many months of positive protection against marine growth.

DIRECTIONS

The bottom to be painted with this anti-fouling paint should be sanded or scraped off as thoroughly as possible. For new wood or any bare wood, prime with PETTIT'S RED LEAD PRIMER. This prime coat should dry 24 hours before the first coat of anti-fouling paint is applied. Two coats of anti-fouling paint should be applied, allowing 6 hours to overnight dry between coats. The boat should be launched within 48 hours after the final coat is applied.

USD. REG. NO. 390-17

CAUTION

HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE!

CONTAINS COPPER AND PETROLEUM DISTILLATE. DO NOT INDUCE VOMITING. Do not apply on window sills, toys, furniture, or interior surfaces which may be used by children. Use with adequate ventilation. Avoid contact with skin and breathing of vapor or spray mist. Wash thoroughly after handling and before eating or smoking. Keep away from heat, sparks and open flame. Close container after each use. Do not reuse empty container. Destroy it by perforation or crushing. Bury or discard in a safe place.

KEEP OUT OF REACH OF CHILDREN

IMPERIAL MEASURE 33 FL. OZ.

ACCEPTED WITH COMMENTS

PETTIT

marine paint



UNEPOXY

ANTI FOULING

1920

BRONZE TROPIC FORMULA

NET 32 FL.OZ.(1 QT.)

CAUTION KEEP OUT OF THE REACH OF CHILDREN.
OTHER WARNINGS ON BACK PANEL

PETTIT PAINT CO., INC.

SAN LEANDRO, CALIF. BELLEVILLE, ILL.

ACTIVE INGREDIENTS

Copper Powder 35.66%

Bis(tri-n-butyltin)
Oxide 4.85%

**INERT
INGREDIENTS** 59.49%

USDA # 390-18

UNEPOXY BRONZE

Unepoxy is an effective hard racing antifouling boat bottom paint for various waters. It can be applied over PETTIT'S VINYLICIDE RED and most aged non-antifouling hard racing finishes. A small test area of Unepoxy on aged hard racing finishes is recommended to determine adhesion and compatibility to the old finish. Old, soft, or semi-hard antifouling paints should be removed for best adhesion. Allow a minimum of 2 hours curing time between coats. After the final coat is applied, the boat may be launched after 8 hours minimum to within 2 months maximum.

FIBERGLASS: Wash fiberglass with PETTIT'S #12120 BRUSHING THINNER to remove parting agent, grease, and dirt. Sand thoroughly with medium grit sandpaper to dull the glossy fiberglass surface. Apply 2 coats of Unepoxy. An alternate system for fiberglass is to wash with PETTIT'S #15095 MUST DEWAXER and then apply a coat of 9399 SANDLESS PREP COAT. Do not sand the Prep Coat. Apply 2 coats of Unepoxy making sure the first coat of Unepoxy is applied to the Prep Coat within 24 hours after the Prep Coat has been applied.

WOODEN HULLS: Old antifouling paint should be scraped to bare wood. PETTIT'S VINYLICIDE RED or aged non-antifouling hard racing finishes should be sanded thoroughly. If priming is necessary on bare wood, apply 1 coat of PETTIT'S RED LEAD PRIMER and let dry 24 hours. Sand lightly and apply 2 coats of Unepoxy.

CLEANING AND THINNING: Use PETTIT'S #12120 BRUSHING THINNER.
DO NOT USE THIS PRODUCT ON STEEL AND ALUMINUM HULLS.
STIR THOROUGHLY BEFORE USING.

CAUTION

HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN IRRITATION.

CONTAINS COPPER AND TIN COMPOUNDS AND AROMATIC HYDROCARBONS. INDUCE VOMITING. Drink milk. Do not breathe spray mist. Do not get in eyes, on skin, or on clothing. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water. Flush eyes with water. Get medical attention if irritation persists. Avoid storage near food or feed products. Do not apply to any surface that will be used by children. Do not reuse empty container. Destroy it by perforating or crushing. Do not contaminate water used for irrigation or domestic purposes. Bury or discard in a safe place. Use with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

ONE QUART U.S. STANDARD

IMPERIAL MEASURE 33 FL. OZ.

ACCEPTED WITH COMMENTS

PETTIT

marine  paint

UNEPOXY

ANTI FOULING

1926

INLAND BRONZE

NET 32 FL.OZ. (1 QT.)

CAUTION

KEEP OUT OF THE REACH OF CHILDREN
OTHER WARNINGS ON BACK PANEL

ACTIVE INGREDIENTS

Copper Powder	33.60%
Bis (tri-butyltin)	
Oxide	3.65%
INERT	
INGREDIENTS	62.75%
	100.00%

USDA REG. #390-19

UNDER THE TRADE
FUNCTIONAL AND
FOR ECONOMIC REASONS
REGISTERED UNDER NO. 390-19

UNEPOXY BRONZE

Unepoxy is an effective hard racing antifouling boat bottom paint for various waters. It can be applied over PETTIT'S VINYLICIDE RED and most aged non-antifouling hard racing finishes. A small test area of Unepoxy on aged hard racing finishes is recommended to determine adhesion and compatibility to the old finish. Old, soft, or semi-hard antifouling paints should be removed for best adhesion. Allow a minimum of 2 hours curing time between coats. After the final coat is applied, the boat may be launched after 8 hours minimum to within 2 months maximum.

FIBERGLASS: Wash fiberglass with PETTIT'S #12120 BRUSHING THINNER to remove parting agent, grease, and dirt. Sand thoroughly with medium grit sandpaper to dull the glossy fiberglass surface. Apply 2 coats of Unepoxy. An alternate system for fiberglass is to wash with PETTIT'S #15095 MUST DEWAXER and then apply a coat of 9399 SANDLESS PREP COAT. Do not sand the Prep Coat. Apply 2 coats of Unepoxy making sure the first coat of Unepoxy is applied to the Prep Coat within 24 hours after the Prep Coat has been applied.

WOODEN HULLS: Old antifouling paint should be scraped to bare wood. PETTIT'S VINYLICIDE RED or aged non-antifouling hard racing finishes should be sanded thoroughly. If priming is necessary on bare wood, apply 1 coat of PETTIT'S RED LEAD PRIMER and let dry 24 hours. Sand lightly and apply 2 coats of Unepoxy.

CLEANING AND THINNING: Use PETTIT'S #12120 BRUSHING THINNER.

DO NOT USE THIS PRODUCT ON STEEL AND ALUMINUM HULLS.
STIR THOROUGHLY BEFORE USING.

CAUTION

HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN IRRITATION.

CONTAINS COPPER AND TIN COMPOUNDS AND AROMATIC HYDROCARBONS. INDUCE VOMITING. Drink milk. Do not breathe spray mist. Do not get in eyes, on skin, or on clothing. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water. Flush eyes with water. Get medical attention if irritation persists. Avoid storage near food or feed products. Do not apply to any surface that will be used by children. Do not reuse empty container. Destroy it by perforating or crushing. Do not contaminate water used for irrigation or domestic purposes. Bury or discard in a safe place. Use with adequate ventilation.

ONE QUART U.S. STANDARD

KEEP OUT OF REACH OF CHILDREN.

IMPERIAL MEASURE 33 FL. OZ.

PETTIT PAINT CO., INC.

SAN LEANDRO, CALIF. BELLEVILLE, N. J.

ACCEPTED WITH COMMENTS