

# PETIT

## ANTI-FOULING

1640 SUPER TROPICOP RED

NET 32 FL.OZ.(1 QT.)

CAUTION KEEP OUT OF THE REACH OF CHILDREN.
OTHER WARNINGS ON BACK PANEL

PETTIT PAINT CO., INC.

#### PETTIT SUPER TROPICOP RED

This is a plastic type of strong anti-fouling paint which incorporates the latest research developments in the marine field.

SUPER TROPICOP RED may be used on either steel or wooden boats to provide positive protection against barnacles, toredo worms and other marine growth.

#### **DIRECTIONS**

The bottom to be painted should be dry and the old paint thoroughly cleaned. Old paint in poor condition should be removed.

Stir the paint thoroughly at first and then occasionally during application.

Allow at least six hours drying time between coats and after the final coat before launching.

WOODEN HULLS: Prime all bare wood with PETTIT'S RED LEAD PRIMER and dry overnight. Sand lightly. Apply two coats of SUPER TROPICOP RED. On repaint work, always apply two coats or SUPER TROPICOP.

STEEL HULLS: Remove all rust, grease and scale from the metal surface. Apply one coat of PETTIT's METAL PRIMER to bare metal. Follow with two coats of PETTIT's ZINC CHROMATE PRIMER or PETTIT'S VINYL RED UNDERCOATER. Finally, apply two coats of SUPER TROPICOP RED.

Use PETTIT's #120 BRUSHING THINNER for thinning, if necessary, and for cleaning brushes.

#### DO NOT USE ON ALUMINUM BOATS.

USDA Reg. No. 390-32

### HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

CONTAINS COPPER AND PETROLEUM DISTILLATE. Do not apply on window sills, toys, furniture, or interior surfaces which may be used L; children. Avoid prolonged contact with skin and breathing vapor of spray mist. Wash thoroughly after handling and before eating or smoking. Keep away from heat and open flame. Close container after each use.

Use with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

IMPERIAL MEASURE 33 FL. OZ.

SAN LEANDRO, CALIF. BELLEVILLE, N. J.

ACCEPTED WITH COMMENTS