

ACCEPTED
 10-7-70
 390-36

PETTIT

marine  paint

ACTIVE INGREDIENTS
 Bis (4-n-butyltin)
 Oxide 6.97%

METAL
 INGREDIENTS 93.00%
 100.00%

UNDA #300-38

ANTI-FOULING

1130

ALUMACIDE

WHITE

NET 32 FL.OZ.(1 QT.)

CAUTION KEEP OUT OF THE REACH OF CHILDREN.
 OTHER WARNINGS ON BACK PANEL

PETTIT PAINT CO., INC.

ALUMACIDE is a very hard plastic antifouling paint designed for aluminum boats and outboard motors. It does not contain any metallic copper or mercury which are responsible for galvanic corrosion. In certain areas where heavy fouling conditions exist, it is suggested that the bottom be cleaned and repainted in midseason.

DIRECTIONS

ALUMACIDE may be applied over existing marine enamel but best results are obtained by removing the old paint to bare metal. If the old paint contains copper or mercury it must be removed to prevent corrosion. Wash the bare metal surface with PETTIT'S #120 BRUSHING THINNER to clean off grease, oil or other foreign materials. Wipe dry with a clean rag. Apply the following system:

- a. Brush or spray one light transparent coat of PETTIT'S METAL PRIMER. Let dry 30 to 60 minutes — do not sand.
- b. Brush or spray one hiding coat of PETTIT'S VINYL RED UNDERCOATER. Let dry 30 to 60 minutes, then sand lightly with fine sandpaper.
- c. Brush or spray two coats of ALUMACIDE. Allow one to two hours between coats and immersion.

If thinning is necessary we recommend 5% to 10% addition of PETTIT'S #120 BRUSHING THINNER or 20% of PETTIT'S #121 SPRAYING THINNER for spray application.

DANGER  **POISON**

HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN IRRITATION. COMBUSTIBLE.
 CONTAINS TIN COMPOUND AND AROMATIC HYDROCARBONS. INDUCE VOMITING. Drink milk. Do not breathe spray mist. Do not get in eyes, on skin or on clothing. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water. Wash clothes before reuse. Flush eyes with water. Get medical attention if irritation persists. Avoid storage near food or food products. Keep away from heat and open flame. Do not apply to any surface that will be used by children.
 Use with adequate ventilation.

ONE QUART U.S. STANDARD

IMPERIAL MEASURE 33 FL. OZ.

SAN FRANCISCO, CALIF. 94177 BELLEVILLE, N.J. 07109