

PTED
3-72
FEDERAL INSECTICIDE
AND ACQUITICIDE ACT
EPA REG. NO. 390-39
ATTACHED COMMENTS

390-39

PETTIT

marine paint

ANTI-FOULING

Jet
ALUMACIDE
BLACK

ACTIVE INGREDIENTS
Bis (Tributyltin)
Sulphide 4.5%
Bis (Tributyltin)
Oxide 1.5%
INERT INGREDIENTS 93.6%
100.0%
EPA Reg. #390-39

NET 32 FL.OZ.(1QT.)

CAUTION KEEP OUT OF THE REACH OF CHILDREN.
OTHER PRECAUTIONS ON BACK PANEL.

PETTIT PAINT CO., INC.

ALUMACIDE is a very hard plastic antifouling paint designed for aluminum boats and outboard motors. It does not contain any metallic copper or mercury which are responsible for galvanic corrosion. In certain areas where heavy fouling conditions exist, it is suggested that the bottom be cleaned and repainted in midseason. This product is not effective against algal fouling organisms.

DIRECTIONS

ALUMACIDE may be applied over existing marine enamel, but best results are obtained by removing the old paint to bare metal. If the old paint contains copper or mercury, it must be removed to prevent corrosion. Wash the bare metal surface with PETTIT'S #120 BRUSHING THINNER to clean off grease, oil or other foreign materials. Wipe dry with a clean rag. Apply the following system:

- Brush or spray one light transparent coat of PETTIT'S METAL PRIMER. Let dry 30 to 60 minutes — do not sand.
- Brush or spray one hiding coat of PETTIT'S VINYL RED UNDERCOATER. Let dry 30 to 60 minutes; then sand lightly with fine sandpaper.
- Brush or spray two coats of ALUMACIDE. Allow one to two hours between coats and immersion.

If thinning is necessary, we recommend 5% to 10% addition of PETTIT'S #120 BRUSHING THINNER or 20% of PETTIT'S #121 SPRAYING THINNER for spray application.

CAUTION

HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN IRRITATION. COMBUSTIBLE. CONTAINS TIN COMPOUND AND AROMATIC HYDROCARBONS. INDUCE VOMITING. Drink milk. Do not breathe spray mist. Do not get in eyes, on skin, or on clothing. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water. Wash clothes before reuse. Flush eyes with water. Get medical attention if irritation persists. Avoid storage near food or feed products. Keep away from heat and open flame. Do not apply to any surface that will be used by children. Do not reuse container. Destroy when empty.

KEEP OUT OF THE REACH OF CHILDREN.

ONE QUART U.S. STANDARD

IMPERIAL MEASURE 33 FL. OZ.

BOROUGH OF ROCKAWAY, N.J.: 07866 - SAN LEANDRO, CALIF. 94577

ACCEPTED
9-13-72
 UNDER THE FEDERAL INSECTICIDE
 FUNGICIDE AND RODENTICIDE ACT
 THIS PRODUCT HAS BEEN REGISTERED
 UNDER NO. _____ SUBJECT
 TO ATTACHED COMMENTS

390-41

PETTIT
marine paint

ACTIVE INGREDIENTS	
Bis (Tributyltin) Oxide	5.0%
Bis (Tributyltin) Sulphide	2.0%
INERT INGREDIENTS	93.0%
	100.0%
EPA Reg. #390-41	

ANTI-FOULING

1649
ALUMACIDE
RED

NET 32 FL. OZ. (1 QT.)

CAUTION KEEP OUT OF THE REACH OF CHILDREN.
 OTHER PRECAUTIONS ON BACK PANEL.

PETTIT PAINT CO., INC.

ALUMACIDE is a very hard plastic antifouling paint designed for aluminum boats and outboard motors. It does not contain any metallic copper or mercury which are responsible for galvanic corrosion. In certain areas where heavy fouling conditions exist, it is suggested that the bottom be cleaned and repainted in midseason. This product is not effective against algal fouling organisms.

DIRECTIONS

ALUMACIDE may be applied over existing marine enamel, but best results are obtained by removing the old paint to bare metal. If the old paint contains copper or mercury, it must be removed to prevent corrosion. Wash the bare metal surface with PETTIT'S #120 BRUSHING THINNER to clean off grease, oil or other foreign materials. Wipe dry with a clean rag. Apply the following system:

- a. Brush or spray one light transparent coat of PETTIT'S METAL PRIMER. Let dry 30 to 60 minutes — do not sand.
- b. Brush or spray one hiding coat of PETTIT'S VINYL RED UNDERCOATER. Let dry 30 to 60 minutes; then sand lightly with fine sandpaper.
- c. Brush or spray two coats of ALUMACIDE. Allow one to two hours between coats and immersion.

If thinning is necessary, we recommend 5% to 10% addition of PETTIT'S #120 BRUSHING THINNER or 20% of PETTIT'S #121 SPRAYING THINNER for spray application.

CAUTION

HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN IRRITATION. COMBUSTIBLE. CONTAINS TIN COMPOUND AND AROMATIC HYDROCARBONS. INDUCE VOMITING. Drink milk. Do not breathe spray mist. Do not get in eyes, on skin, or on clothing. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water. Wash clothes before reuse. Flush eyes with water. Get medical attention if irritation persists. Avoid storage near food or feed products. Keep away from heat and open flame. Do not apply to any surface that will be used by children. Do not reuse container. Destroy when empty.

KEEP OUT OF THE REACH OF CHILDREN.

ONE QUART U.S. STANDARD

IMPERIAL MEASURE 33 FL. OZ.

BOROUGH OF ROCKAWAY, N.J. 07866 - SAN LEANDRO, CALIF. 94577