

0911-05

# PETTIT

marine  paint

ACTIVE IN  
BIS  
BI  
IN

## SPECIALTY

**1806  
OUTDRIVE  
ANTI-FOULING  
BLACK**  
**DANGER!**  
CONTENTS UNDER PRESSURE  
EXTREMELY FLAMMABLE. VAPOR HARMFUL.  
See caution elsewhere on label.  
(Not effective for algae fouling.)  
NET WEIGHT: 15 OZ.

**PETTIT PAINT CO., INC.**

### PETTIT SPRAYCAN FINISHES

#### PREPARATION DIRECTIONS

If the paint is in good condition it will only be necessary to thoroughly sand or bronze wool the surface and wipe clean.

If the paint is in poor condition it will be necessary to completely remove all existing paint with PETTIT'S NON-FLAMMABLE PAINT & VARNISH REMOVER back to the bare metal.

Wash the bare metal surface with PETTIT'S #12<sup>o</sup> BRUSHING THINNER to clean off grease, oil or other foreign materials. Wipe dry with a clean rag. Apply the following system:

- a. Brush or spray one light coat of PETTIT'S VINYL METAL PRIMER. Let dry 30 to 60 minutes — do not sand.
- b. Brush or spray one hiding coat of PETTIT'S VINYL RED UNDERCOATER. Let dry 30 to 60 minutes, then sand lightly with fine sandpaper.
- c. Spray two coats of OUTDRIVE BLACK. Allow one to two hours between coats and immersion.

#### DIRECTIONS FOR USE

- 1. Shake can thoroughly until agitator clicks sharply back and forth for three minutes.
- 2. Clean surface to be sprayed. All oil, rust, dirt or loose coating should be removed.
- 3. Press sprayhead with forefinger to spray. The valve must be completely depressed for proper results.
- 4. Hold the can about 10 to 12 inches away from the surface. Do not spray at any closer distance.
- 5. Spray a very light mist coat and allow this to become tacky. Then go over the work again with a medium coat. Too heavy a coat will cause sags and runs. Practice on an old surface first.
- 6. Best results are obtained when the contents are at room temperature. Can may be warmed in water no hotter than 90° F.
- 7. A dirty nozzle may be cleaned by taking off plastic sprayhead and reaming out nozzle with a pin. Cover nozzle with finger when replacing sprayhead to avoid accidental spray.
- 8. After each use, turn can upside down and spray until nozzle is cleared of spray.

**CAUTION! HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN OR EYE IRRITATION. CONTAINS TIN COMPOUNDS AND AROMATIC HYDROCARBONS. INDUCE VOMITING. Drink milk. Avoid breathing spray mist. Do not get in eyes, on skin, or on clothing. In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention if irritation persists. Avoid storage near food or feed products. Do not apply to any surface that will be used by children. May be absorbed through skin. Wash contaminated clothes before re-use. Keep away from heat, sparks, and open flame. Do not puncture. Exposure to temperatures above 130° F. may cause bursting. Do not throw into fire or incinerator.**

Use with adequate ventilation KEEP OUT OF REACH OF CHILDREN

BOROUGH OF ROCKAWAY, N.J. 07866 - SAN LEANDRO, CALIF. 94577