

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS
WARNING**

KEEP OUT OF REACH OF CHILDREN
Use only with
adequate ventilation.

Harmful if swallowed. Avoid contact with
skin and breathing of vapor or spray.
Causes eye and skin irritation.

FIRST AID: In case of contact, im-
mediately flush eyes or skin with
plenty of water for at least 15 min-
utes. For eyes, call a physician. If
inhaled remove to fresh air. Remove
and wash contaminated clothing be-
fore reuse. Wash thoroughly with soap
and water after handling and before
eating and smoking.


If swallowed, drink promptly a large
quantity of milk, egg whites, gelatin
solution or if these are not available,
drink large quantities of water. Never
give anything by mouth to an uncon-
scious person. Avoid alcohol. Call a
physician immediately.

ENVIRONMENTAL HAZARD
Do not contaminate water by cleaning
of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARD
COMBUSTIBLE: Do not use or store near
heat or open flame.

(continued on right hand panel)

PETTIT

APPROVED
marine  *paint*

UNEPOXY

ANTI FOULING

**1820 BLACK
TROPIC FORMULA**

32 FL.OZ. (1 QT.) 946 mL

WARNING! KEEP OUT OF REACH OF CHILDREN.
COMBUSTIBLE. OTHER PRECAUTIONS ON SIDE PANEL.

(continued from left hand panel)

DIRECTIONS FOR USE

It is a violation of federal law to use
this product in a manner inconsistent
with its labeling.

NOTE—Wear protective clothing when
product is used in confined areas or ap-
plied by spraying, wear a respirator jointly
approved by the Mining Enforcement and
Safety Administration (formerly the U.S.
Bureau of Mines) and by the National
Institute for Occupational Safety and Health
under the provisions of 30 CFR 11.

GENERAL DESCRIPTION

Unepoxy is an anti-fouling protective
coating resistant to algae, barnacles
and other marine fouling.

STORAGE & DISPOSAL

Do not contaminate water, food, or
feed by storage or disposal. Open
dumping is prohibited.

Pesticide, spray mixture, or rinsate that
cannot be used or chemically reprocessed
should be disposed of according to proce-
dures approved by Federal, State, or local
disposal authorities.

Container—Triple rinse (or equivalent)
and dispose of in an approved landfill or
bury in a safe place. Consult Federal, State,
or local disposal authorities for approved
alternative procedures.

E.P.A. REG. NO.390-55
E.P.A. EST. NO.390-NJ-1

PRODUCT DESCRIPTION: Unepoxy is an anti-
fouling protective coating resistant to algae,
barnacles and other hard antifouling panels if
thoroughly sanded or removed for best adhe-
sion.

PREPARATION OF SURFACE: The surface is
cleaned and/or sanded before any primers or
paints are applied.

APPLICATION AND TEMPERATURE: Unepoxy can
be applied by spraying, brushing, or rolling
under the following conditions. The temperature range of application is
50°F to 90°F.

PREPARATION OF PAINT: Unepoxy is best ap-
plied with a mechanical paint shaker. Before using check the
shaker to make sure it is in good working order.
If the paint has been on the shelf for several
months, it may have settled. Stir the paint
thoroughly before use.

THINNER: Use Pettit's 12120 Brushing Thinner for
brushing or inadequate paint application will occur.

DRY TIMES: Let the first coat of Unepoxy dry before
applying the second coat. The paint should be
dry to the touch in 4 hours and preferably
dry for 24 hours before the vessel is put
into service.

COVERAGE: Unepoxy covers approximately 100
square feet per gallon. Coverage varies with
surface conditions and application method.

MAINTENANCE OF ANTI-FOULING PAINT: No
occurrences can adversely affect antifouling paint
performance. If the paint is found to be
peeling or flaking, it should be removed
and the surface cleaned. Lightly scrub
the surface with Pettit's 12120 Brushing Thinner.

FIBERGLASS: Wash the fiberglass with Pettit's 12120
Brushing Thinner. Do not use sandpaper to
scuff the fiberglass. After the hull has been
washed, apply a coat of Pettit's 12120
Brushing Thinner.

BLENDED GELCOLE: Remove all antifouling
coatings with Pettit's 12120 Brushing Thinner.
Sanding is not necessary. Sand lightly
and then apply two coats of Unepoxy.

WOODEN HULLS: Old antifouling paint should be
removed with Pettit's 12120 Brushing Thinner
and the hull sanded. Let dry for 24 hours.
STEEL HULLS/UNDERWATER METAL PARTS:
The surface with Pettit's 12120 Brushing Thinner to
remove old antifouling paint. Follow with
two coats of Pettit's Vinyl Red Undercoat.

50-192 **DO NOT USE THIS PRO**

PETTIT PAINT CO., INC.

BOROUGH OF ROCKAWAY

PETTIT
 Marine paint

UNEPOXY

ANTI FOULING
 1820 BLACK
 TROPIC FORMULA

946 mL **WARNING!** KEEP OUT OF REACH OF CHILDREN.
 COMBUSTIBLE. OTHER PRECAUTIONS ON SIDE PANEL.

PAINT CO., INC.

(continued from left hand page)

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

NOTE:—Wear protective clothing when product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

GENERAL DESCRIPTION

Unepoxy is an anti-fouling protective coating resistant to algae, barnacles and other marine fouling.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

Pesticide, spray mixture, or residue that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State, or local disposal authorities.

Container:—Triple rinse (or equivalent) and dispose of in an approved landfill or bury in a safe place. Consult Federal, State, or local disposal authorities for approved alternative procedures.

E.P.A. REG. NO.390-55
 E.P.A. EST. NO.390-NJ-1

UNEPOXY ANTIFOULING

PRODUCT DESCRIPTION: Unepoxy is an effective, fast drying, antifouling boat bottom paint for various waters. It can be applied over a red lead and other hard antifouling paints. If these old paints are on a hull and wood-hull Old 1820 of Unepoxy antifouling paint should be thoroughly sanded or removed for best adhesion.

PREPARATION OF SURFACE: The surface to be painted should be dry, clean and oil free. It should be properly prepared by solvent cleaning and sanding before any primers or paints are applied. Follow the recommended system below.

APPLICATION AND TEMPERATURE: Unepoxy can be applied by brush, roller or spray. The work should be done between 9:00 A.M. and 4:00 P.M. under good drying conditions. The temperature range of application is 40° to 90° F. Two coats should always be applied for best antifouling protection.

PREPARATION OF PAINT: Unepoxy is heavily loaded with cuprous oxide. As a result of this loading there is a tendency for settling to occur especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the upper and bottom of the can to make sure all the pigment is at the bottom. If mixing is going to be done with a wooden paddle or an electric drill, stirrer, bring off half of the liquid from the top of the can into another container properly cover in any settled pigment. Then recombine the two parts thoroughly.

THINNER: Use Pettit's 12120 Brushing Thinner for thinning the Unepoxy on a worky or dry day, or for cleaning up equipment. Do not use the Unepoxy or inadequate paint application will occur.

DRY TIMES: Let the first coat of Unepoxy dry for two to four hours minimum before applying the second coat. After the second coat is applied, let the paint dry at least 24 hours or preferably overnight before immersing the boat. Under adverse drying conditions let the boat dry overnight to make sure all the solvent is out of the paint film. Maximum immersion time is two months.

COVERAGE: Unepoxy covers approximately 400 square feet per gallon.

MAINTENANCE OF ANTIFOULING PAINT: No antifouling paint can be effective under all conditions of exposure. Manmade pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water, and even electrolysis can ruin an antifouling paint. Therefore we strongly suggest that the bottom of the boat be checked several times a month to make sure it is clean and that no growth is occurring. Lightly scrub the bottom with a soft brush to remove anything from the antifouling paint surface.

PAINT SYSTEMS

FIBERGLASS: Wash the fiberglass with Pettit's 12120 Brushing Thinner or 15095 Deconer to remove parking agent, grease, and dirt. Sand thoroughly with 80-120 grit sandpaper to dull the glossy fiberglass surface. Rewash the sanded surface and then apply two coats of Unepoxy. To ship the sanding operation after the boat has been washed, apply a coat of Pettit's 6004 Ship Sand primer. Then apply two coats of Unepoxy.

BLISTERED GELCOTE: Remove all antifouling paint by sanding or using Pettit's 9010 Fiberglass Paint & Varnish Remover. Sand the gelcote and fill any voids with Pettit's 7190 Polyester Mender. Sand smooth. Apply a coat of Pettit's 4169 Polyepoxy Undercoater / 4077 Polyepoxy Brush Hardener. Let dry 24 hours minimum, sand lightly and then apply two coats of Unepoxy.

WOODEN HULLS: Old antifouling paint should be thoroughly sanded or scraped to bare wood. If priming is necessary on bare wood, apply one coat of Pettit's Red Lead Primer and let dry for 24 hours. Sand lightly and apply two coats of Unepoxy.

STEEL HULLS - UNDERWATER METAL PARTS: To remove old rust and scale from the metal surface scrape or sandblast with wire brush. Wash the surface with Pettit's 12120 Brushing Thinner to remove grease and dirt. Apply one coat of Pettit's Metal Primer to bare metal and let dry four hours. Follow with two coats of Pettit's Vinyl Red Undercoater and let dry two hours between coats and four hours before applying two coats of Unepoxy.

50-92 **DO NOT USE THIS PRODUCT ON ALUMINUM HULLS AND OUTDRIVES.** 20

BOROUGH OF ROCKAWAY, N.J. 07866 - SAN LEANDRO, CALIF. 94577