


PETTIT

marine



paint

ANTI-FOULING

1641
CHESAPEAKE
RED COPPER

ACCEPTED

OCT 27 1981

U.S. DEPT. OF AGRICULTURE
FEDERAL INSECTARY
REGISTRATION DIVISION
WASHINGTON, D.C. 20250
LPA Reg. No. 390-571

1 GALLON 3.785 LITERS

WARNING! KEEP OUT OF REACH OF CHILDREN.
COMBUSTIBLE. SEE SIDE PANEL FOR
ADDITIONAL PRECAUTIONARY STATEMENTS

PETTIT PAINT CO. INC.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING

KEEP OUT OF REACH OF CHILDREN

Use only with adequate ventilation.

Harmful if swallowed. Avoid contact with skin and breathing of vapor or spray mist. Causes eye and skin irritation.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. If inhaled, remove to fresh air. Remove and wash contaminated clothing before reuse. Wash thoroughly with soap and water after handling and before eating and smoking.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Never give anything by mouth to an unconscious person. Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARD

Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARD

COMBUSTIBLE: Do not use near open heat or flame.

CHESAPEAKE RED COPPER

PRODUCT DESCRIPTION: Chesapeake Red Copper is an effective antifouling paint when fishponds, boats, and other structures are properly prepared and painted with this antifouling paint. It is not recommended for use on structures that are in poor condition.

PREPARATION OF SURFACE: The surface to be painted must be dry, clean, and free of all the properly prepared by solvent cleaning and sandblasting. The surface must be properly prepared before the recommended systems below.

APPLICATION AND TEMPERATURE: The surface to be painted may be applied by brush, roller, or spray. The work should be done between 9:00 A.M. and 4:00 P.M. under good drying conditions. The temperature range of application is 40° to 90° F. Two coats should always be applied for best antifouling protection.

PREPARATION OF PAINT: Chesapeake Red Copper contains a heavy pigment. As a result of using this product, there is a tendency for settling to occur, especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible, shake the can of paint on a mechanical paint shaker. Before using, check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then remix the two parts together thoroughly.

THINNER: Use Pettit's 12120 Brushing Thinner or Mineral Spirits for thinning the paint on a warm, windy day, or for cleaning up equipment.

DRY TIMES: Let the first coat of Chesapeake Red Copper dry six hours to overnight before the second coat is applied. After the second coat is applied, immerse the hull within 48 hours.

COVERAGE: Chesapeake Red Copper covers approximately 400 square feet per gallon.

MAINTENANCE OF ANTIFOULING PAINT: An antifouling paint is effective under normal conditions of exposure. Man-made pollution and natural currents can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, salt water, and electrolysis can ruin antifouling paint. Therefore, we strongly suggest that the bottom of the hull be cleaned several times a month to make sure it is clean and that no growth is occurring. Scrape the bottom with a soft brush to remove anything from the antifouling paint surface.

WOODEN HULLS: Scrape or sand off all old paint. Prime a bare wood with Pettit Red Lead Primer or Chesapeake Red Copper thinned with one of our recommended thinners. After the primer coat has dried, apply two coats of paint.

STEEL HULLS: Wire wheel or lightly sandblast any rust scale rusted paint. Apply two coats of Pettit 6888Q Rust Lok Steel Primer to any bare steel. After the primer coat has dried, approximately two hours, apply the first of two coats of the Chesapeake Red Copper.

DO NOT USE THIS PRODUCT ON ALUMINUM HULLS AND OUTDRIVES.

continued from left hand page

DIRECTIONS FOR USE

is a violation of Federal law to use this product in a manner inconsistent with its labeling.

When product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining Enforcement and Safety Administration, formerly the U.S. Bureau of Mines, and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

GENERAL DESCRIPTION

Chesapeake Red Copper is an antifouling protective coating resistant to algae, barnacles and other marine growth.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Do not use in a spray mixture or residue that cannot be used according to label instructions must be disposed of according to Federal, State or Local procedures under the Resource Conservation and Recovery Act. Do not use as a paint thinner — Triple rinse (or equivalent) and offer for recycling or reconditioning, or dispose of in a sanitary landfill, or by other approved State and local procedures.

A REG. NO. 390-57
A. EST. NO. 390-NJ-1

BOROUGH OF ROCKAWAY, N.J. 07866 - SPRING VALLEY, CALIF. 92077