

**PRECAUTIONARY STATEMENTS**  
**HAZARD TO HUMANS AND DOMESTIC ANIMALS**

**DANGER**

**KEEP OUT OF REACH OF CHILDREN**  
Use only with adequate ventilation  
**CAUSTIC** Causes severe skin and eye damage. Do not get on skin, clothing or in eyes. Wear a face shield and rubber gloves when handling this in a well ventilated area. Harmful if swallowed or inhaled. Do not breathe vapors or spray mist.

**PRACTICAL TREATMENT** In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get immediate medical attention if swallowed. Do not induce vomiting. This product contains petroleum distillates. Get immediate medical attention if in eyes. Flush eyes with water. Get medical attention.

**ENVIRONMENTAL HAZARD**  
This product is toxic to fish and wildlife. Do not contaminate water by cleaning equipment or disposal of a can. Do not apply directly to water.

**PHYSICAL OR CHEMICAL HAZARD**  
**COMBUSTIBLE**: Do not use or store near heat or open flame.

Continued on right hand panel

Continued from left hand panel

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.  
**NOTE** — When product is used in confined areas or applied by spraying, wear a respirator mask approved by the Mining, Education and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

**GENERAL DESCRIPTION**

**HORIZONS** is an anti-foaming protective coating resistant to algae, barnacles and other marine fouling.

**STORAGE & DISPOSAL**

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label directions, contact your State Pesticide or Toxicant Control Agency, or the Hazardous Waste representative of the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL** Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or by other procedures approved by State and local authorities.  
EPA 806-10 360-58  
EPA 811-10 390-82-1

**HORIZONS ANTI-FOILING**

**Directions** — A Pettit marine antifouling paint is designed to protect boat hulls from barnacles, algae and other marine growth. Both the maximum bottom and underwater performance of antifouling coatings. This product provides continuous antifouling action on the painted surface of all hulls. The paint also allows greater water uptake by the hull's epoxy coating, giving a slight amount of hull flex. Horizons works against any Pettit's epoxy sheathing or finished or other hard antifouling paints. Do not use over hard antifouling paint that has not been removed. Remove them and before the proper surface level below.

**Preparation of Hulls** — The hull to be painted should be dry, clean and oil free. It should be properly prepared by sanding, scraping and a suitable surface primer or patch are applied. Unless the manufacturer's instructions specify otherwise, the maximum recommended sanding grit size is 100 mesh. The sand should be between 200 and 400 mesh and 100 mesh sand is preferred. The temperature range of application is between 55 and 85 F. Do not use and painting should be done within 24 hours. The maximum depth of application is between 55 and 85 F. Do not use and painting should be done within 24 hours. The maximum depth of application is between 55 and 85 F. Do not use and painting should be done within 24 hours.

**Painting** — Horizons marine antifouling paint is applied to the hull in a thin, even coat. It is necessary to thoroughly clean the paint before using. If possible, clean the hull of paint with a high pressure water spray. Wash the hull and bottom of the hull to make sure all the paint has been removed. If necessary, spray to be sure all water particles are removed and cover your hull with the paint. Apply the paint in a thin, even coat. Do not use and painting should be done within 24 hours. The maximum depth of application is between 55 and 85 F. Do not use and painting should be done within 24 hours.

**Paint Storage** — Horizons marine antifouling paint is stored in a cool, dry place. Do not use and painting should be done within 24 hours. The maximum depth of application is between 55 and 85 F. Do not use and painting should be done within 24 hours.

PETTIT PAINT COMPANY, INC.  
BOROUGH OF ROCKAWAY, N.J. 07866 — SPRING VALLEY, CA. 92077