

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER**

**KEEP OUT OF REACH OF CHILDREN.
Use only with adequate ventilation.**
COMBUSTIBLE: Causes severe skin and eye damage. Do not get on skin, clothing or in eyes. Wear a face shield and rubber gloves when handling. Use in a well ventilated area. Harmful if swallowed or inhaled. Do not breathe vapors or spray mist.

PRACTICAL TREATMENT: In case of skin contact remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled remove to fresh air. Use artificial respiration if breathing has stopped. Get immediate medical attention. If swallowed do not induce vomiting. This product contains petroleum distillates. Get immediate medical attention if in eyes. Flush eyes with water. Get medical attention.

ENVIRONMENTAL HAZARD
This product is toxic to fish and wildlife. Do not contaminate water by cleaning equipment or disposal of waste. Do not apply directly to water.

PHYSICAL OR CHEMICAL HAZARD
COMBUSTIBLE! Do not use or store near heat or open flame.

(continued on right hand panel)

PETTIT
770064900

HORIZONS ANTI-FOULING

ACCEPT
1380
GREEN
AGG 20

Under the Federal Fungicide, and Rodenticide Act, this product is registered under EPA Reg. No. 302

3 QUART 946 ML

PETTIT PAINT CO. INC.

(continued from left hand panel)

DIRECTIONS FOR USE
It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

NOTE — When product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining, Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

GENERAL DESCRIPTION
HORIZONS is an anti-fouling protective coating resistant to algae, barnacles and other marine fouling.

STORAGE & DISPOSAL
Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by one according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative of the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

E.P.A. REG. NO. 390-59
E.P.A. EST. NO. 980-NA-1

HORIZONS ANTI-FOULING

HORIZONS is a Pettit marine antifouling paint designed to protect boat hulls from barnacles, algae and other marine growth. Both the recessed hull and exposed hull surfaces are antifouling surfaces. This product provides continuous antifouling activity on the painted surface of all hulls. The paint surface also slowly erodes away where the hull is being used, giving a clean, smooth finish at all times. HORIZONS may be applied over Pettit's equal shipping or finished or other hard antifouling paints, old hull and non-antifouling paints. HORIZONS may be painted directly on bare hulls. HORIZONS may be painted over the proper systems listed below.

PREPARATION OF PAINT: HORIZONS contains copper oxide. As a result, there is a tendency for settling to occur especially if the paint is left open on the shelf several weeks. It is necessary to thoroughly stir the paint before using. If possible, stir the can of paint on a mechanical paint shaker. Before using, check the sides and bottom of the can to make sure all the pigment has been stirred in. If stirring is going to be done with a wooden paddle or stirrer, stir near, but not at, the top of the can and then scrape the sides of the can with a wire brush to break up the paint.

APPLICATION AND REPAIRS: HORIZONS may be applied by brush, roller or spray. The work should be done between 40° and 80° F and 40% to 70% relative humidity. The temperature range of application is between 55° and 90° F. All hulls are and preferably three or four coats should be applied for best antifouling protection. Sub coats of HORIZONS should be applied to high wear areas and the substrate.

PREPARATION OF PAINT: HORIZONS contains copper oxide. As a result, there is a tendency for settling to occur especially if the paint is left open on the shelf several weeks. It is necessary to thoroughly stir the paint before using. If possible, stir the can of paint on a mechanical paint shaker. Before using, check the sides and bottom of the can to make sure all the pigment has been stirred in. If stirring is going to be done with a wooden paddle or stirrer, stir near, but not at, the top of the can and then scrape the sides of the can with a wire brush to break up the paint.

REPAIRS: Use Pettit's 12120 Duplicating Primer for repairing HORIZONS on a warm, sunny day or cleaning up equipment. Do not use this HORIZONS. Otherwise, appropriate paint application will occur.

DRY TIMES: Let each coat of HORIZONS dry four hours minimum before applying the next coat. After the final coat is applied, let the paint dry at least eight hours or preferably overnight before launching the boat. Under adverse conditions let the last dry overnight to make sure all water is out of the paint film.

COVERAGE: HORIZONS covers approximately 400 square feet per gallon.

REMARKS: HORIZONS is a water-based paint. Its antifouling action can be effective under all conditions of exposure. Main-made pollution and control requirements can adversely affect antifouling paint performance. Examine hull and water temperature, salt, dirt, oil, barnacle growth, and non-antifouling paint over an antifouling paint. Therefore, we strongly suggest that the bottom of the hull be checked periodically to make sure it is clean.

PAINT SYSTEMS
INTERGLAZES: Wash the fiberglass with Pettit's 12120 Duplicating Primer or 12095 Primer to remove parking agents, grease and dirt. Sand thoroughly with 80 grit sandpaper to dull the glossy fiberglass surface. Remove the sanding surface and then apply at least two coats of HORIZONS. In paint old, hard antifouling paint, lightly sand the painted surface before applying HORIZONS antifouling paint.

REPAIRS: Remove an antifouling paint by sanding or using Pettit's 9030 Fiberglass Paint & Varnish Remover. Sand the substrate and fill any voids with Pettit's 7190 Polyurethane Filler. Sand smooth and apply a coat of Pettit's 4100 Polyurethane Undercoat/4021 Polyurethane Hardener. Let dry 74 hours minimum, sand thoroughly with 80 grit sandpaper and then apply HORIZONS antifouling paint.

NON-FIBERGLASS: Old, hard antifouling paint should be thoroughly sanded. If priming is necessary on bare wood, apply a finish up coat of HORIZONS to bare wood. Then apply the subsequent coats of HORIZONS antifouling paint.

SEALED HULLS AND UNDERDECK METAL PARTS: To remove old seal and scale from the metal surface, scrape, sandblast or use bleach. Wash the surface with Pettit's 12120 Duplicating Primer to remove grease and dirt. Apply one coat of Pettit's 6455/644 Metal Primer to the bare metal and let it dry four hours. Follow with one coat of Pettit's 4100 Polyurethane Undercoat/4021 Polyurethane Hardener and let dry 74 hours. Then sand the surface thoroughly with 80 grit sandpaper and apply HORIZONS antifouling paint.

DO NOT USE THIS PRODUCT ON A COPPER HULL OR COPPER FITTINGS.

PETTIT PAINT COMPANY, INC.
BOROUGH OF ROCKAWAY, N.J. 07866 — SPRING VALLEY, CA. 92077

12-1 1043-81 9/1/81

**DIRECTIONS FOR USE
GENERAL CLASSIFICATION**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Foaming Insurance has been specifically formulated for Institutional, Commercial and Industrial cleaning and disinfecting in Nursing Homes, Hospitals, Offices, Schools, Motels and Hotels, Recreational Facilities and Factories.

DISINFECTING, DEODORIZING AND CLEANING

To disinfect hard non-porous surfaces such as bathroom tiles, walls, fixtures, shower stalls, sinks, bathtubs, hampers, tables, chairs and counters:

(1) Shake can before using. (2) Hold can six to eight inches from surface to be treated. (3) Spray area until it is covered with a white foam. Allow foam to penetrate and remain wet for 10 minutes. No scrubbing is necessary. (4) Wipe off with clean cloth, mop or sponge. Foaming Insurance will not leave grit or soap scum. For heavily soiled areas, remove gross soil before treatment.

MILDEWSTAT — To control mold and mildew on pre-cleaned hard non-porous surfaces (such as floors, walls, table tops) spray surfaces to be treated making sure to wet completely. Let air dry. Repeat application at weekly intervals or when mildew growth reappears.

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMAN
AND DOMESTIC ANIMALS
WARNING**

Keep out of Reach of Children. Causes eye and skin irritation. Do not get in eyes, skin or on clothing. Harmful if swallowed.

**STATEMENT OF
PRACTICAL TREATMENT**

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash all contaminated clothing before reuse. If swallowed, drink milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Call a physician.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.



**CLEANER
DEODORIZER
AEROSOL
DETERGENT
DISINFECTANT**

For Industrial and Institutional Use Only

ACTIVE INGREDIENTS:
n-Alkyl (60% C₁₂, 30% C₁₄, 5% C₁₆, 5% C₁₈) dimethyl benzyl ammonium chlorides 0.1%
n-Alkyl (68% C₁₂, 32% C₁₄) dimethyl ethylbenzyl ammonium chlorides 0.1%
INERT INGREDIENTS 99.8%
EPA REG. NO. 1043-81

Only for Sale To, Use and Storage by Service Personnel

**KEEP OUT OF REACH
OF CHILDREN
WARNING**

Contents under pressure. Do not puncture. Do not use or store near heat or open flame. Exposure to temperature above 130 °F may cause bursting. Never throw container into fire or incinerator.

See side panel for additional precautionary and practical treatment statements.



Vestal Laboratories, Inc.
A Subsidiary of Chem-D Corp.
St. Louis, MO 63110

Can Size 20 oz. Net Contents 18 oz.

Foaming Insurance inactivates the Herpes Simplex Type 2 virus when used as directed on washable hard non-porous environmental surfaces.

Foaming Insurance is formulated to deliver 2000 ppm active quat for routine cleaning, disinfecting and deodorizing in institutions such as Nursing Homes, Hospitals, Offices, Schools, Industrial Plants, Medical and Dental Offices, Veterinary Clinics, Motels and Hotels and other public areas. When used as directed, Foaming Insurance is designed to clean and disinfect inanimate washable hard surfaces such as walls, sinks, tables, chairs, telephones, bathrooms, shower stalls, bathtubs, hampers, cabinets and bed springs.

In addition, Foaming Insurance deodorizes those areas which are generally hard to keep fresh smelling such as garbage storage areas, garbage bins and cans, basements, restrooms and other areas which are prone to odors caused by microorganisms.

When used as directed, Foaming Insurance demonstrates effective disinfection against Staphylococcus aureus, Salmonella choleraesuis and Pseudomonas aeruginosa, thus meeting requirements for hospital use. Efficacy tests have demonstrated that Foaming Insurance is an effective one-step cleaner disinfectant in the presence of 5% serum/organic soil.

Foaming Insurance is fungicidal against pathogenic fungi (T. mentagrophytes, Athletes' Foot) when used as directed on hard surfaces found in the bathroom, shower stall and locker room, or other hard non-porous surfaces commonly contacted by bare feet.

Foaming Insurance controls mold and mildew, and the odors they cause when used on hard non-porous inanimate surfaces.

STORAGE AND DISPOSAL

- DO NOT CONTAMINATE WATER FOOD OR FEED BY STORAGE OR DISPOSAL
- OPEN DUMPING IS PROHIBITED
- DO NOT REUSE EMPTY CONTAINER
- WRAP CONTAINER AND PUT IN TRASH COLLECTION

Superscript used is first letter of lot number.
EPA Est. No. 33595-MO-1 (S) 10900-OH-1 (S)
10807-GA-1 (S)

6404

397A-1008

ACCEPTED
AUG 19 1985
Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 1043-81

(e.g. Aspergillus niger)
Repeat application at two-week intervals or when mildew growth reappears.
NOTE: The cleaning agents in Foaming Insurance can