


PETTIT

marine  *paint*

NOT REVIEWED

In Accordance with FH Notice 8
and on Draft Labeling P

SPECIALTY

FLUME RED COPPER ANTIFOULING PAINT

1 GALLON
3.785 LITERS

KEEP OUT OF REACH OF CHILDREN.
WARNING! SEE SIDE PANEL FOR
ADDITIONAL PRECAUTIONARY STATEMENTS.

PETTIT PAINT CO., INC.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breathe sanding dust, vapor or spray mist. While spraying or sanding any flume surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS: This pesticide is extremely toxic to fish. Do not apply directly to water by cleaning or disposal of wastes or directly to lakes, streams, ponds or wetlands. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD: COMBUSTIBLE! Do not use or store near heat or open flame.

(continued on right hand panel)

Handwritten mark

USE DIRECTIONS:

PRODUCT DESCRIPTION: Flume Red Copper Antifouling paint is manufactured as an antifouling paint for use on wood and iron irrigation flume gates and adjacent concrete spillways. It can be applied over c J, soft or hard, antifouling paints that are in good condition.

PREPARATION OF SURFACE: The surface to be painted should be dry, clean and oil free. It should be lightly wire-brushed or sandblasted to remove all loose soil, rust, scale or paint. On hardwood or iron, first apply one coat of a suitable primer. Electrolytic corrosion could occur if the material is directly applied to ferrous materials without adequate preparation.

APPLICATION AND TEMPERATURE: Flume Red Copper Antifouling can be applied by brush, roller or spray. The work should be done between 9 a.m. and 4 p.m. under good conditions. The temperature range for application is 40°F. to 90°F. One coat would generally be sufficient for effective antifouling protection. Yearly renewal is generally required, dependent on conditions of exposure.

PREPARATION OF PAINT: Flume Red Copper Antifouling contains cuprous oxide, a heavy pigment. There is a tendency for settling to occur, especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible, shake the can of paint on a mechanical paint shaker. Before using, check the sides and bottom of the can to make sure all of the pigment has been thoroughly incorporated. If mixing will be done with a wooden paddle or an electric drill mixer, pour half of the liquid from the top of the can into another can and properly mix any settled pigment; then remix the two parts together thoroughly.

DRY TIME: Let the paint dry overnight before resuming water delivery.

COVERAGE: Flume Red Copper Antifouling covers approximately 9 m² of surface per gallon.

MAINTENANCE OF ANTIFOULING PAINT: No antifouling paint can be effective under all conditions of exposure. Manmade pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water and electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the irrigation structures be checked several times per month to make sure they are clean and that no growth is occurring. If necessary, lightly scrub the surface with a soft brush to remove attached materials.

(continued from left hand panel)

DIRECTIONS FOR USE

is a violation of Federal law to use this product in manner inconsistent with its labeling. See back panel for USE DIRECTIONS.

GENERAL DESCRIPTION

FLUME RED COPPER ANTIFOULING PAINT is a protective coating to control filamentous green algae genera including *Stigeoclonium*, *Oedogonium*, *Ulothrix*, *Cladophora*, and *Spirogyra*; filamentous blue-green algae including *Phormidium* and *Oscillatoria*; and several invertebrate organisms including Black Fly (*Simulium* spp.) Caddis Fly (*Hydropsyche* spp.) and Bryozoa.

STORAGE & DISPOSAL

Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

Container — Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

P.A. REG. NO.390-60

P.A. EST. NO.390-NJ-1

BOROUGH OF ROCK AWAY, N.J. 07866 - STONING VALLEY, CALIF. 92077