



Sea-Master

**SHRIMP
BOAT**
COPPER
ANTI-FOULING
PAINT

ACTIVE INGREDIENTS
COPPER 10.0%
NET WEIGHT 32 FL OZ (1 QT) 946 mL

This product contains
petroleum distillates.

32 FL OZ (1 QT) 946 mL

KEEP OUT OF REACH OF CHILDREN.
WARNING! SEE SIDE PANEL FOR
ADDITIONAL PRECAUTIONARY STATEMENTS.

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS
WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe sanding dust, vapor or spray mist. While spraying or sanding any flume surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

COMBUSTIBLE! Do not use or store near heat or open flame

(continued on right hand panel)

ACCEPTED
with comment
APR 28 1983
3907D

(continued from left hand panel)

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

NOTE -- When product is used in confined areas or applied by spraying, wear a respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11.

GENERAL DESCRIPTION

Shrimp Boat is an antifouling protective coating resistant to algae, barnacles and other marine fouling.

STORAGE & DISPOSAL

Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

Container Disposal

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

E.P.A. REG. NO. 390-70
E.P.A. REG. NO. 390-NJ-1



SHRIMP BOAT SEMI-HARD COPPER BOTTOM PAINT

Shrimp Boat's unique formula releases CONTROLLED amounts of toxicant, Cuprous Oxide, through the process of EROSION of the paint film, constantly protecting the hull against fouling by MARINE GROWTH. This "CHALKING- under-water" dissolving action is chemically programmed to occur in the presence of sea water. A small part of the exposed film surface slowly ERODES away leaving a freshly exposed toxic film at the surface until all of the TOXICANT contained in the MATRIX is dissipated or so weakened in strength as to permit fouling.

DIRECTIONS FOR USE

1. Use brush, spray or medium knap roller;
2. Mix paint thoroughly and keep it mixed;
3. Do NOT paint outside in high humidity, rain, or temperature below 50°.
4. Allow DRYING TIME of 8 hours minimum between coats -- preferably overnight.
5. After second or final coat, place boat in water between 4 and 6 hours, while still TACKY.
6. Whenever boat is hauled, repaint entire submerged surface for continued protection.
7. CLEAN brushes and/or equipment with SEA-MASTER #T-123 Thinner.
8. Do not use this paint above the water line.

When sanding old antifouling paint, use a face mask to prevent inhalation of sand and dust. To achieve maximum antifouling protection, be sure to apply at least two coats of Shrimp Boat. Allow overnight drying before launching. Shrimp Boat covers 400 sq. ft. per gallon.

REPAINT WORK

1. Scrape and scrub old finish until hull is clean of fouling.
2. If OLD finish is in GOOD condition.
3. Feather edges of old paint.
4. And apply two (2) coats of SEA-MASTER Shrimp Boat.
5. Do NOT start to paint until hull is thoroughly DRY.

FIBERGLASS HULLS

1. Clean, removing all dirt, oil, grease, wax and/or mold release agents.
2. Sand lightly removing GLOSS to provide "tooth".
3. Apply one (1) or two (2) coats SEA-MASTER No. 103, FIBERGLASS PRIMER.
4. Sand lightly, wipe off sanding dust and
5. Apply two (2) coats of SEA-MASTER Shrimp Boat.

NEW WOOD HULLS

1. Sand to a SMOOTH finish.
2. Apply 1 or 2 coats of SEA-MASTER #101, Barrier Primer. Follow instructions carefully.
3. Apply 2 coats of Shrimp Boat bottom paint.

DO NOT USE ON ALUMINUM HULLS AND OUTDRIVES

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

47. 4. 1. 1944
 48. 4. 1. 1944
 49. 4. 1. 1944
 50. 4. 1. 1944

הַיְּמִינִית

Subject: Antismuggling Unit - 100-678987
Registration No. 100-678987
KPA Registration No. 100-678987
Submission: March 17, 1964

1. To the extent permitted by law, submitted in connection with registration under EIRPA sec. 3(c)(7)(B), is acceptable, provided that you:

1. Submit and/or file all data required for registration/certification of your product under TIEPPA sec. 2(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Make the labeling changes listed below before you release the product for shipment bearing the amended label(s):
 - a. Delete the last clause, beginning with "Statement of..." while preparing the revised label(s)....
 - b. For registration or cert. delete the first antifoaming bottom label, beginning with sec. 2. (b)(1), in effect. Use the EPA's most acceptable standard format -- and the term unique. These statements are misleading.
3. Submit five (5) copies of the final revised label(s) before you release the product for shipment.

SYMBOL ►
SURNAME ►
DATE ►

EPA 8-770-1-9-1-1-1-1-1-1

CONCURRENCES

OFFICIAL FILE COPY



-2-

If these two items are not possible, then the registration will be
subject to cancellation in accordance with 21 CFR 162.104. Such release for
shipment of the product bearing the amended labeling constitutes acceptance of
these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

Richard E. Mountfort *RFM*
Product Manager (21)
Pesticide-Regulation Branch
Registration Division (21-261)

Enclosure

RD:K7Mountfort:DCR-25763:W446-3277C:jjk:Raven:474-2013:1/24/83