

CREOSOTE WOOD PRESERVING OIL

C O P Y E D

OCT 10, 1972

ACTIVE INGREDIENTS 100%
Coal Tar Creosote Oils 75%
Petroleum Hydrocarbons 25%

Gives protection against dry rot, and helps prevent termite infestation of wood. Gives a desirable brown stain.

Low cost protection for farm buildings. May be dipped, brushed or sprayed.

Fence posts, foundation timbers and other heavy wood members should be free of bark, dry and well seasoned. If dipped for immersion treatment, allow to remain in solution for 12 to 48 hours.

Wood to be in contact with soil should be brushed or sprayed with at least two flowing coats or dipped for not less than 3 minutes for each inch of thickness.

Creosote Oil has a high degree of penetration. Is an excellent weed killer for weeds along roads, highways, and fences. Weeds should be sprayed with undiluted Creosote Oil to point of run off, once or twice a season. Avoid spray drift to desirable plants. Do not contaminate water used for irrigation or domestic purposes.

CAUTION:

KEEP OUT OF REACH OF CHILDREN

Avoid breathing fumes or vapors of Creosote Oil. Avoid contact with skin. If spilled on hands, wash well with soap and water. Harmful if swallowed. Keep out of the reach of children.

Do not use in dairy barns or poultry houses. Wear rubber gloves when handling freshly treated lumber. Do not re-use empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place. This product is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of wastes.

EPA Reg. No. 421 - 899

A Product of *James Varley & Sons, Inc.* ST. LOUIS, MO.

Net Contents