

ACCEPTED
 MAR 22, 1973
 UNDER THE FEDERAL
 INACTIVE
 #438-10

QUALITY PRODUCTS SINCE 1927

**DIRECTIONS
 FOR LAUNDRY USE**

Use STACHLOR BLEACH with any good laundry detergent or soap. STACHLOR bleaches, removes stains, deodorizes, and disinfects.

MACHINE LAUNDERING: In top loading automatics and wringer washers, use 3/4 cup STACHLOR per load. For front loading washers, use 1/2 cup per load. STACHLOR BLEACH SHOULD BE ADDED TO THE WASH WATER BEFORE LAUNDRY.

HAND LAUNDERING: Use 1 1/4 to 2 tablespoons of STACHLOR per two gallons of water. Add STACHLOR to water before adding garments.

STAIN REMOVAL: Stains caused by fruit, vegetables, grass, coffee, tea, chocolate, wine, many inks, and medicines, plus mildew and scorch; use 1/3 cup STACHLOR per gallon of hot water. Before laundering, soak entire stained item in the solution for 5 minutes. Rinse well, and repeat if necessary. USE COOL WATER SOLUTION FOR STAINS THAT CAN BE SET BY HOT WATER. EXAMPLE: EGG, MILK, OR BLOOD, COLORED OR DELICATE FABRICS.

NYLON FABRICS YELLOWED WITH AGE: Soak 20 to 30 minutes in solution of 1 1/2 to 2 tablespoons STACHLOR BLEACH per 1 gallon of water and 1 tablespoon of household vinegar. Rinse, repeat if necessary.

BLEACH TEST: Before using STACHLOR BLEACH on colors, or special finishes, test for color fastness by soaking an inconspicuous portion of the fabric for 5 minutes in a solution of 1 1/2 tablespoons STACHLOR BLEACH in 2 gallons of hot, sudsy water.

FOR INDUSTRIAL USE ONLY

TO DISINFECT, DEODORIZE, AND REMOVE STAINS:
 From Bath Tubs, Showers, Sinks, Drainboards, Refrigerators,
 (cont. on other side of panel)

STACHLOR BLEACH



E.P.A. Reg. No. 438-60

ACTIVE INGREDIENTS

Sodium Hypochlorite 7.35% by weight

INERT INGREDIENTS

92.65% by weight

CAUTION KEEP OUT OF REACH OF CHILDREN.
 DO NOT TAKE INTERNALLY. SEE SIDE
 PANEL FOR ADDED PRECAUTIONS.

KEEP IN A COOL PLACE
 NET CONTENTS - 5 U.S. GALS.

Stoves, Dishes, Glassware, Enamelware, Tile, Plastic, Marble and Porcelain; wash thoroughly, then wipe with a solution of 4 tablespoons (2 fluid ounces) STACHLOR BLEACH. (If stain persists, keep wet with STACHLOR BLEACH solution for 5 minutes.) Repeat if necessary. Do not use on aluminum, chipped enamelware, or silver. NOTE: After glassware has been disinfected, rinse with potable water.

TOILET BOWLS & URINALS: Clean, flush, and add 1/3 cup STACHLOR BLEACH, then swish solution over insides. Let stand 1 to 15 minutes in a solution of 4 tablespoons STACHLOR BLEACH to each 1/2 gallon of hot water. Rinse, and drain dry.

AS AN EMERGENCY TREATMENT FOR DRINKING WATER: As a precaution against bacterial contamination, add 1 1/2 tablespoons STACHLOR BLEACH to 10 gallons of water, or 10 drops of STACHLOR BLEACH to 1 gallon of water. Allow to stand 10 minutes before drinking.

SEPTIC TANK OPERATION IS NOT AFFECTED BY USE OF STACHLOR BLEACH.
 Degrades with age. Use a test kit and increase dosage as necessary to obtain required level of available chlorine.

CAUTION

HARMFUL IF SWALLOWED. SKIN AND EYE CONTACT MAY CAUSE SEVERE IRRITATION.

ANTIDOTE-EXTERNAL: In case of contact with eyes, or skin; flush thoroughly with water.

ANTIDOTE-INTERNAL: If swallowed, drink raw egg white, milk or rice gruel. Follow with emetic (tablespoon of mustard in glass of warm water). CALL PHYSICIAN IMMEDIATELY.

12-72

STATE CHEMICAL COMPANY TEXAS 79105