

CAUTION
COMBUSTIBLE MIXTURE

N. Y. I. D. C. of A. No. 1774

DIRECTIONS FOR USE

This product is a ready to use clean oil solution useful for the protection of wood against fungus growths which cause rot and stain, termites, Lytus (powder post) beetles and carpenter ants. It contains water repellents to aid in the control of shrinking, swelling, and checking, grain raising and warping.

WOOD PRESERVATION AND DIMENSIONAL CONTROL

For best results, this product should be applied so as to effect maximum penetration into the wood and heavy absorption, especially at joints and wherever end grain exists. A 3 minute immersion period is recommended for cutwork. For other open tank treatments, complete immersion of the wood in the solution is generally recommended for five minutes per inch of thickness. For the control of dimensional changes, shrinkage and swelling, the treatment of the end grain is most important since the moisture pick up there is a hundred to a thousand times greater than at the flat or large grain surface for many species of wood.

Where open tank treating is impractical as in the case of an existing structure, two heavy brush applications of this product should be applied, cutting out and removing all ground wood ten feet beyond any visible evidence of decay. All wood should be normally dry, and the framing or cutting completed before application of this product.

COVERAGE: Approximately 5 to 10 gallons per thousand board feet for open tank treating; 400 square feet per gallon for brush application on smooth woods. Textured surfaces absorb more solution.

This product is effective for application to wood for the control of termites, powder post (lytus) beetles and carpenter ants. In all of these cases, it will be effective only in the areas of the wood contacted by the solution. Therefore, thoroughness of treatment is essential to good control.

TERMITE CONTROL: For protection of new wood prior to installation, see instructions above. For application to wood in place to protect against subterranean termite damage, apply the solution to run off, allow to soak in, and make at least one more application. Care must be exercised that the solution does not contact asphaltic products (tar paper, composition shingles, or other such items) or that it is not applied in such a way that it will stain plaster or other surfaces. Treatment of the wood is supplemental to soil treating.

POWDER POST BEETLE CONTROL: Lumber, flooring or other items infested with powder post beetles can be controlled by immersing the wood in this product for a minimum of 5 minutes per inch of thickness. Since there is a potential hazard from dermal contact after treatment of floors, furniture and the like, re-waxing of these items after treatment with a heavy duty paste wax, after the solvent has evaporated, is necessary to insure against this hazard.

CARPENTER ANTS: This product applied to infested wood either by spraying or by injection into the cavities made by the ants, has proved useful for clearing out ants, swarms in the wood. Since poisoning of the colony of these insects is the most timely treatment of infested wood, use is fully complementary.



WOODTOX
READY TO USE



WATER REPELLENT & PENTA WOOD PRESERVATIVE

Preserves windows, flooring, siding, fences and all wood safe from rot, mildew discoloration and Termites — Helps control shrinkage and swelling — Minimizes warping, grain raising and checking.

DOUBLE PROTECTION:

- Long lasting water repellents keep out moisture which causes warping & swelling.
- Long lasting PENTA fungicide protects against decay, staining fungi and mold.

SURFACES PAINTABLE AFTER TREATMENT.

WOOD TREATING CHEMICALS DEPT.

KOPPERS COMPANY, INC.

5137 SOUTHWEST AVENUE, ST. LOUIS, MISSOURI 63109

WARNING: KEEP OUT OF REACH OF CHILDREN

See side panel for other warnings

SEE LIMIT OF WARRANTY AND LIABILITY BEFORE BUYING OR USING

IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN TO SUPPLIER UNOPENED

EPA Reg. No. 453-41

EPA Est. 453-MO-1

ACTIVE INGREDIENTS:	
Pentachlorophenol*	4.47%
Other Chlorophenols & Related Compounds*	52%
Mineral Spirits	24.55%
INERT INGREDIENTS	18.49%

* EPA Health Hazard Division, 40 CFR 151.103, 151.104, 151.105, 151.106, 151.107, 151.108, 151.109, 151.110, 151.111, 151.112, 151.113, 151.114, 151.115, 151.116, 151.117, 151.118, 151.119, 151.120, 151.121, 151.122, 151.123, 151.124, 151.125, 151.126, 151.127, 151.128, 151.129, 151.130, 151.131, 151.132, 151.133, 151.134, 151.135, 151.136, 151.137, 151.138, 151.139, 151.140, 151.141, 151.142, 151.143, 151.144, 151.145, 151.146, 151.147, 151.148, 151.149, 151.150, 151.151, 151.152, 151.153, 151.154, 151.155, 151.156, 151.157, 151.158, 151.159, 151.160, 151.161, 151.162, 151.163, 151.164, 151.165, 151.166, 151.167, 151.168, 151.169, 151.170, 151.171, 151.172, 151.173, 151.174, 151.175, 151.176, 151.177, 151.178, 151.179, 151.180, 151.181, 151.182, 151.183, 151.184, 151.185, 151.186, 151.187, 151.188, 151.189, 151.190, 151.191, 151.192, 151.193, 151.194, 151.195, 151.196, 151.197, 151.198, 151.199, 151.200

NET CONTENTS U.S. GALLONS

WARNING

Keep out of reach of children. Do not use in areas where children play. Do not use in areas where food is prepared or stored.

Do not breathe vapors. Do not get in eyes. Wash thoroughly after handling.

Wear protective clothing and rubber gloves when handling the freshly treated lumber.

DO NOT USE NEAR OPEN FLAMES OR HEAT SOURCES.

FIRST AID: If swallowed, induce vomiting by tickling down throat or by giving soap or strong salt. Do not drink. Repeat until vomit is clear. Call a physician. Give nothing by mouth to an unconscious person.

FIRST AID: In case of contact with skin, wash with water. If in eyes, flush with water for at least 15 minutes and get medical attention.

NOTE TO PHYSICIAN: This product is a metabolite causes hyperthermia. Treat symptomatically.

This product is toxic to fish, wildlife, and domestic animals. Keep out of lakes, streams, and ponds. Keep away from crops when not in use. Do not contaminate water. Cleaning of equipment or disposal of wastes. Apply product only as directed on this label.

Vapors may cause injury if adequate ventilation is not assured. Do not use this product indoors, or any other confined areas, where the vapors may concentrate and cause injury to plant or animal life.

Apply this product only as specified on this label.

NOTICE

Avoid contamination of feed or foodstuffs. Do not reuse container. Return to dealer for destruction and burn in a safe place. Do not contaminate water by cleaning equipment or disposal of wastes.

Treated sawdust and other wood wastes should not be in contact with domestic animals, or be spread in areas where it will come in contact with useful beings.

LIMIT OF WARRANTY AND LIABILITY

This company warrants that the material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the directions for use. This product is sold subject to the understanding that the Buyer assumes all risks of use or handling which may result in loss or damage which are beyond the control of the seller, such as, for example, incompatibility with other products and the manner of application. **NO OTHER EXPRESSED OR IMPLIED WARRANTIES OF FITNESS OR MERCHANTABILITY IS MADE.** The exclusive remedy of the buyer, and the limit of liability of the company or any other seller for any and all losses, injuries or damages resulting from the use of this product, shall be the purchase price paid for the product. The responsibility of this product is limited to the use of this product as directed on the label. The company is not liable for any damages, including consequential damages, resulting from the use of this product.

