

## FOR INDUSTRIAL USE ONLY

### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

### IMPORTANT! DO NOT DILUTE.

#### FOR EXTERIOR USE ONLY.

This product is a clean oil solution useful for the protection of wood against fungus growths which cause rot and stain. It contains water repellents to aid in the control of shrinking, swelling and checking, grain raising and warping.

For best results, this product should be applied so as to effect maximum penetration into the wood and heavy absorption especially at joints and wherever end grain exists. A 3-minute immersion period is recommended for millwork. For other open tank treatments, complete immersion of the wood in the solution is generally recommended for five minutes per inch of thickness. For the control of dimensional changes, shrinkage and checking, the treatment of the end grain is most important since the moisture pick-up there is a hundred to a thousand times greater than at the flat or edge grain surface for many species of wood.

Where open tank treating is impractical, two heavy brush applications of this product should be applied, cutting out and removing all sound wood two feet beyond any visible evidence of decay. All wood should be thoroughly dried and the framing or cutting completed before application of this product.

Estimated Coverage: 5 to 10 gallons per thousand board feet of wood surface to be treated. Allow 1/2 gallon per square foot per gallon for brush application.

### STORAGE AND DISPOSAL

**PROHIBITIONS** Do not contaminate water, food or feed by storage or disposal.

**PESTICIDE DISPOSAL** Pesticide label, in case of insecticide, must be followed. If the label does not specify disposal instructions, the product must be disposed of in accordance with the Federal or approved state procedure under the Subtitle C of the Resource Conservation and Recovery Act.

**CONTAINER DISPOSAL** Do not reuse or refill. If other containers are used, thorough cleaning of pesticide label and instructions must be followed. Do not use other approved state and local procedures.

### LIMIT OF WARRANTY AND LIABILITY

This Company warrants that this product conforms to the description on the label and is free from defects in the material and workmanship under the directions of use. This product is sold as a "stand-alone" product and the buyer assumes all risks of use or handling of this product in strict accordance with the directions given here with which are beyond the control of the seller, such as for example, incompatibility with other products and the manner of its use or application. **NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY IS MADE.** The exclusive remedy of the buyer, and the limit of liability of this company or any other seller for any and all losses, injuries or damages resulting from the use or handling of this product shall be the purchase price paid by the user or buyer for the quantity of this product involved. The buyer and all users are deemed to have accepted the terms of this price which may not be varied by any other agreement.

# KOPPERS®

## WOODTOX® READY TO USE

### WATER REPELLENT WOOD PRESERVATIVE

#### DOUBLE PROTECTION:

- Long lasting water repellents keep out moisture which causes warping & swelling.
- Long lasting PENTA fungicide protects against decay, staining fungi and mold.

#### SURFACES PAINTABLE AFTER TREATMENT.

KEEP OUT OF REACH OF CHILDREN

### WARNING

See side panel for first aid and additional precautionary statements.

READ "LIMIT OF WARRANTY AND LIABILITY"  
BEFORE BUYING OR USING.

IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN  
AT ONCE UNOPENED.

EPA Reg. No. 453-41  
EPA Est. 453-MO-1

#### ACTIVE INGREDIENTS:

Hexachlorophenol*	4.47%
Other Chlorophenols & Related Compounds*	52.00%
Mineral Spirits	34.55%
<b>INERT INGREDIENTS</b>	<b>10.46%</b>

\* 2,4,6-Trichloro-Penta-chlorophenol, a related compound.

**Koppers Company, Inc.**  
**Wood Treating Chemicals Dept.**

5137 Southwest Avenue, St. Louis, Missouri 63110  
(314) 772-2200

NET CONTENTS

U.S. GALLONS

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS (AND  
DOMESTIC ANIMALS)**

**WARNING**

**MAY BE FATAL IF SWALLOWED.  
HARMFUL IF INHALED OR ABSORBED  
THROUGH THE SKIN. CAUSES SKIN  
AND EYE IRRITATION.**

**May be irritating to the respiratory tract.**

Do not get in eyes, on skin or on clothing. Use of goggles and protective clothing (rubber gloves) is recommended when brushing or dipping, and use of an approved respirator when appropriate. Avoid prolonged and/or repeated breathing of vapors, mist or substantially saturated atmosphere. Use only in well ventilated areas. Not for use or storage in or around the home. Keep containers closed when not in use. Do not take internally.

**FIRST AID: If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting.**

**If inhaled, remove to fresh air.**

**In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse.**

**NOTE TO PHYSICIAN: Pentachlorophenol in this product is a metabolic stimulant. Treat symptomatically.**

**ENVIRONMENTAL HAZARDS:**

This product is toxic to fish and wildlife. Do not apply directly to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

This product is toxic to domestic animals. Treated sawdust and other wood wastes should not come in contact with domestic animals or be used as mulch where it will come in contact with useful, living plants. Care should be taken to prevent drip from contacting ornamental shrubs, trees, grass and other desirable vegetation.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors or any other confined areas, where the vapors may concentrate or migrate indoors and cause injury to plant or animal life.

**PHYSICAL OR CHEMICAL HAZARDS COMBUSTIBLE: DO NOT use, pour, spill or store near heat or open flame.**

**IN CASE OF FIRE: Use dry chemicals, foam, water fog or CO<sub>2</sub>. Cool closed containers with water.**

FPL 1166 R 07 8205

