

This product is a clean oil solution useful for the protection of wood against fungus growths which cause rot and stain, termites, Lyctus, powder post beetle, and carpenter ants, and contains water repellents to aid in the control of checking, warping and checking, grain raising and swelling.

DIRECTIONS FOR USE

WOOD PRESERVATION AND DIMENSIONAL CONTROL

For best results, this product should be applied so as to effect maximum penetration into the wood and heavy absorption especially at joints where end grain exists. For best results, a 24-hour period is recommended for open tank or open tank treatments, complete absorption of the Woodtox solution is generally achieved in five minutes per inch of thickness. The control of dimensional change, such as checking, swelling, the treatment of the end grain is particularly important since the moisture pickup in the end grain is a thousand times greater than in the flat or edge grain surface for many species of wood.

Where open tank treating is impractical as in the case of an existing structure, two heavy brush applications of this product should be applied, cutting out and removing all unsound wood two feet beyond any visible evidence of decay. All wood should be normally dry, and the framing or cutting completed before application of this product.

Do not paint or varnish wood that has been treated with this product until the excess petroleum solvents have volatilized from the wood.

Estimated Coverage: 5 to 10 gallons per thousand board feet for open tank treating, 200 square feet per gallon for brush application.

PRESSTREAT

REC-29 1968
 45583
 Assignment

Prevents decay and sapstain and kills termites

A ready-to-use water repellent wood preservative, suitable for use in commercial pressure treating plants. It is formulated to meet the requirements of the performance standards of the American Wood Preservers Institute (AWPI) for water repellent preservatives, and for dimensional stabilization and for protection.

CAUTION: KEEP OUT OF REACH OF CHILDREN

4.50
 5.50
 85.05
 9.95/11

Warning: Harmful if swallowed or absorbed through skin! Causes skin irritation! Do not breathe vapors or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.
 Do not store or use near open flame. Avoid contamination of feed and food stuffs.

WOOD TREATING CHEMICALS CO.

5137 SOUTHWEST AVE. • ST. LOUIS, MO. 63110

ESDA Reg. No. 453-83

GALLON

This product is effective for application to wood for the control of termites, powder post, Lyctus, beetle and carpenter ants. In all of these cases, it will be effective only in the area of the wood contacted by the solution. Therefore, thoroughness of treatment is essential to good control.

DIRECTIONS FOR USE

TERMITE CONTROL. For protection of new wood prior to installation, see instructions on other parts of this label. For application to wood in place to protect against subterranean or drywood termite damage, apply the solution to run-off, allow to soak in, and make at least one more application. Care must be exercised that the solution does not contact asphaltic products, tar paper, composition shingles, or other such items, so that it is not applied in such a way that it will stain plaster or other surfaces. Treatment of the wood is supplemental to soil treating.

POWDER-POST BEETLE CONTROL. Lumber, flooring or other items infested with powder post beetles can be controlled by increasing the wood in this product for a minimum of 5 minutes per inch of thickness. Because special precautions must be taken for application to infested floors, furniture and the like, contact the manufacturer for information on these types of uses.