

This product is a clean oil solution useful for the protection of wood against fungus growths which cause rot and stain, termites, Lyctus (powder post) beetles and carpenter ants and contains water repellents to aid in the control of shrinking, swelling and checking, grain raising and warping.

DIRECTIONS FOR USE

WOOD PRESERVATION AND PROTECTION
 This product is used for the protection of wood against rot, stain, termites, Lyctus (powder post) beetles and carpenter ants. It is also used to control shrinking, swelling and checking, grain raising and warping. It is generally recommended for the protection of wood in contact with the ground, in contact with water, or in contact with other wood. It is also used for the protection of wood in contact with the ground, in contact with water, or in contact with other wood. It is also used for the protection of wood in contact with the ground, in contact with water, or in contact with other wood.

Do not paint or varnish wood that has been treated with this product until the excess petroleum solvents have volatilized from the wood.

Estimated Coverage: 5 to 10 gallons per thousand board feet for open tank treating; 200 square feet per gallon for brush application.

USDA Reg. No. 451.14

ACCEPTED

COMPOSITION A

WOOD PRESERVATIVE

WATER-BASED

FEDERAL SPECIFICATION TTW-572
 (MAY 1955)

WARNING: KEEP OUT OF REACH OF CHILDREN

Active Ingredient	40
Water	50
Other Ingredients	10
Total	100

WOOD TREATING CHEMICALS

This product is effective for application to wood for the control of rot, stain, termites, Lyctus (powder post) beetles and carpenter ants. It is also used to control shrinking, swelling and checking, grain raising and warping. It is generally recommended for the protection of wood in contact with the ground, in contact with water, or in contact with other wood.

DIRECTIONS FOR USE

WOOD PRESERVATION AND PROTECTION
 This product is used for the protection of wood against rot, stain, termites, Lyctus (powder post) beetles and carpenter ants. It is also used to control shrinking, swelling and checking, grain raising and warping. It is generally recommended for the protection of wood in contact with the ground, in contact with water, or in contact with other wood. It is also used for the protection of wood in contact with the ground, in contact with water, or in contact with other wood.

CAUTION: This product is highly flammable. Keep away from fire and heat. Do not use in confined spaces. Do not breathe vapors. Do not get on skin or clothing. Wash with soap and water after contact with skin. Do not eat, drink, or smoke while using this product.

WARNING: Harmful if swallowed or absorbed through skin. Causes skin irritation. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing.

Wash with soap and water after contact with skin. Do not eat, drink, or smoke while using this product.