FOR MILITARY USE ONLY
WARNING

[illegible] surface sealing

FIRE HAZARD The solvent used in the preservatives may have a flash point as low as 100 F (37.8 C) and care should be taken to prevent fire. No smoking, welding, or other source of fire should be permitted near the treating operation, or near treated material until after 24 hours of drying under conditions of adequate ventilation to insure removal of flammable vapors. Treating should be done out of doors or in a thoroughly ventilated room. Adequate precautions to prevent fire should be taken in [illegible] the preservatives.

IRRITATING EFFECT Some of the ingredients used in pre[illegible] may be irritating to the skin [illegible] greatly [illegible] them. Adequate [illegible] and other protective [illegible] of protective ointments and of protective clothing is recommended if applied by spraying. Goggles and respirators should be worn. Workmen should avoid the use of [illegible]

APPLICATION [illegible] before [illegible] the application [illegible] to a [illegible] and [illegible] When [illegible] treat[illegible] should be [illegible] to assembly [illegible] the [illegible] where the preservatives are likely to affect the [illegible] the preservatives should be [illegible] after [illegible] preservatives should be applied [illegible]

DIRECTIONS FOR CIVILIAN USE

WOOD PRESERVATION

KOPPERS

WOOD PRESERVATIVE SURFACE SEALING COMPOUND

WARNING

FIRST AID

[illegible] TO PHYSICIAN

ENVIRONMENTAL CAUTION

ACCEPTED
10 APR 1975
UNDER [illegible]
453-532

NOTICE

WOOD TREATING CHEMICALS DEPT

WARNING: KEEP [illegible]

USE OF PRESERVATIVE AND [illegible]

NET CONTENTS US GALLONS