SUPER DIPRITE.

SAPSTAIN CONTROL CHEMICAL

SUPER DIPRITE is a fungicide recommended for the control of sapstain and mold that degrade lumber and poles, posts and other forest products during the seasoning period. This product has an excess of alkalinity so that it is generally unnecessary to add soda ash or similar alkaline materials when dipping oak.

For use under normal seasoning weather conditions, use 10 pounds of SUPER DIPRITE per 100 U.S. gallons of water on lumber 2 inches or less in thickness, making sure the lumber is completely submerged in the dip solution.

for use during rainy seasons or under conditions where seasoning takes place very slowly and for the treatment of heavy timber by dip or spray, use double strength (20 pounds per 100 gallons of water).

EPA-Reg. 453-245

ACCEPTED

WAY 24 1974

UNDER THE FEDERAL INSECTIONS

PUNGICIDE AND RODENTICIDE ACT

FOR ECONOMIC POISON REGISTER
ED UNDER TO 455 AY 5 SUBJECT

TO ATTACHED COMMENTS.



WOOD PRESERVATIVE

FOR CONTROL OF STAIN AND MOLD ORGANISMS WHICH DEGRADE LUMBER AND OTHER FOREST PRODUCTS

ACTIVE INGRELIENTS:	
Sodium pentachlorophenate*	27.65%
Sodium salts of other chlorinated phenols*	3.85%
Sodium tetraborate pentahydrate	49.66%
Sodium carbonate (Soda Ash)	12.34%
INERT INGREDIENTS:	6.50%
Total	100.00%

WARNING

KEEP OUT OF REACH OF CHILDREN

Harmful or fatal if swallowed or absorbed through skin. Do not breathe dust or spray dust. In case of swallowing, induce vomiting by administering mustard and water or other emetic. Call a physician. Causes skin initiation of not get in eyes, on skin or on clothing. In case the dry material or its solution gets on the skin, wash with plenty and warm water; if in the eyes, flush with copious quantities of water for several minutes.

Wear rubber gloves and protective clothing when handling the freshly treated lumber.

This product is toxic to fish and wildlife. Keep out of any body of water. Do not contaminate water by cleaning of equipment or disposal of waste.

Do not reuse container. Destroy by burning or crushing and burying in non-cropland away from water supplies. If burned, keep out of smoke and fumes.

LIMIT OF WARRANTY AND LIABILITY

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the directions for use. This product is sold subject to the understanding that the buyer assumes all risks of use or handling which may result in loss or damage which are beyond the control of the seller, such as for example incompatibility with other products and the manner of its use of application. NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY IS MADE. The exclusive remedy of the buyer, and the limit of liability of this company or any other seller for any and all losses, injuries or damages resulting from the use or handling of this product shall be the purchase price paid by the user or buyer for the quantity of this product involved. The buyer and all users are deemed to have accepted the terms of this notice which may not be varied by any verbal or written agreement.

WOOD TREATING CHEMICALS DEPT.

KOPPERS COMPANY, INC.

5137 SOUTHWEST AVENUE, ST. LOUIS, MISSOURI 63110