

DIRECTIONS

This product can be diluted with either oil or water. Although oil solutions give longer residual protection and are usually more effective for spray application, either oil or water can be used as a diluent as indicated below.

An oil spray solution is prepared by adding one gallon of this product to 28 gallons of kerosene, diesel oil or No. 2 fuel oil.

FOR PROTECTION OF LOGS IN THE WOODS AGAINST AMBROSIA BEETLES AND WOOD BORERS BY SPRAYING:

For best results, the logs should be sprayed as soon as possible after the trees have been felled and the logs bucked. Thorough wetting of all log surfaces — bark and ends, is essential to good control. One gallon of the diluted material will usually cover 100 square feet of log surface.

FOR PROTECTION OF LUMBER AGAINST AMBROSIA BEETLES BY SPRAYING:

The diluted product can be sprayed on the lumber before it is stacked, or after the lumber is in the seasoning stacks. When spraying stacked lumber, use a high pressure sprayer equipped with a nozzle that produces a fine mist. Direct the spray so that the mist gets into all air spaces between the lumber in the stack. Usually 3 to 4 pints of solution will treat 1,000 board feet of 1-inch lumber.

FOR PROTECTION OF DECKED LOGS AGAINST BARK BEETLES:

To keep bark beetles out of decked or "yarded" logs, add one gallon of this product to 56 gallons of diesel or No. 2 fuel oil. Apply by spraying so that the spray mist reaches all surfaces of the logs — not just the ends of the logs. One gallon of this diluted material will usually protect 100 square feet of log surface.

FOR PROTECTION OF LUMBER AGAINST AMBROSIA BEETLES IN CONJUNCTION WITH ANTI-STAIN DIP TREATMENT:

Water base emulsions can be prepared by diluting this product with water, and the lumber can be dipped therein or the emulsion can be added to the SUPER NOXTANE in the dip vat. In either case, the material should be agitated to produce a suitable milky emulsion before use and agitation during use may be necessary to insure a good emulsion.

One gallon of this product added to 160 gallons of anti-stain chemical in the dip vat (such as Super Noxtane solution) gives a concentration of BHC that has given uniformly good results over many years.

Wear synthetic rubber gloves or plastic coated gloves in handling solution and freshly treated lumber.

NOTICE

Avoid contamination of feed or food stuffs.

Do not reuse container. Return to drum reconditioner or destroy and bury in a safe place.


Treated sawdust and other wood wastes should not come in contact with domestic animals, or be used as mulch where it will come in contact with useful living plants.

KOPPERS

TIMBERTREATTM 95 INSECTICIDE



For dip and spray application to green logs and lumber for control of Ambrosia Beetles and Wood Borers during storage.



TRADEMARK OF
WOOD TREATING CHEMICALS DEPT.

KOPPERS COMPANY, INC.

5137 SOUTHWEST AVENUE, ST. LOUIS, MISSOURI 63110

WARNING: KEEP OUT OF REACH OF CHILDREN.

See side panel for other warnings.

READ "LIMIT OF WARRANTY AND LIABILITY" BEFORE BUYING OR USING.

IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN AT ONCE UNOPENED.

ACTIVE INGREDIENTS:

Gamma isomer of Benzene Hexachloride	11.22%
Other Isomers of Benzene Hexachloride	15.18%
Petroleum Solvents	59.60%
INERT INGREDIENTS	14.00%
Total	100.00%

EPA Reg. No. 453-260

NET CONTENTS

U.S. GALLONS

WARNING

MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION. COMBUSTIBLE.

Do not breathe spray mist. Use only with adequate ventilation. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.

Do not use, pour, spill or store near heat or open flame.

FIRST AID: If swallowed induce vomiting by sticking finger down throat or by giving soapy or strong salty water to drink. Repeat until vomit is clear. Call a physician. Never give anything by mouth to an unconscious person.

FIRST AID: In case of contact, wash skin with soap and water, for eyes, flush with water for at least 15 minutes and get medical attention.

This product is toxic to fish and wildlife. Keep out of lakes, streams and ponds. Birds feeding on treated areas may be killed. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not use on household pets or livestock.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapors may concentrate and cause injury to plant or animal life.

LIMIT OF WARRANTY AND LIABILITY

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the directions for use. This product is sold subject to the understanding that the buyer assumes all risks of use or handling which may result in loss or damage which are beyond the control of the seller, such as for example incompatibility with other products and the manner of its use or application. NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY IS MADE. The exclusive remedy of the buyer, and the limit of liability of this company or any other seller for any and all losses, injuries or damages resulting from the use or handling of this product shall be the purchase price paid by the user or buyer for the quantity of this product involved. The buyer and all users are deemed to have accepted the terms of this notice which may not be varied by any verbal or written agreement.

11572-2