

DIRECTIONS FOR USE

Wear synthetic rubber gloves or plastic coated gloves in handling solutions and freshly treated lumber.

Lumber should be anti-stain treated within 24 hours after cutting. Delayed application may permit interior stain. Freshly sprayed or dipped lumber should be protected from rain washing. Tanks should be covered by a roof to prevent the addition of rain water and consequent dilution of the solution.

Be sure that vats and spray equipment are cleaned regularly to remove sawdust and other debris.

MIXING INSTRUCTIONS — Mix one gallon of this product per 100 gallons of water for lumber 2" or less in thickness to protect against sap staining organisms during protracted storage periods.

Lumber should be totally immersed or sprayed so as to insure all surfaces are treated. For lumber thicker than 2", or where temperature and humidity conditions promote severe sapstain, use double strength solution.

Put about 1/2 of the water to be used in the mixing tank. Add the correct amount of this product and rinse container into the tank. Add the balance of water needed and mix thoroughly.

When using proportioning pumps for mixing, this product should be maintained at temperatures higher than 50 degrees F. to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting on the pump dial.

NOTICE

Avoid contamination of feed or foodstuffs.

Do not reuse container. Return to drum reconditioner or destroy and bury in a safe place. Do not contaminate water by cleaning equipment or disposal of waste and containers.

Treated sawdust and other wood wastes should not come in contact with domestic animals, or be used as mulch where it will come in contact with useful living plants.

ACCEPTED

JUL 28 1975

UNDER THE FEDERAL INSECTICIDE,
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTRATION
NO. 453-261

LIQUID NOXTANE® SS1 wood fungicide



For control of sapstain and mold on freshly cut species of lumber, including Douglas Fir, White Fir, Southern Yellow and Western Pines, and Hemlock.

TRADEMARK OF
WOOD TREATING CHEMICALS DEPT.

KOPPERS COMPANY, INC.

5137 SOUTHWEST AVENUE, ST. LOUIS, MISSOURI 63110

WARNING:

See side panel for other warnings.

KEEP OUT OF REACH OF CHILDREN

READ "LIMIT OF WARRANTY AND LIABILITY"
BEFORE BUYING OR USING.

IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN
AT ONCE UNOPENED.

EPA Reg. No. 453-261

EPA Est. 453-MO-1

EPA Est. 33907-CA-01

ACTIVE INGREDIENTS:	
Pentachlorophenol	13.96%
Tetrachlorophenol	8.14%
Other Chlorophenols	5.52%
INERT INGREDIENTS:	
.....	72.38%
Total	100.00%

NET CONTENTS 55 U.S. GALLONS

MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES SKIN AND EYE IRRITATION. MAY CAUSE DELAYED CHEMICAL BURNS. COMBUSTIBLE.

Do not get in eyes, on skin or on clothing. Do not breathe vapor or spray mist.

Wear protective clothing and rubber gloves when handling this product or freshly treated lumber. Use only with adequate ventilation.

Do not use, pour, spill or store near heat or open flame.

FIRST AID: If swallowed induce vomiting by sticking finger down throat or by giving soapy or strong salty water to drink. Repeat until vomit is clear. Call a physician. Never give anything by mouth to an unconscious person.

FIRST AID: In case of contact, wash skin with soap and water, for eyes, flush with water for at least 15 minutes and get medical attention.

NOTE TO PHYSICIAN: This product is a metabolic stimulant, causes hyperthermia. Treat symptomatically.

ENVIRONMENTAL CAUTIONS: This product is toxic to fish and wildlife. Keep out of any body of water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapors may concentrate and cause injury to plant or animal life. Keep containers closed when not in use.

Care should be taken to prevent drip or spray from contacting ornamental shrubs, trees, grass, and other desirable vegetation.

LIMIT OF WARRANTY AND LIABILITY

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the directions for use. This product is sold subject to the understanding that the buyer assumes all risks of the use or handling which may result in loss or damage which are beyond the control of the seller, such as for example incompatibility with other products and the manner of its use of application. NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY IS MADE. The exclusive remedy of the buyer, and the limit of liability of this company or any other seller for any and all losses, injuries or damages resulting from the use or handling of this product shall be the purchase price paid by the user or buyer for the quantity of this product involved. The buyer and all users are deemed to have accepted the terms of this notice which may not be varied by any verbal or written agreement.