

# KOPPERS

## WOODTOX<sup>®</sup> S CONCENTRATE



### WATER REPELLENT WOOD PRESERVATIVE

Specially formulated for treatment of millwork prior to factory or field priming. Diluted product meets NWMA standards and Federal Specification TT-W-572B, Comp A.

**DILUTION:** Before using, dilute at the ratio of one part this product to five parts by volume of a mineral spirits, naphtha, or equivalent solvent weighing not more than 6.58 lbs./gal. to make a ready-to-use solution containing not less than 5.2% Technical Pentachlorophenol by weight. The diluent should have an end point no greater than 360° F. for quick drying and paintability. Agitate thoroughly before using.

### WOOD TREATING CHEMICALS DEPT.

KOPPERS COMPANY, INC.

5137 SOUTHWEST AVENUE, ST. LOUIS, MISSOURI 63117

**CAUTION: KEEP OUT OF REACH OF CHILDREN**

KEEP OUT OF REACH OF CHILDREN  
EYE IRRITANT  
IF ACCIDENTALLY IN CONTACT WITH EYES, WASH WITH WATER AND GET MEDICAL ATTENTION  
KEEP OUT OF REACH OF CHILDREN  
KEEP OUT OF REACH OF CHILDREN

#### ACTIVE INGREDIENTS

Technical Pentachlorophenol  
Methyl Cellulose  
Methyl Silicate

#### INERT INGREDIENTS

Mineral Spirits  
Naphtha  
Water

EPA Reg. No. 153-262  
EPA Est. 153-MG-1

NET CONTENTS U.S. GALLONS

#### DIRECTIONS FOR USE

This product is a clean oil solution useful for the protection of wood against fungus growths which cause rot and stain, termites, Lyctus (powder post) beetles and carpenter ants, and contains water repellents to aid in the control of shrinking, swelling and checking, grain raising and warping.

#### WOOD PRESERVATION AND DIMENSIONAL CONTROL

For best results, this product should be applied so as to penetrate to the maximum penetration into the wood and to penetrate into all joints and wherever end grain exists. A 15-minute immersion period is recommended for millwork. For other open tank treatments, complete immersion of the wood in the solution is generally recommended for five minutes per inch of thickness. For the control of dimensional change, shrinkage and swelling, the treatment of the end grain is most important since the moisture pickup there is multiplied to a thousand times greater than at the flat or edge grain surface for many species of wood.

Where open tank treating is impractical as in the case of an existing structure, two heavy brush applications of this product should be applied, cutting out and removing all unsound wood two feet beyond any visible evidence of decay. All wood should be normally dry, and the framing or cutting completed before application of this product.

Do not paint or varnish wood that has been treated with this product until the excess petroleum solvents have volatized from the wood.

Estimated Coverage: 5 to 10 gallons per thousand board feet for open tank treating, 200 square feet per gallon for brush application.

This product is effective for application to wood for the control of termites and powder post (Lyctus) beetles. In these cases, it will be effective only in the areas of the wood contacted by the solution. Therefore, thoroughness of treatment is essential to good control.

**TERMITE CONTROL:** For protection of new wood prior to installation, see instructions above. Care must be exercised that the solution does not contact asphaltic products (tar paper, composition shingles, or other such items) or that it is not applied in such a way that it will stain plaster or other surfaces. Treatment of the wood is supplemental to soil treating.

**WATER REPELLENT:** For protection of wood against water damage, apply this product to the wood surface. The water repellent will penetrate into the wood and form a protective film on the surface. This film will repel water and prevent it from penetrating the wood. The water repellent will also prevent water from penetrating the wood through joints and cracks.

**Water Repellent:** For protection of wood against water damage, apply this product to the wood surface. The water repellent will penetrate into the wood and form a protective film on the surface. This film will repel water and prevent it from penetrating the wood. The water repellent will also prevent water from penetrating the wood through joints and cracks.

#### NOTICE

Avoid contact with food or foodstuffs.

Do not reuse container. Return to proper disposal or destroy, and burn in a safe place. Do not contaminate water by cleaning equipment or disposing of wastes and containers. Treated sawdust or other wood wastes should not come in contact with domestic animals. Do not be used as fuel where it will cause a fire hazard.

#### CAUTION

KEEP OUT OF REACH OF CHILDREN  
EYE IRRITANT  
IF ACCIDENTALLY IN CONTACT WITH EYES, WASH WITH WATER AND GET MEDICAL ATTENTION

Do not breathe vapors of this product. Wash face and hands thoroughly after handling.

Wear protective clothing and shoes when using on the freshly treated lumber.

**DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.**

**FIRST AID:** If swallowed, induce vomiting by drinking down throat or by giving 1 cup of strong salt water to drink. Repeat until vomit is clear. Call a physician. Do not give anything by mouth to an unconscious person.

**FIRST AID:** In case of contact, wash skin with soap and water, for eyes, flush with water for at least 15 minutes and get medical attention.

**NOTE TO PHYSICIAN:** This product is a metabolic stimulant, causes hyperthermia. Treat symptomatically.

This product is toxic to fish, wildlife and domestic animals. Keep out of lakes, streams and ponds. Keep containers closed when not in use. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors, or in other confined areas where the vapors may concentrate and cause injury to plant or animal life.

#### LIMIT OF WARRANTY AND LIABILITY

This product is warranted to be free from defects in material and workmanship under normal conditions of use. The warranty does not extend to any damage or injury caused by fire, flood, theft, or other causes beyond the control of the manufacturer. The manufacturer shall not be liable for any damage or injury caused by the use of this product in violation of the instructions on the label.

WARRANTY: This product is warranted to be free from defects in material and workmanship under normal conditions of use. The warranty does not extend to any damage or injury caused by fire, flood, theft, or other causes beyond the control of the manufacturer. The manufacturer shall not be liable for any damage or injury caused by the use of this product in violation of the instructions on the label.

453-262

EPL 153-R-03