FOR INDUSTRIAL USE ONLY

DIRECTION FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DILUTE BEFORE USING FOR EXTERIOR USE ONLY.

This product is a clean oil solution useful for the protection of wood against fungus growths which cause rot and stain. It contains water repellents to aid in the control of shrinking, swelling, end checking, grain raising and warping.

For best results, this product should be applied so as to effect maximum penetration into the wood and heavy absorption especially at joints and wherever end grain exists. A 3-minute immersion period is recommended for millwork. For other open tank treatments, complete immersion of the wood in the solution is generally recommended for tive minutes per inch of thickness. For the control of dimensional changes, shrinkage and swelling, the treatment of the end grain is most important since the moisture pick-up there is a rundred to a thousand times greater than at the first or edge grain surface of many species of wood.

Where open tank treating is impractical, two heavy brush applications of this product should be applied, cutting out and removing all unsound wood two feet beyond any visible evidence of decay. All wood should be normally dry, and the framing or cutting completed before application of this product.

Do not paint or varnish wood that has been treated with this product until the excess petroleum solvents have volatized from the wood

Estimated Coverage: 5 to 10 gallons per thousand board feet for open tank treating, 200 square feet per gallon for brush application.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinse water that cannot be used according to lahel instructions must be disposed of recording to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Triple rinse (or equivalent) Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures LIMIT OF WARRANTY AND LIABILITY

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the directions for use. This product is sold subject to the understanding that the buyer assumes all risks of use or handling of this material not in strict accordance with the directions given herewith which are beyond the control of the seller, such as for example incompatibility with other products and the manner of its use of application. NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY IS MADE. The exclusive remedy of the buyer, and the limit of liability of this company or any other seller for any and all losses, injuries or damages resulting from the use or handling of this product shall be the purchase price paid by the user or buyer for the quantity of this product involved. The buyer and all users are deemed to have accepted the terms of this notice which may not be varied by any verbal or written agreement.

KOPPER5

WOODTOX® 140-T CONCENTRATE WATER REPELLENT WOOD PRESERVATIVE

Specially formulated for treatment of millwork prior to factory or field priming. Diluted product meets NWMA standards and Federal Specification TT-W-572B, Comp A.

ACCEPTED

SEP 2 2 1983

From the Federal Insecticide, religion to, and Redenticide Act, and area alod, for the posticide to the transfer under EFA ling. No. 453-267

Dit.UTION: Before using, dilute at the ratio of one part this product to four parts by volume of a mineral spirits, naphtha, or equivalent solvent weighing not more than 6.54 lbs./gal. to make a ready-to-use solution containing not less than 5.2% Technical Pentachlorophenot by weight. The diluent should have an end point no greater than 360° F. for quick drying and paintability. Agitate thoroughly before using. This product contains a minimum of 1.78 pounds of Technical Pentachlorophenol per gallon of concentrate.

KEEP OUT OF REACH OF CHILDREN WARNING

See side panel for first aid and additional precautionary statements.

READ "LIMIT OF WARRANTY AND LIABILITY" BEFORE BUYING OR US-ING. IF SUCH TERMS ARE NOT AC-CEPTABLE, RETURN AT ONCE UNOPENED.

EPA Reg. No 453-267 EPA Est. 33760-OR 01 ACTIVE INGREDIENTS:
Pentachlorophenoi* 18.92%
Other Chlorophenois and
Related Compounds* 2.20%
INERT INGREDIENTS 78.88%
Total 100.00%
*22.0% Technical Pentachlorophenoi
as defined in Fed Spec. TT-W-570.

Koppers Company, Inc.
Wood Treating Chemicals Dept.
5137 Southwest Avenue, St. Louis, Missouri 63110
(314) 772-2200

NET CONTENTS

U.S. GALLONS

PRECAUTION HAZARDS (ANIMALS)

MAY BE FAT ABSORBED AND EYE IRI CHEMICAL BI

Do not get in engles and protein mended when proved respiratiand/or repeate tially saturate tilated areas, home. Keep Cortake internally.

FIRST AID: H Control Center duce vomiting Do not induce an unconscious

If inhaled, remo

in case of eye of water for 15 skin contact, Remove conta clothes before

NOTE TO PHY duct is a meta ENVIRONMEN

This product is directly to law taminate water of wastes

This product it sawdust and contact with dispersion with a where it will contact should be contamental struggetation.

Vapors may ca insured. Do not confined area migrate indoord life. Keep con-

PHYSICAL OR DO NOT use flame

IN CASE OF FI or CO₂. Cool cl

KOPPERS.

WOODTOX® 140-T CONCENTRATE WATER REPELLENT WOOD PRESERVATIVE

Specially formulated for treatment of millwork prior to factory or field priming. Diluted product meets NWMA standards and Federal Specification TT-W-572B, Comp A.

LCCEPTED.

SEP 2 2 1983

to the Tederal Insecticide, to the the condition Redenticide Act is an included for the position of the tederal under EFFs Reg. No. 463-267

DILUTION: Before using, dilute at the ratio of one part this product to four parts by volume of a mineral spirits, naphtha, or equivalent solvent weighing not more than 6.54 lbs./gal. to make a ready-to-use solution containing not less than 5.2% Technical Pentachlorophenol by weight. The diluent should have an end point no greater than 360° F, for quick drying and paintability. Agitate thoroughly before using. This product contains a minimum of 1.78 pounds of Technical Pentachlorophenol per gallon of concentrate

KEEP OUT OF REACH OF CHILDREN WARNING

See side panel for first aid and additional precautionary statements.

READ "LIMIT OF WARRANTY AND LIABILITY" BEFORE BUYING OR USING. IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN AT ONCE UNOPENED.

EPA Reg. No. 453-267 EPA Est. 33760-OR-01 Pentachlorophenol* 18.92%
Other Chlorophenols and
Related Compounds* 2.20%
INERT INGREDIENTS 78.88%
Total 100.00%
*22.0% Technical Pentachlorophenol

as defined in Fed. Spec. TT-W-570.

Koppers Company, Inc.
Wood Treating Chemicals Dept.
5137 Southwest Avenue, St. Louis, Missouri 63110
(314) 772-2200

NET CONTENTS

U.S. GALLONS

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

WARNING

MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. CAUSES SKIN AND EYE IRRITATION. MAY CAUSE DELAYED CHEMICAL BURNS.

Do not get in eyes, on skin or on clothing. Use of goggles and protective clothing (rubber gloves) is recommended when brushing or dipping, and use of an approved respirator when appropriate. Avoid prolonged and/or repeated breathing of vapors, mist or substantially saturated atmosphere. Use only in well ventilated areas. Not for use or storage in or around the home. Keep containers closed when not in use. Do not take internally.

FIRST AID: If swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

If inhaled, remove to fresh air.

In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse.

NOTE TO PHYSICIAN: Pentachlorophenol in this product is a metabolic stimulant. Treat symptomatically.

ENVIRONMENTAL HAZARDS:

This product is toxic to fish and wildlife. Do not apply directly to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes

This product is toxic to domestic animals. Treated sawdust and other wood wastes should not come in contact with domestic animals or be used as mulch where it will come in contact with useful living plants. Care should be taken to prevent drip from contacting ornamental shrubs, trees, grass and other desirable vegetation.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapors may concentrate or migrate indoors and cause injury to plant or animal life. Keep containers closed when not in use.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE.

DO NOT use, pour, spill or store near heat or open flame

IN CASE OF FIRE: Use dry chemicals, foam, water fog or CO₂. Cool closed containers with water.

FPL 2328 R03 8205

a manner incon-

protection of wood stain. It contains og, swelling, and

e as to effect maxlater especially at immersion period cank treatments, a generally recomfer the central of the treatment of the pick-up there is a flat or edge grain

evy brush applicaut and removing all ence of decay. All cutting completed

ated with this provolatized from the

and board feet for for brush applica-

or feed by storage

or rinse water that rust be disposed of res under Subtitle C

ent) Then offer for a dispose of in a c local procedures.

ins to the chemical ine purposes refersoid subject to the colluse of handling me directions given mer, such as for exity was remainer of its use of the Warranty OF exclusive remedy impany or any other resulting from the hase price paid by stuct involved. The collustry withten agreement