

TRIBUCIDE TP-30



READY TO USE **WATER REPELLENT WOOD PRESERVATIVE**

Preserves Wood—Stops Rot and Decay—Prevents Fungi and Molds of Wood—Clear—Paintable

WARNING

KEEP OUT OF REACH OF CHILDREN

MAY BE FATAL IF SWALLOWED. MAY BE ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION. COMPUSTIBLE.

See side panel for additional precautionary statements.

READ LIMIT OF WARRANTY AND LIABILITY BEFORE BUYING OR USING

IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN AT ONCE UNOPENED

EPA R-g. No. 453-278 FPA E 5, 453 MO-1

ACTIVE INGREDIENTS:

Bis(Tri-n-Butyltin)Oxide30% Pentachiorophenoi* Other Chlorophenois* & .21%

Related Compounds INERT INGREDIENTS 97.73% ** TOTAL 100.00%

*2.08% Technical Pentachlorophenol as de fined in Fed. Spec. TT-W-570

Net Contents . U.S. "Allons (

Liters)

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This preservative is recognized as effective for above ground use, and not recommended for ground contact.

This clear oil solution has been developed for the protection of wood against fungus growths which cause rot and stain. It also contains water repellents to aid in the control of shrinking, swelling, end checking, grain raising and warping.

For the control of dimensional changes, shrinkage and swelling. the treatment of the end grain is most important since the moisture pick-up there is a hundred to a thousand times greater than at the flat or edge grain surface for many speries of wood. For best results, this product should be applied so as to effect greater absorption at joints and wherever end grain exists. All wood should be normally dry, and the framing or cutting completed before application of this product.

This product can be applied to millwork and other wood products by various methods including immersion, brushing, vacuum, pressure and flooding. This product will be effective only in the areas of the wood contacted by the solution. Therefore, thoroughness of treatment is essential.

ESTIMATED COVERAGE: 5 to 10 gallons per thousand beard feet for open tank treatment. 200 square feet per gallon for brush application.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by atorage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Posticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and dispose of in an approved landfill or bury in a safe place.

GENERAL: Consult Federal, State, or local disposal authorities for approved alternative procedures.

LIMIT OF WARRANTY AND LIABILITY

This company warrants that this material conforms to the chemical description on the to in the directions for use. This product is sold subject to the understanding that the not in strict accordance with the directions given berewith which are beyind the conti other products and the manner of its use of application. NO OTHER DARESSED OR IT MADE. The exclusive remedy of the buyer, and the limit of liability of this company or resulting from the use or handling of this product shall be the purchase price paid by t The buyer and all users are deemed to have accepted the terms of this notice which

> KOPPERS COMPANY, INC., WOOD TREAT 5137 SOUTHWEST AVENUE, ST. LOU

PRECAUT

HAZARDO (AND DO

MAY BE ABSORBE IRRITATIO

Do not get in or spray mis handling this

KEEP OUT USE WITH

Vapors may Do not use where vapol mal life. Ke

This product other waste Avoid contar

FIRST AID: if swallowed vomiting. In water; for d minutes and

PHYSICAL O COMBUSTII open flame. IN CASE OF Cool closed

ENVIRONME This produc water. Do disposal of

Treated sai mulch when should be mental shri

This produ



-30



/E

--Prevents

REACH OF CHILDREN

BE ABSORBED

ments.

VE INGREDIENTS:	,
(Tri-n-Butyltin)Oxide	.30%
-tachiorophenoi*	1.76%
Chlorophenois* &	
ated Compounds	.21%
T'INGREDIENTS	97.73%
TOTAL	00.00%
% Technical Pentachloropher	iol as de

llons (Liters)

in Fed. Spec. TT-W-570

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This preservative is recognized as effective for above ground use, and not recommended for ground contact.

This clear oil solution has been developed for the protection of wood against fungus growths which cause rot and stain. It also contains water repellents to aid in the control of shrinking, swelling, end checking, grain raising and warping.

for the control of dimensional changes, shrinkage and swelling, the treatment of the end grain is most important since the moisture pick-up there is a hundred to a thousand times greater than at the flat or edge grain surface for many species of wood. For best results, this product should be applied so as to effect greater absorption at joints and wherever end grain exists. All wood should be normally dry, and the framing or cutting completed before application of this product.

This product can be applied to millwork and other wood products by various methods including immersion, brushing, vacuum, pressure and flooding. This product will be effective only in the areas of the wood contacted by the solution. Therefore, thoroughness of treatment is essential.

ESTIMATED COVERAGE: 5 to 10 gallons per thousand board feet for open tank treatment. 200 square feet per gallon for brush application.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and dispose of in an approved landfull or bury in a safe place

GENERAL: Consult Federal, State, or local disposal authorities for approved alternative procedures

LIMIT OF WARRANTY AND LIABILITY

PRECAUTIONARY STATEMEN.

HAZARDS TO HUMANS
(AND DOMESTIC ANIMALS)

MAY BE FATAL IF SWALLOWED. MAY BE ABSORBED THROUGH SKIN. CAUSES SKIN IRRITATION.

Do not get in eyes, on skin or on clothing. Do not breathe vapor or spray mist. Wear protective clothing and rubber gloves when handling this product or freshly treated lumber.

KEEP OUT OF REACH OF CHILDREN. USE WITH ADEQUATE VENTILATION.

Vapors may cause injury if adequate ventilation is not insured. On not use this product indoors, or any other confined areas, where vapors may concentrate and cause injury to plant or animal life. Keep containers closed when not in use.

This product is toxic to domestic animals. Treated sawdust and other wastes should not come in contact with domestic animals.

Avoid contamination of feed or foodstuffs.

FIRST AID

If swalfowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting. In case of skin contact, wash thoroughly with soap and water; for eyes, flush immediately with plenty of water for 15 minutes and get medical attention. If inhaled, remove to fresh air.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE: Do not use, pour, spill or store near heat or open flame.

IN CASE OF FIRE: Use dry chemicals, foam, water fog or CO_2 . Cool closed containers with water.

ENVIRONMENTAL HAZARDS

This product is texic to fish and wildlife. Keep out of any body of water. Do not contaminate water by cleaning of equipment or disposal of wastes.

Treated sawdust and other wood wastes should not be used as mulch where it will come in contact with useful living plants. Care should be taken to prevent drip or spray from contacting crnamental shrubs, trees, grass, and other desirable vegetation.

This product is phytotoxic and will cause injury to plants on contact.

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the directions for use. This product is sold subject to the understanding that the buyer assumes all risks of use or handling of this material not in strict accordance with the directions given herewith which are beyond the control of the seller, such as for example incompatibility with other products and the manner of its use of application. NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY IS MADE. The exclusive remedy of the buyer, and the limit of liability of this company or any other seller for any and all losses, injuries or damages resulting from the use or handling of this product shall be the purchase price paid by the user or buyer for the quantity of this product involved. The buyer and all users are deemed to have accepted the terms of this notice which may no; be varied by any verbal or written agreement

KOPPERS COMPANY, INC., WOOD TREATING CHEMICALS DEPT. 5137 SOUTHWEST AVENUE, ST. LOUIS, MISSOURI 63110

30

90