

# KOPPERS

FOR INDUSTRIAL USE ONLY

## WOODTREAT<sup>®</sup> MB

**READY TO USE  
WATER REPELLENT  
WOOD PRESERVATIVE**

**ACCEPTED**  
NOV 25 1985  
Under the Federal Insecticide, Fungicide, and Herbicide Act as amended for the first time registered under EPA Reg. No. 453-298

Preserves Wood—Stops Rot and Decay—Prevents Fungi and Molds of Wood—Clear—Paintable

**KEEP OUT OF REACH OF CHILDREN  
CAUTION:**


See side panel for additional precautionary statements.

READ "LIMIT OF WARRANTY AND LIABILITY" BEFORE BUYING OR USING.  
IF SUCH TERMS ARE NOT ACCEPTABLE, RETURN AT ONCE UNOPENED.

ACTIVE INGREDIENT: 3-Iodo-2-Propynyl Butyl Carbamate 0.50%  
INERT INGREDIENTS 99.50%  
TOTAL 100.00%

EPA Reg. No. 453-  
EPA Est. 453-MO-1

Net Contents U.S. Gallons (      Liters)



PRECAUTIONARY STATEMENT  
HAZARDS TO HUMAN AND DOMESTIC ANIMALS

CAUTION: CONTAINS PETROLEUM DISTILLATES. Use only with adequate ventilation. Avoid prolonged breathing of vapor. May be fatal if swallowed. Causes substantial but temporary eye injury. Do not get in eyes, on skin or on clothing. Wear goggles and rubber gloves when handling, and rubber gloves and protective clothing when handling freshly treated lumber. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before re-use.

Vapors may cause injury if adequate ventilation is not insured. Do not use this product indoors or in any other confined areas where vapors may concentrate and cause injury to plant or animal life.

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.

IF SWALLOWED: Do not induce vomiting. Promptly drink a large quantity of milk, egg whites or gelatin solution; if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention immediately.

IF INHALED: Remove victim to fresh air.

IF IN EYES: Flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Treated sawdust and other wood wastes should not be used as mulch where they will come in contact with useful living plants. Care should be taken to prevent drip from contacting ornamental shrubs, trees, grass and other desirable vegetation.

PHYSICAL AND CHEMICAL HAZARDS

COMBUSTIBLE: Do not use, pour, or spill near heat or open flame. In case of fire, use water fog, foam, carbon dioxide or dry chemical. Cool closed containers with water.

FOR INDUSTRIAL USE ONLY

DO NOT DILUTE

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This preservative is recognized as effective for above ground use, and not recommended for ground contact. Woodtreat<sup>®</sup> MB is intended for use on new lumber, plywood, particle board, wafer-board, millwork and similar types of wood products.

This clear oil solution has been developed for the protection of wood against fungus growths which cause rot and stain. It also contains water repellants to aid in the control of shrinking, swelling, end checking, grain raising and warping.

For best results, this product should be applied so as to effect maximum penetration into the wood and heavy absorption especially at joints and wherever end grain exists. A 3-minute immersion period is recommended for millwork. For other open tank treatments, complete immersion of the wood in the solution is generally recommended for five minutes per inch of thickness. For the control of dimensional changes, shrinkage and swelling, the treatment of the end grain is most important since the moisture pick-up there is a hundred to a thousand times greater than at the flat or edge grain surface for many species of wood.

Where open tank treating is impractical, two heavy brush applications of this product should be applied, cutting out and removing all unsound wood two feet beyond any visible evidence of decay. All wood should be normally dry and the framing or cutting completed before application of this product.

ESTIMATED COVERAGE: 5 to 10 gallons per thousand board feet for open tank treatment. 200 square feet per gallon for brush application.

STORAGE AND DISPOSAL

STORAGE: Store in a closed, properly labelled container in a cool place. If static generating conditions exist, provide necessary grounding and bonding. Keep containers closed when not in use.

PESTICIDE DISPOSAL. Do not contaminate water, food or feed by storage or disposal. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL. Triple rinse (or equivalent), Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

LIMIT OF WARRANTY AND LIABILITY

This company warrants that this material conforms to the chemical description on the label and is reasonably fit for the purposes referred to in the directions for use. This product is sold subject to the understanding that the buyer assumes all risks of use or handling of this material not in strict accordance with the directions given herewith which are beyond the control of the seller, such as for example, reactivity with other products and the manner of its use or application. NO OTHER EXPRESSED OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY IS MADE. The exclusive remedy of the buyer, and the limit of liability of this company in any case shall be any and all losses, repairs or damages resulting from the use or handling of this product shall be the purchase price paid by the user or buyer for the quantity of this product involved. The buyer and all users are deemed to have accepted the terms of this notice which may not be varied by any verbal or written agreement.

KOPPERS COMPANY, INC., WOOD TREATING CHEMICALS DEPT.  
5137 SOUTHWEST AVENUE, ST. LOUIS, MISSOURI 63110