

CD-1-35-1536

ACCEPTED  
UNDER THE FEDERAL INSECTICIDE  
FUNGICIDE AND FUNGICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
E.P. UNDER NO. 458-2



E.P.A. Reg. No. 458-2

## WARNING

Do not use near open flame — flash point is 170°F. minimum

- Harmful if swallowed or absorbed thru skin • Causes skin irritation • Do not breathe vapor or spray mist
- Do not get in eyes, on skin, or on clothing • Wear rubber gloves and protective clothing when handling the freshly treated lumber • Wash thoroughly after handling.

Keep away from children, domestic animals, and food-stuffs.

Do not use inside dairy barns, silos, or other structures where it may contact food, feed, or livestock.

Do not contaminate water by cleaning of equipment, or disposal of wastes • Product is toxic to fish and other aquatic life • Keep out of any body of water.

Do not reuse empty container  
• Destroy it by perforating or crushing • Bury or discard in safe place.

Subject to proper handling and storage, this product is warranted to be of merchantable quality and there are no warranties which extend beyond the descriptions hereon. Liability is limited to replacing or giving credit for the purchase price. Manufacturer shall not be liable for any special or consequential damages.

# CREOSOTE OIL

## A LIFE SAVER FOR ALL WOOD

READY TO USE • EASY TO APPLY

<b>Active Ingredients:</b>	
Coal tar oils .....	97%
<b>Inert Ingredients:</b>	
Water .....	3%

## DIRECTIONS

Wood should be dry, well seasoned and entirely free of bark.

Use as received. Apply with brush, mop, sprinkling can, or sprayer.

Or, for best penetration and longest life, soak wood.

### TO BRUSH OR MOP

Flow USOL Creosote Oil on liberally, especially at cracks, cut surfaces and joints. Two or three applications should be made to all wood which will contact the soil.

### TO SPRAY

Apply two or three coats for best protection. Warming oil will make spraying easier.

### TO DIP

Soak for a minimum of five minutes — preferably 15. Posts and heavy building timbers should be soaked for 12 to 48 hours.

NOTE: Oil will always run freely if kept in warm room.

**WARNING: KEEP OUT OF REACH OF CHILDREN**

See side panel for additional warnings.

NET CONTENTS ONE GALLON

MANUFACTURED BY

**STANDARD TAR PRODUCTS CO.**

skin irritation • Do not breathe vapor or spray mist  
 • Do not get in eyes, on skin, or on clothing • Wear rubber gloves and protective clothing when handling the freshly treated lumber • Wash thoroughly after handling.

Keep away from children, domestic animals, and food-stuffs.

Do not use inside dairy barns, silos, or other structures where it may contact food, feed, or livestock.

Do not contaminate water by cleaning of equipment, or disposal of wastes • Product is toxic to fish and other aquatic life • Keep out of any body of water.

Do not reuse empty container  
 • Destroy it by perforating or crushing • Bury or discard in safe place.

Subject to proper handling and storage, this product is warranted to be of merchantable quality and there are no warranties which extend beyond the descriptions hereon. Liability is limited to replacing or giving credit for the purchase price. Manufacturer shall not be liable for any special or consequential damages.

# OIL A LIFE SAVER FOR ALL WOOD

## READY TO USE • EASY TO APPLY

Active Ingredients:  
 Coal tar oils ..... 97%  
 Inert Ingredients:  
 Water ..... 3%

Or, for best penetration and longest life, soak wood.

### TO BRUSH OR MOP

Flow USOL Creosote Oil on liberally, especially at cracks, cut surfaces and joints. Two or three applications should be made to all wood which will contact the soil.

### TO SPRAY

Apply two or three coats for best protection. Warming oil will make spraying easier.

### TO DIP

Soak for a minimum of five minutes – preferably 15. Posts and heavy building timbers should be soaked for 12 to 48 hours.

NOTE: Oil will always run freely if kept in warm room.

## WARNING: KEEP OUT OF REACH OF CHILDREN

See side panel for additional warnings.

NET CONTENTS ONE GALLON

MANUFACTURED BY

## STANDARD TAR PRODUCTS CO.

2456 West Cornell St. Milwaukee, Wis. 53209



CUSTOMER  
 MIDWAY CAN CO.  
 GALLON "F" INSIDE SOLDER

DESIGN  
 USOL CREOSOTE OIL  
 CUT EDGE/20.260" x 9.562"

COLOR SEQUENCE  
 YELLOW BASE, RED & BLACK PRINTS & VARNISH

CUSTOMER  
 Please examine the sketch, engraving, or black and white proofs with care before approving same. Sketches, engraving and negatives for proofs furnished by us remain the property of The Sherwin Williams Company, Cleveland, Ohio, and it will not be responsible for the return of proofs with or without signature for any reason, corrections or necessary corrections overlooked by you. By approving this sketch, engraving, or black and white proofs from the original design, the undersigned customer holds The Sherwin Williams Company harmless for all damages or claims that may be made against it for non-compliance with Local, State or Federal

Laws and regulations, or for conflict with rights of third parties in connection with trademarks, designs, labels, copyrights, patents, or unfair competition. Allowances must be made for variations in colors on sketches and color proofs since colors cannot always be exactly reproduced. Reasonable allowances must be made for normal variation in color when lithographing design. Changes are to be made by written memorandum only. In case of sketches do not make changes by marking, defacing, mutilating or cutting up sketches.



E.P.A. Reg. No. 458-2

# CREOSOTE

## A LIFE SAVER FOR ALL WOOD

### EASY TO APPLY

97%

3%

OUT OF REACH OF CHILDREN

For additional warnings.

NET CONTENTS ONE GALLON

MANUFACTURED BY

### STANDARD TAR PRODUCTS CO.

Milwaukee, Wis. 53209

### DIRECTIONS

Wood should be dry, well seasoned and entirely free of bark.

Use as received. Apply with brush, mop, sprinkling can, or sprayer.

Or, for best penetration and longest life, soak wood.

#### TO BRUSH OR MOP

Flow USOL Creosote Oil on liberally, especially at cracks, cut surfaces and joints. Two or three applications should be made to all wood which will contact the soil.

#### TO SPRAY

Apply two or three coats for best protection. Warming oil will make spraying easier.

#### TO DIP

Soak for a minimum of five minutes — preferably 15. Posts and heavy building timbers should be soaked for 12 to 48 hours.

NOTE: Oil will always run freely if kept in warm room.



# CREOSOTE

## OIL A LIFE SAVER FOR ALL WOOD

### FEATURES

- **PENETRATING** — Soaks in deeply. Dries clean and leaves no sticky surface.
- **LASTING** — Stays in wood and remains effective for years. Insoluble in water. Surfaces will not crack, peel, blister or flake. Cannot be rubbed or scraped off.
- **ECONOMICAL** — Increases life of wood, saving repairs and replacement.
- **CONVENIENT** — No stirring or mixing. Ready for immediate use. Wood can be treated by coating or soaking.
- **ATTRACTIVE** — A rich brown color for all types of buildings.

### THE "OLD RELIABLE" IN WOOD PRESERVATIVES.

<b>COVERAGE — Per Gallon</b>	
If brushing or mopping	200 sq. ft. approx.
If spraying	100 sq. ft. approx.
If dipping (butt-treatment)	20 ave. size posts

## WARNING: KEEP OUT OF REACH OF CHILDREN

See WARNINGS on other panel!

NET CONTENTS ONE GALLON

MANUFACTURED BY

### STANDARD TAR PRODUCTS CO.

2456 West Cornell St. Milwaukee, Wis. 53209

# A LIFE SAVER FOR ALL WOOD

## EASY TO APPLY

97%

3%

## OUT OF REACH OF CHILDREN

Additional warnings.

ONE GALLON

MANUFACTURED BY

**STANDARD TAR PRODUCTS CO.**

Milwaukee, Wis. 53209

Or, for best penetration and longest life, soak wood.

### TO BRUSH OR MOP

Flow USOL Creosote Oil on liberally, especially at cracks, cut surfaces and joints. Two or three applications should be made to all wood which will contact the soil.

### TO SPRAY

Apply two or three coats for best protection. Warming oil will make spraying easier.

### TO DIP

Soak for a minimum of five minutes — preferably 15. Posts and heavy building timbers should be soaked for 12 to 48 hours.

NOTE: Oil will always run freely if kept in warm room.

# OIL

# A LIFE SAVER FOR ALL WOOD

## FEATURES

- **PENETRATING** — Soaks in deeply. Dries clean and leaves no sticky surface.
- **LASTING** — Stays in wood and remains effective for years. Insoluble in water. Surfaces will not crack, peel, blister or flake. Cannot be rubbed or scraped off.
- **ECONOMICAL** — Increases life of wood, saving repairs and replacement.
- **CONVENIENT** — No stirring or mixing. Ready for immediate use. Wood can be treated by coating or soaking.
- **ATTRACTIVE** — A nut brown color for all types of buildings.

### THE "OLD RELIABLE" IN WOOD PRESERVATIVES.

**COVERAGE — Per Gallon**  
 If brushing or mopping ..... 200 sq. ft. approx.  
 If spraying ..... 100 sq. ft. approx.  
 If dipping (butt-treatment) ..... 20 ave. size posts

## WARNING: KEEP OUT OF REACH OF CHILDREN

See WARNINGS on other panel!

NET CONTENTS ONE GALLON

MANUFACTURED BY

**STANDARD TAR PRODUCTS CO.**

2456 West Cornell St. Milwaukee, Wis. 53209



CUSTOMER <b>MIDWAY CAN CO.</b>	DESIGN <b>USOL CREOSOTE OIL</b>	ART NO <b>SA 4399</b>	LITHO REG. NO <b>A-7448</b>	DESIGN NO <b>CD-1-35-1536</b>																																		
<b>GALLON "F" INSIDE SOLDER</b>	<b>CUT EDGE/20.260" x 9.562"</b>	ARTIST <b>W.D.N.</b>	CHECKED BY <b>B.N.</b>	DATE <b>9-14-72</b>																																		
COLOR SEQUENCE <b>YELLOW BASE, RED &amp; BLACK PRINTS &amp; VARNISH</b>		<table border="1"> <thead> <tr> <th rowspan="2">MARK "OK" AFTER EACH APPROVED ITEM</th> <th colspan="6">REVISIONS</th> </tr> <tr> <th>REVS'D</th> <th>OK</th> <th>DATE</th> <th>REVS'D</th> <th>OK</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td><b>DESIGN</b></td> <td></td> <td></td> <td></td> <td><b>NEW BLACK ONLY</b></td> <td><b>2/21/73</b></td> <td></td> </tr> <tr> <td><b>COPY</b></td> <td></td> <td></td> <td></td> <td><b>NEW BLACK ONLY</b></td> <td><b>2/26/73</b></td> <td></td> </tr> <tr> <td><b>LEGAL</b></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td><b>GD-1-351536A</b></td> </tr> </tbody> </table>			MARK "OK" AFTER EACH APPROVED ITEM	REVISIONS						REVS'D	OK	DATE	REVS'D	OK	DATE	<b>DESIGN</b>				<b>NEW BLACK ONLY</b>	<b>2/21/73</b>		<b>COPY</b>				<b>NEW BLACK ONLY</b>	<b>2/26/73</b>		<b>LEGAL</b>						<b>GD-1-351536A</b>
MARK "OK" AFTER EACH APPROVED ITEM	REVISIONS																																					
	REVS'D	OK	DATE	REVS'D	OK	DATE																																
<b>DESIGN</b>				<b>NEW BLACK ONLY</b>	<b>2/21/73</b>																																	
<b>COPY</b>				<b>NEW BLACK ONLY</b>	<b>2/26/73</b>																																	
<b>LEGAL</b>						<b>GD-1-351536A</b>																																
<p><small>CUSTOMER: Please review the sketch, engraving, or black and white proofs. All items that are applied on same. Sketches, engraving and negative for proofs furnished by us remain the property of The Sherwin Williams Company, Cincinnati, Ohio, and it will not be responsible for the return of proofs with your signature for any reason. If you require necessary corrections, contact us. By returning proofs, you are authorizing us to reproduce them from the original design. The undersigned customer holds The Sherwin Williams Company harmless for all damages or claims that may be made against it for compliance with Local, State or Federal Laws and regulations, or for conflict with rights of third parties in connection with trademarks, designs, labels, copyrights, patents, or unfair competition. Allowances must be made for variations in colors on sketches and color proofs since colors cannot always be exactly reproduced. Reasonable allowances must be made for normal variation in color when lithographing design. Changes are to be made by written memorandum only. In case of sketches do not make changes by marking, defacing, mutilating or cutting up sketches.</small></p>		<p>PLEASE SIGN HERE WHEN JOB IS APPROVED</p> <p>DATE</p>																																				