

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS
WARNING**

• May be fatal if swallowed or absorbed through skin • Causes skin irritation • Do not breathe vapor or spray mist • Do not get in eyes, on skin, or on clothing • Wear rubber gloves and protective clothing when handling the freshly treated lumber • Wash thoroughly after handling.

Keep away from children, domestic animals, and food stuffs.

STATEMENT OF PRACTICAL TREATMENT

In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention.

If swallowed, call physician immediately. Do not induce vomiting.

If inhaled, remove to fresh air.

For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse.

NOTE TO PHYSICIAN: Pentachlorophenol in this product is a metabolic stimulant. Treat symptomatically.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL AND CHEMICAL HAZARDS

Do not use near open flame.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For Outdoor Use Only.

For non-paintable application

**BEFORE USING DILUTE WITH 10 PARTS
OF LIGHT FUEL OIL OR KEROSENE.**

TO STOP WOOD ROT

Wood should be dry, unpainted, well seasoned and bark free.
COATING: Apply two or three drenching coats with a mop, sprinkling can or brush.

DIPPING: Soak five minutes or more for each inch of thickness. Wood which will contact the ground should be soaked at least half an hour. Posts, poles and timbers should soak for 24 to 48 hours.

TO KILL TERMITES

Remove all wood scraps, saw dust, chips, and refuse under and around infested buildings.

Saturate ground thoroughly, using a sprinkling can. Replace all infested timbers with new ones.

Soak new timbers in USOL PENTA Concentrate for two hours. Also apply two or three drenching coats to all uninfested wood.



E.P.A. Reg. No. 458-16
E.P.A. Est. No. 458-WI-1



TEN-TO-ONE CONCENTRATE

**STOPS WOOD ROT, DECAY,
AND KILLS TERMITES**

1 Gallon Makes 11 Gallons

For wood protection above and below ground

ACTIVE INGREDIENTS:

Pentachlorophenol*	36.98%
Other Chlorophenols and related compounds	4.30%

INERT INGREDIENTS:

Petroleum Solvents	58.72%
--------------------	--------

TOTAL 100.00%

*As defined by Fed. Spec. TT-W-570

WARNING: KEEP OUT OF REACH OF CHILDREN

See side panel for additional precautionary statements

NET CONTENTS ONE GALLON

MANUFACTURED BY

STANDARD TAR PRODUCTS CO.

2456 West Cornell St. Milwaukee, Wis. 53209

DIRECTIONS FOR USE (CONT'D)

SUBTERRANEAN TERMITES

**DIRECTIONS FOR
HOMEOWNER USE**

TERMITE CONTROL IN EXISTING STRUCTURES
Buildings with Basements or Crawl-Spaces

First remove all wood debris and wood forms. Around piers, pipes, chimney bases and along foundations of poured concrete, dig a trench 6 inches wide and 4 inches deep. For brick and block foundations, dig the trench about 12 inches deep. If footing is more than 12 inches deep, make holes with a crowbar, pipe or a rod about one foot apart, that extend from the trench bottom to the top of the footing. Make holes closer in hard-packed clay soils. NEVER DIG BELOW THE TOP OF THE FOOTING. Apply the emulsion (or solution) in the trench at a rate of 4 gallons per 10 linear feet per foot of depth. Apply half of this to the back-fill. Likewise, treat along the inside of foundations of crawl-space buildings. Cover treated soil with a thin layer of untreated soil.

For raised porches, terraces, and entrance slabs, drill holes at one foot intervals, 6 inches from the foundation, and pour one-half gallon of emulsion (or solution) into each hole. Refill holes. Slabs with heat ducts or radiating heat pipes should be treated by commercial pest control operator.

The object is to establish a treated soil barrier which will prevent termite entry. Other critical areas may also require treatment, particularly if there are inaccessible areas, basements of slab-type construction. It is suggested that you contact the Agricultural Cooperative Extension Service for advice or consult a Commercial Pest Control Service.

Avoid contamination of public and private water supplies by following these precautions. Do not allow a hose or any type of faucet extension to reach into the termite chemical solution while filling or mixing this material with water. Use anti-back-flow or anti-siphonage equipment on all fitting equipment. These devices can be purchased at hardware or plumbing supply stores. Use of anti-back-flow equipment will help to insure that the user of this toxic chemical will not contaminate domestic water supplies. Refer to Federal, (Federal Housing Administration), state, and local specifications for safe distances of treatment areas from wells. Soil in the vicinity of wells, cisterns, or ponds should not be treated if it is water saturated, subject to excessive saturation, due to an accumulation of water or if the soil to be treated around the perimeter of the structure is at a grade lower than surrounding yard or property area. If this is the situation, treat as follows: **DO NOT APPLY UNDER PRESSURE.** Soil should be removed to an area safe from well or domestic water contamination, treated, allowed to stand undisturbed for two to four hours, then returned to the trench which has been lined with a 4 mil plastic sheeting. Be careful not to puncture the plastic sheeting when returning soil to the trench. Do not treat structures that contain cisterns or wells.

KEEP FROM FREEZING

**DISPOSAL • DO NOT REUSE EMPTY
CONTAINER • WRAP CONTAINER
AND PUT IT IN TRASH COLLECTION.**

Subject to proper handling and storage, this product is warranted to be of merchantable quality and there are no warranties which extend beyond the descriptions hereon. Liability is limited to replacing or giving credit for the purchase price. Manufacturer shall not be liable for any special or consequential damages.



TEN-TO-ONE CONCENTRATE

- PROVIDES PROTECTION from decay for wood in contact with the soil — fence posts, gate posts, corral posts, barn timbers, and the like.
- PREVENTS ATTACK by termites and other wood-boring insects.
- GIVES CLEAN, PAINTABLE SURFACE when diluted with paint thinner — for protection of wood above ground.

For NON-PAINTABLE APPLICATION:

Dilute with light fuel oil or kerosene. See "Directions" to apply.

Follow directions for paintable application, but use only on wood surfaces that will not be in contact with the ground. Allow treated surfaces to dry three or four days before painting.

For PAINTABLE APPLICATION:

Dilute one gallon of Concentrate with 10 gallons of paint thinner.

COVERAGE


Dilute solution applied to rough timber. (Coverage varies according to species and condition of wood.)

One brush or spray coat	100 sq. ft. approx.
Two dippings	75 sq. ft. approx.

WARNING: KEEP OUT OF REACH OF CHILDREN

See WARNINGS on other panel!

NET CONTENTS ONE GALLON



MANUFACTURED BY

STANDARD TAR PRODUCTS CO.

2456 West Cornell St. Milwaukee, Wis. 53209

ACCEPTED

MAR 17 1983

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the sale of this product.

45-16

CD4