

EPA Reg. No. 458-

EPA Est. No. 458-WI-1

COPPER GREEN™

PRESERVATIVE FOR WOOD

STOPS WOOD ROT, DECAY, MILDEW  
AND TERMITE ATTACK

PAINTABLE . READY TO USE

To Protect Wood Used Above Ground  
And Below Ground  
Or In Contact With Water.

## ACTIVE INGREDIENT:

Copper Naphthenate . . . . . 19.3% Minimum  
(equivalent to 2% metallic copper)

INERT INGREDIENTS: . . . . . 80.7% Maximum

Total 100.0%

WARNING: Keep out of reach of children


See side panel for additional  
precautionary statements

NET CONTENTS

Manufactured by

STANDARD TAR PRODUCTS CO., INC.

2456 West Cornell St. Milwaukee, WI 53209



## HAZARDS TO HUMANS AND DOMESTIC ANIMALS

### WARNING

Harmful if swallowed, inhaled or absorbed through skin. Causes eye and skin irritation. Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. Wear goggles, rubber gloves and protective clothing when applying or handling the freshly treated lumber. Wash thoroughly after handling.

Keep out of reach of children

### STATEMENT OF PRACTICAL TREATMENT

In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention.

If swallowed, call physician immediately. Do not induce vomiting.

If inhaled, remove to fresh air.

For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse.

### ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

### PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame. Use with adequate ventilation.

Do not use or store inside the home.

### DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For Outdoor Use Only.

Use as received without dilution.

Shake Well Before Using.

TO STOP WOOD ROT, DECAY AND MILDEW

Wood should be dry, unpainted, well seasoned and bark free.

COATING: Apply two or three drenching coats with a mop, sprinkling can or brush. Allow at least one hour between applications.

DIPPING: Soak five minutes or more for each inch of thickness of wood. Posts, poles and timbers should soak 24 to 48 hours.

Allow treated surface to dry (usually all solvent is gone in 24 hours) before painting or varnishing.

Oil or alkyd stains or paints can be applied after an overnight dry, but the green may bleed through lighter colors. Do not over coat with latex paint or clear finishes until thoroughly cured (6 to 12 months).

Do not apply over painted or varnished surfaces.

Do not apply over bark.

### STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage or disposal. Keep closures tight and upright to prevent leakage. Soak up spills or leaks with sand, dirt or synthetic absorbent and remove to container.

DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL: Triple rinse (or equivalent) and offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by State and local authorities.

COPPER GREEN<sup>TM</sup>  
PRESERVATIVE FOR WOOD



- . PROVIDES PROTECTION for years from decay for wood in contact with soil - fence posts, gate posts, corral posts, barn timbers and the like. Can also be used on wood surfaces in contact with soil, concrete or water including Foundation, sills, docks and boats.
- . PREVENTS ATTACK by termites and other wood-boring insects. Powder post beetles are killed by application of this preservative
- . PENETRATING solution soaks in deeply, dries clean and leaves no sticky surfaces.
- . LASTING protection. Stays in wood and remains effective for years. Will not leach from wood.
- . ECONOMICAL to use. Increases life of wood. Saves repairs and replacements.
- . CONVENIENT to use. No stirring or mixing. Ready for immediate use. Wood can be treated by coating or soaking.

APPROXIMATE COVERAGE

Depending upon method of application and porosity, texture and dryness of wood:  
200-400 square feet per gallon.

CLEAN UP

Rinse brushes and equipment with water immediately after completion of jobs for fast clean up. Soap and water may be necessary if product begins to dry and becomes sticky on brushes.

KEEP FROM FREEZING

Subject to proper handling and storage, this product is warranted to be of merchantable quality and there are no warranties which extend beyond the descriptions hereon. Liability is limited to replacing or giving credit for the purchase price. Manufacturer shall not be liable for any special or consequential damages.