
452-,21



EPA Reg. No. 458-EO EPA Est. No. 452-WI-1

 $\operatorname{organisol}^{\operatorname{TM}}$ TWENTY-TO-ONE CONCENTRATE

STOPS WOOD ROT, DECAY, MILDEW AND PREVENTS TERMITE ATTACK



Under the Federal Insecticide, Fundation, and Redenticide Act, ds amanded, for the pasticide ristered under PA Reg. No.

To Protect Wood Used Above Ground And Below Ground

ACTIVE INGREDIENTS:

Methylene bis (thiocyanate)	10.0 % MIN. 10.0 % MIN.
INERT INGREDIENTS:	80.0 % MAX.
TOTAL	100,0 %

DANGER : Keep out of reach of children

See side panel for additional precautionary statements

NET CONTENTS

Manufactured by STANDARD TAR PRODUCTS CO., INC. 2456 West Cornell St. Milwaukee, WI 53209



ORGANISOLTM

TWENTY-TO-ONE CONCENTRATE

. PROVIDES PROTECTION for wood in contact with the soil - fence posts, gate posts, corral posts, barn timbers and the like. It also protects from decay, mildew and rotting for wooden flooring, for decks and patios, ladders, doors, window frames and sashes, stakes and small dimensional lumber, wooden siding and shingles.

. PREVENTS ATTACK by termites and other woodboring insects.

. GIVES CLEAN, PAINTABLE SURFACE for protection of wood above ground.

. PENETRATING solution soaks in deeply, dries clear and leaves no sticky surfaces. Will not leach from wood.

ORGANISOL 20-1 Concentrate is easily diluted with petroleum solvents such as paint thinner or mineral spirits. For NCN-PAINTABLE APPLICATIONS, use light fuel oil or kerosene.

To obtain various final treating solution concentrations, use the following dilution table:

For	1.0%,	add.	99.0	gallons	to	one	gallon	Concentrate
For	2.0%,	add	49.0	gallons	to	one	gallon	Concentrate
For	3.0%,	add	32.3	gallons	to	one	gallon	Concentrate
For	4.0%,	add	24.0	gallons	to	one	gallon	Concentrate
For	5.0%,	add	19.0	gallons	to	one	gallon	Concentrate

CLEAN UP

Rinse brushes and equipment with mineral spirits after completion of jobs for fast clean up.

KEEP FROM FREEZING

IMPORTANT NOTICE TO BUYER: Neither manufacturer nor seller makes any representation of warranty, expressed or implied, concerning this material, other than indicated on the label. Neither shall be held reponsible in any manner for any personal injury, property damange or other type of loss resulting from the improper handling, storage and use of this material. See label directions. The buyer accepts and uses this material under these conditions.

Manufacturer will refund the purchase price or replace this product, if within one year of the date of purchase, it is shown to be defective Manufacturer's liability under any warranty, whether expressed or implied, is limited to one year from date of purchase and does not include any labor, incidential or consequented damanges or losses.

DOMESTIC ANIMALS

DANGER

Corrosive, causes irreversible eye damage and skin damage. Harmful if swallowed, inhaled or absorbed through skin · Causes eye and skin irritation· Use only in well ventilated area · Do not breathe vapor or spray mist · Do not get in eyes, on skin, or on clothing Wear goggles, face shield or safety glasses, rubber gloves and protective clothing when handling · Wash thoroughly with scap and water after handling.

Keep out of reach of children

STATEMENT OF PRACTICAL TREATMENT

In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention.

If swallowed, call physician immediately. Do not induce vomiting.

If inhaled, remove to fresh air.

For skin contact, wash thoroughly with soap and water. Remove contaminated clothing and shoes. Wash clothes before reuse.

ENVIROMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL AND CHEMICAL HAZARDS

Do not use or store near heat or open flame. Use with adequate ventilation. Do not use or store inside the home.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For Outdoor Use Only.

Shake Well Before Using,

TO STOP WOOD ROT, DECAY AND MILPEW Wood should be dry, unpainted, will seasoned and bark free. sprinkling can or brush. DIPPING: Soak five minutes or more for each inch of thickness of wood. Posts, poles and timbers should soak 24 to 48 hours.

Allow treated surface to dry (Usually all solvent is gone in 24 hours) before painting or varnishing.

Can be painted over when thoroughl dry.

For best results, dilute Concentrate to obtain final treating solution percentages. Percentages are on a volume basis. For lumber to be used above ground but sheltered from rain and sun, a 1.0% to 2.0% solution will provide necessary protection. For all exterior uses where rain and sunlight will be a factor, 2.0% to 3.0% should be applied when the dip treatment is used. Suggested dosage for below ground use is a treating solution of 3.0% to 5.0%

STORAGE AND DISPOSAL

DO NOT USE OR STORE INSIDE THE HOME. DO NOT REUSE EMPTY CONTAINER. KEEP AWAY FROM FOOD AND FEED. KEEP CLO-SURES TIGHT AND UPRIGHT TO PREVENT LEAKAGE. SOAK UP SPILLS OR LEAKS WITH SAND, DIRT OR SYNTHETIC ABSORBENT AND REMOVE TO CONTAINER. DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL. PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE, OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST E.P.A. **REGIONAL OFFICE FOR GUIDANCE.** HOMEOWNER USE: SECURELY WRAP ORIG-INAL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISCARD'IN TRASH. INDUSTRIAL USE: WASTES RESULTING FROM THE USE OF THIS PRODUCT MAY OF DISPOSED OF ON SITE OR AT AN APPROYEO WASTE DISPOSAL FACILITY TRIPLE RINSE (OR EQUIVALENT). THEN OFFER FOR RECYCLING OR RECONDITIONS ING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER PROCEDURES APPROVED BY GTATE AND LOCAL AUTHORITIES.